

AIR PRODUCTS AND CHEMICALS, INC. -- ACETYLENE, ETHYNE, ETHINE -- 6830-00-337-0389

=====  
Product Identification  
=====

Product ID:ACETYLENE, ETHYNE, ETHINE

MSDS Date:07/10/1986

FSC:6830

NIIN:00-337-0389

MSDS Number: BHDLJ

=== Responsible Party ===

Company Name:AIR PRODUCTS AND CHEMICALS, INC.

Box:538

City:ALLENTOWN

State:PA

ZIP:18105

Country:US

Info Phone Num:215-481-4911

Emergency Phone Num:1-800-5

23-9374 IN PA:1-800-322-9092

CAGE:00742

=== Contractor Identification ===

Company Name:AIR PRODUCTS AND CHEMICALS INC

Address:7201 HAMILTON BLVD

Box:City:ALLENTOWN

State:PA

ZIP:18195-1501

Country:US

Phone:800-345-3148/ 800-752-1597

CAGE:00742

Company Name:OXYGEN SALES AND SERVICE INC

Address:2043 S 35TH ST

Box:11393

City:TACOMA

State:WA

ZIP:98411-0393

Country:US

CAGE:5H199

=====  
Composition/Information on Ingredients  
=====

Ingred Name:ACETYLENE

CAS:74-86-2

=====

==== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACETYLENE IS A SIMPLE

ASPHYXIANT,IRRITANT, & ANESTHETIC. ABOUT 100 MG PER LITER MAY BE TOLERATED FOR 0.5-1.0 HOUR. THERE IS NO EXPERIMENTAL EVIDENCE OF CHRONIC HARMFUL EFFECTS.

Explanation of Carcinogenicity:ACETYLENE IS CLASSIFIED AS A SIMPLE ASPHYXIANT & HAS NO TLV.

Effects of Overexposu

re:HEADACHES, DIZZINESS, SHORTNESS OF BREATH, &

LOSS OF CONSCIOUSNESS MAY OCCUR IF THE GAS IS PRESENT IN QUANTITIES SUFFICIENT TO DILUTE THE OXYGEN CONCENTRATION IN AIR.SYMPTOMS OF ANOXIA OCCUR ONLY WHE N THE GAS CONCENTRATIONS ARE WITHIN THEFLAMMABLE RANGE & THE MIXTURE HAS NOT IGNITED.

=====  
===== First Aid Measures =====

First Aid:FIRST/SECOND (MINOR) THERMAL BURNS FROM FIRES SHOULD BE IMMERSUED IN COOL WATER FOR 30 MINUTES. MAJOR SECOND/THIRD DEG

BURNS SHOULD BE COVERED IN THE CLEANEST MATERIAL AVAILABLE. PERSONS SUFFERING FR OM LACK OF OXYGEN SHOULD BE MOVED TOFRESH AIR, ASSISTED RESPIRATION & SUPPLEMENTAL OXYGEN SHOULD BE GIVEN IF THE VICTIM IS NOT BREATHING. SEEK IMMEDIATE AID OF A PHYSICIAN.

=====  
===== Fire Fighting Measures =====

Flash Point Method:CC

Flash Point:OF/-18C

Autoignition Temp:Autoignition Temp Text:\*\*

Lower Limits:2.5

Upper Limits:100

Extinguishing Media:CARBO

N DIOXIDE, DRY CHEMICAL, HALON

Fire Fighting Procedures:USE WATER SPRAY TO KEEP CYLINDERS/CONTAINERS COOL IF EXPOSED TO FIRE. KEEP PERSONNEL AWAY SINCE CONTAINERS CAN RUPTURE VIOLENTLY WHEN EXPOSED TO FIRE.

Unusual Fire/Explosion Hazard:ACETYLENE IS EXTREMELY

FLAMMABLE/EXPLOSIVE & BURNS WITH AN INTENSELY HOT FLAME. CAN REIGNITE IF FIRE IS EXTINGUISHED W/O SHUTTING OFF ACETYLENE SOURCE.

=====  
===== Accidental Release Measures =====

Spill Release Procedures:

VENTILATE AREA TO PREVENT FLAMMABLE MIXTURE FROM FORMING. REMOVE SOURCES OF IGNITION,HEAT,SPARKS, ETC. CAREFULLY REMOVE CYLINDERS W/SLOW LEAKS TO A REMOTE OUTDOOR LOCATION. CONTACT AIR PRODUCTS FOR ASSISTANCE.AVOID ENTERING AREA W/FLAMMABLE ATMOS.

===== Handling and Storage =====

Handling and Storage Precautions:USE A SUITABLE HANDTRUCK FOR MOVEMENT.STORAGE SHOULD NOT BE IN HEAVY TRAFFIC AREAS TO PREVENT DAMAGE. KEEP CYLINDERS AWAY FROM SOURCES OF HEAT.

Other Precautions:SEGREGATE FULL/EMPTY CYLINDERS. AVOID DRAGGING,ROLLING, OR SLIDING CYLINDERS. CYLINDERS SHOULD BE UPRIGHT & SECURED WHEN IN USE. STORAGE OF 2500CU.FT. OR LESS IS PERMISSIBLE W/IN BUILDING,IN EXCESS OF 2500CU.FT. MUST BE STORED OUTDOORS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:OXYGEN DEFICIENT ATMOSPHERES ARE IN THE FLAMMABLE RANGE. DO NOT ENTER!! RESPIRATORS WILL NOT FUNCTION.

Ventilation:NATURAL OR MECHANICAL WHERE GAS IS PRESENT.

Protective Gloves:LEATHER GLOVES/WELDERS GLOVES

Eye Protection:SAFETY GLASSES/WELDERS GOGGLES

Other Protective Equipment:LEATHER SLEEVES,LEATHER APRON,OTHER STANDARD PROTECTIVE EQUIPMENT.

Supplemental Safety and Health

NK

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:\*SEE BELOW

Vapor Pres:590 PSIA

Vapor Density:0.0681

Spec Gravity:1 ATM .906

Solubility in Water:1 ATM 1.0

Appearance a

nd Odor:PURE: COLORLESS, ODORLESS IMPURITIES: GARLIC  
LIKE ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:NO

OXIDIZER AS OXYGEN,HALOGENS.FORMS EXPLOSIVE COMPOUNDS WITH  
COPPER,BRASS,COPPER SALT,HG/HG SALTS, K, AG/AG SALTS, & HNO3

Stability Condition to Avoid:AVOID MECH. SHOCKS TO CONTAINERS OF  
ACETYLENE.NEVER UTILIZE FREE GAS OUTSIDE THE CYLINDER AT PRESS IN  
EXCESS OF 15 PSIG.

Hazardous Decomposition Products:ACE

TYLENE WILL DECOMPOSE INTO

ELEMENTAL CARBON & HYDROGEN UNDER THE ABOVE CONDITIONS.

===== Disposal Considerations =====

Waste Disposal Methods:DO NOT ATTEMPT TO DISPOSE OF RESIDUAL GASEOUS  
ACETYLENE IN CYLINDERS. RETURN TO AIR PRODUCTS FORDISPOSAL.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whats  
oever,

expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.