

DIAL CORP THE -- EA 956 PART B -- 8040-00-463-7042

===== Product Identification =====

Product ID:EA 956 PART B
MSDS Date:01/10/1989
FSC:8040
NIIN:00-463-7042
Kit Part:Y
MSDS Number: BHDLY
=== Responsible Party ===
Company Name:DIAL CORP THE
Address:1865 DIAL TOWER
Box:312
City:PHOENIX
State:AZ
ZIP:85077-1865
Country:US

Info Phone Num:602-991-3000
Emergency Phone Num:602-991-3000

CAGE:0EK45

=== Co

ntractor Identification ===

Company Name:DEXTER CORPORATION ADHESIVE & COATING SYSTEMS

Address:2850 WILLOW PASS ROAD

Box:312

City:BAY POINT

State:CA

ZIP:94565-3299

Country:US

Phone:202-483-7616

CAGE:33564

Company Name:DIAL CORP THE

Address:111 W CLARENDON AVE

Box:3223

City:PHOENIX

State:AZ

ZIP:85077

Country:US

Phone:602-991-3000

CAGE:0EK45

===== Composition/Information on Ingredients =====

Ingred Name:DIETHYLENE TRIAMINE

CAS:111-40-0

RTECS #:IE1225000

Fraction by Wt: 300F

Ext

inguishing Media: DRY CHEMICAL OR HALON FIRE EXTINGUISHER, OR WATER
SPRAY, FOAM OR FOG.

Fire Fighting Procedures: USE SELF-CONTAINED BREATHING APPARATUS WHEN
FIGHTING FIRES IN CONFINED AREAS.

Unusual Fire/Explosion Hazard: DENSE SMOKE AND TOXIC GASSES MAY BE
LIBERATED.

===== Accidental Release Measures =====

Spill Release Procedures: WEAR PROTECTIVE CLOTHING, GLOVES AND SAFETY
GLASSES. COVER WITH ABSORBENT MATERIAL, THEN SCRAPE UP AND
TRANS
FER TO METAL CONTAINER. WIPE UP REMAINING RESIDUE WITH SOLVENTS
OBSERVING SOLVENT FLAMMABILITY CAUTIONS OR USE DETERGENT.

===== Handling and Storage =====

Handling and Storage Precautions: KEEP PRODUCT COOL IN ACCORDANCE WITH
LABEL INSTRUCTIONS.

Other Precautions: FOLLOW RECOMMENDED CURING SCHEDULE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection: NOT REQUIRED WITH GOOD INDUSTRIAL VENTILATION.

Ventilation: LOCAL

EXHAUST RECOMMENDED. MECHANICAL RECOMMENDED.

Protective Gloves: IMPERVIOUS PLASTIC OR RUBBER.

Eye Protection: SAFETY GLASSES OR GOGGLES.

Other Protective Equipment: AS NEEDED TO PROTECT SKIN AND CLOTHING.

Work Hygienic Practices: WASH WITH SOAP AND WATER.

Supplemental Safety and Health

KEY 1: C2. KIT CONSISTS OF TWO PARTS. SEE PNI C FOR OTHER PART.

===== Physical/Chemical Properties =====

HCC: B2

Boiling Pt: B.P. Text: 405F

Vapor Pres: 0.37MM HG

Vapor Density: 3.48, AIR=1

Sp

ec Gravity:0.951, H2O=1

Evaporation Rate & Reference:LOW

Solubility in Water:100%

Appearance and Odor:AMBER LIQUID WITH AMMONIACAL ODOR.

Percent Volatiles by Volume:LOW

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS, STRONG LEWIS OR MINERAL ACIDS.

Hazardous Decomposition Products:CO, NOX, ALDEHYDES, ACIDS AND
UNDETERMINED ORGANICS.

Conditions to Avoid Polymerization:AVOID MIXING RESIN/CURING AGENT I
N

BATCHES > 1 LB TOTAL. DO NOT HEAT MIXED ADHESIVE >75F UNLESS CURING
SURFACES BONDED.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF AS HAZARDOUS WASTE ACCORDING TO
D.O.T. HAZARD CLASS. IF NOT REGULATED BY D.O.T., DISPOSE OF AS
ORM-E. DISPOSAL METHOD CAN BE LAND BURIAL ORCHEMICAL INCINERATION
AS REGULATED BY ALL GOVERNMENTAL AGENCIES.

Disclaimer (provided with this information by the compiling agencies):

This info

rmation is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.