

KALCOR COATINGS COMPANY -- SANDING SEALER CLEAR ID 272-0190F -- 8010-00-663-2673
===== Product Identification =====

Product ID:SANDING SEALER CLEAR ID 272-0190F

MSDS Date:03/20/1986

FSC:8010

NIIN:00-663-2673

MSDS Number: BHDS

=== Responsible Party ===

Company Name:KALCOR COATINGS COMPANY

Address:37721 STEVENS BLVD

Box:NA

City:WILLOUGHBY

State:OH

ZIP:44094

Country:US

Info Phone Num:216-94

6-4700

Emergency Phone Num:216-381-5614

CAGE:DO396

=== Contractor Identification ===

Company Name:KALCOR COATING CO

Address:37721 STEVENS BLVD

Box:City:WILLOUGHBY

State:OH

ZIP:44094-6231

Country:US

Phone:216-946-4700

CAGE:33201

Company Name:KALCOR COATINGS COMPANY

Address:37721 STEVENS BLVD

City:WILLOUGHBY

State:OH

ZIP:44094

Phone:800-424-9300 CHEMTREC

CAGE:DO396

===== Composition/Information on Ingredients =====

Ingred Name:N-HEPTANE

CAS:142-82-5

RTECS #:MI7700000

Fraction b

y Wt: 20%
OSHA PEL:500 PPM/500 STEL
ACGIH TLV:400 PPM/500STEL;9293

Ingred Name:N-BUTYL ACETATE (SARA III)
CAS:123-86-4
RTECS #:AF7350000
Fraction by Wt: 20%
OSHA PEL:150 PPM/200 STEL
ACGIH TLV:150 PPM/200STEL;9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:METHYL ISOBUTYL KETONE (SARA III)
CAS:108-10-1
RTECS #:SA9275000
Fraction by Wt: 10%
OSHA PEL:100 PPM/75 STEL
ACGIH TLV:50 PPM/75 STEL; 9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:ISOPROPYL ALCOHOL (SARA III)
CA
S:67-63-0
RTECS #:NT8050000
Fraction by Wt: 10%
OSHA PEL:400 PPM/500 STEL
ACGIH TLV:400 PPM/500STEL;9192

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)
CAS:1330-20-7
RTECS #:ZE2100000
Fraction by Wt: 5%
OSHA PEL:100 PPM/150 STEL
ACGIH TLV:100 PPM/150STEL;9192
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:TOLUENE (SARA III)
CAS:108-88-3
RTECS #:XS5250000
Fraction by Wt: 5%
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:METHYL

ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS:78-93-3

RTECS #:EL6475000

Fraction by Wt: < 5%

OSHA PEL:200 PPM/300 STEL

ACGIH TLV:200 PPM/300STEL 9192

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:DIOCTYL PHTHALATE

VAPOR PRESS 1.2/200C MM HG @ 20C

CAS:117-84-7

Fraction by Wt: 1%

OSHA PEL:5 PPM

ACGIH TLV:5 PPM

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

=====
First Aid

Measures =====

First Aid:INHALATION: REMOVE TO FRESH AIR. RESTORE BREATHING.TREAT SYMPTOMATICALLY.CONSULTA PHYSICIAN. EYES:FLUSH IMMEDIATELY W/LARGE AMOUNTS OF WATER FOR 15 MINUTES.TAKETO PHYSICIAN FOR TREATMENT. SKIN: WASH A FFECTED AREAS W/SOAP AND WATER. REMOVECONTAMINATED CLOTHING.CONSULT A PHYSICIAN IF IRRITATION PERSISTS.INGESTION:DRINK1-2 GLASSES OF WATER TO DILUTE.DONOT INDUCE VOMITING. CONSULT A PHYSICIAN.

=====
Fire Fightin

g Measures =====

Flash Point:AIR

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:85.5

=====
Stability and Reactivity Data
=====

Stability Indicator/Materials to Avoid:YES

NONE REASONABLY FORESEEABLE

=====
Disposal Considerations
=====

Waste Disposal Methods:DISPOSAL MUST BE DONE IN ACCORDANCE W/FEDERAL, LOCAL,& STATE REGULATIONS.BEFORE ATTEMPTING CLEAN UP REFER TO HAZARD CAUT

ION INFORMATION IN OTHER SECTIONS OF THE SHEET.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.