View NSN Online: https://aerobasegroup.de/nsn/7930-00-721-8873

INDUSTRIAL FLOOR FINISHES -- LIQUID POLISH -- 7930-00-721-8873

Product ID:LIQUID POLISH MSDS Date:05/01/1987 FSC:7930 NIIN:00-721-8873 MSDS Number: BHDTF === Responsible Party === Company Name: INDUSTRIAL FLOOR FINISHES Address:605 SPRING STREET City:BEDFORD State:MA ZIP:01730 Country:US Emergency Phone Num:(617) 667-5161 Preparer's Name: T. PITROL FFYO CAGE:INDUS === Contractor Identification === Company Name: INDUSTRIAL FLOOR FINISHES Address:605 SPRINGS RD City:BEDFORD State:MA ZIP:01730 Country:US Phone:1-617-667-5161 CAGE:INDUS Company Name: PEMATEX INDUSTRIAL CORPORATION Address:30 TOWER LANE, AVON PARK SOUTH Box:City:AVON State:CT ZIP:06001 CAGE:PERMA

Ingred Name:STODDARD SOLVENT CAS:8052-41-3 RTECS #:WJ8924000 Fraction by Wt: 17% OSHA PEL:500 PPM ACGIH TLV:100 PPM; 9293

=======

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:PRIMARY EYE/SKIN IRRITANT WITH CONTACT. INHALATION: HEADACHE, DIZZINESS & NAUSEACHRONIC: NOT SUFFICIENT DATA, EXERCISE CARE, DO NOT USE ABOVE TLV Effects of Overexposure:NK PRIMARY EYE/SKIN IRRITANT WITH CONTACT. INHALATION: HEADACHE, DIZZINGESS & NAUSEA CHRONIC: NOT SUFFICIENT DATA, EXERCISE CARE, DO NOT USE ABOVE TLV First Aid:EYE CONTACT: FLUSH WITH WATER, SKIN: WASH WITH SOAP & WATER, APPLY SKIN CREAM. INHALATION: REMOVE TO FRESH AIR, RESTORE BREATHING, CALL PHYSICIAN. INGESTION: DRINK WATER OR MILK, DO NOT INDUCE VOMIT ING. CALL POISON CONTROL Flash Point Method:TCC Flash Point:MIN 104F 40. 00C Lower Limits:0.8 Upper Limits:6.0 Extinguishing Media: FOAM, CO2, DRY CHEMICAL, WATER FOG Fire Fighting Procedures:WATER MAY BE USED TO COOL CONTAINERS TO PREVENT PRESSURE BUILD-UP OR AUTO-IGNI- TION Unusual Fire/Explosion Hazard: ISOLATE FROM HEAT, CLOSED CONTAINERS MAY EXPLODE IF EXPOSED TO EXTREME HEAT Spill Release Procedures: REMOVE SOURCES OF IGNITION, SPRINKLE WITH ABSORB- ENT. FOG WITH WATER FLUSH/SCRAPE I NTO RETAINING AREA/CONTAINER, INCREASE VENTILATION AVOID BREATH-ING VAPORS. Handling and Storage Precautions: KEEP AWAY FROM HEAT, SPARKS & OPEN FLAME, USE AD- EQUATE VENTILATION AVOID PROLONGED/REPEATED CON-TACT KEEP CONTAINER CLOSED Other Precautions: KEEP AWAY FROM CHILDREN AVOID STATIC BUILD UP

Respiratory Protection:SELF

CONTAINED BREATHING APPARATUS FOR CONCENTRATIONS ABOVE TLV Ventilation:LOCAL: YES, MECHANICAL: EXHAUST FROM LOWER LEVELS Protective Gloves:USE RUBBER GLOVES Eye Protection:SAFETY GLASSES Other Protective Equipment:EYE BATH, SAFETY SHOWER, PROTECTIVE CREAM Supplemental Safety and Health NK

Boiling Pt:B.P. Text:215 Vapor Pres:2 Vapor Density:3.8 Spec Gravity:1.1 Evaporation Rate & amp; Reference:0.8 WATER Solubility in Wat er:PARTIAL Appearance and Odor:GREEN CREAMY LIQUID Percent Volatiles by Volume:74

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZERS Stability Condition to Avoid:HEAT, SPARKS, OPEN FLAME AND FIRE Hazardous Decomposition Products:THERMAL DECOMPOSTION PRODUCES FUMES MAY YIELD CARBON MON- OXIDE

Waste Disposal Methods:INCINERATE OR DISPOSE OF IN A CCORDANCE WITH LOCAL STATE & FEDERAL REGULATIONS. EMPTY CONTAINERS MAY RETAIN FUMES. DO NOT EXPOSE TO HEAT OR FLAME

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.