

TRIAD PAINT & CHEMICAL CORP. -- PRIMER SURFC,SANDING WOOD STRUCT,BRN 20400 --
8010-00-055-5101

===== Product Identification =====

Product ID:PRIMER SURFC,SANDING WOOD STRUCT,BRN 20400

MSDS Date:09/01/1983

FSC:8010

NIIN:00-055-5101

MSDS Number: BHFKZ

=== Responsible Party ===

Company Name:TRIAD PAINT & CHEMICAL CORP.

Address:810 EVERGREEN AVENUE

Box:NA

City:BROOKLYN

State:NY

ZIP:11207

Country:US

|

Info Phone Num:(718) 443-2278

Emergency Phone Num:(718) 443-2778

CAGE:JO907

=== Contractor Identification ===

Company Name:TRIAD PAINT & CHEMICAL CORP.

Address:810 EVERGREEN AVENUE

Box:NA

City:BROOKLYN

State:NY

ZIP:11207

Country:US

Phone:(718) 443-2278

CAGE:JO907

Company Name:TRIAD PAINT AND CHEMICAL CORP

Address:810 EVERGREEN AVE

Box:City:BROOKLYN

State:NY

ZIP:11207-1140

Country:US

CAGE:33151

===== Composition/Information on Ingredients =====

Ingred Name:MINERAL SPIRITS

Fract

ion by Wt: 21.75%
ACGIH TLV:100 PPM

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Effects of Overexposure:VAPORS MIGHT BE IRRITATING TO EYES, NOSE, &
THROAT. REPEATED/EXCESSIVE EXPOSURE MAY RESULT IN HEADACHE,
DIZZINESS, SLEEPINESS & NAUSEA. DEFATTING TO SKIN.

=====
First Aid Measures
=====

First Aid:INHALATION: PROVIDE FRESH AIR AND REST. SKIN: WASH WITH MILD
SOA
P & WATER. USE EMOLLIENT CREAM OR LOTION. EYE: WASH WITH A
GENTLE STREAM OF WATER FOR 10MINS. CONSULT A PHYSICIAN.

=====
Fire Fighting Measures
=====

Flash Point Method:PMCC
Flash Point:105F/41C
Lower Limits:6.0
Upper Limits:1.0
Extinguishing Media:FOAM, CO2, DRY CHEMICAL
Fire Fighting Procedures:WEAR SELF CONTAINED APPARATUS. WATER STREAM
WILL SPREAD OIL FIRES.
Unusual Fire/Explosion Hazard:KEEP WORK AREA FREE OF HOT METAL OR OTHER
SOURCES OF IGN
ITION. VAPOR FORMS EXPLOSIVE MIXTURE BETWEEN
UPPER/LOWER EXPLOSIVE UNITS.

=====
Accidental Release Measures
=====

Spill Release Procedures:AVOID FLAME & SPARK SOURCES. PROVIDE ADEQUATE
VENTILATION, WIPE UP SPILL W/INERT ABSORBENT(S) & NON-SPARKING
TOOLS. SAFELY DISCARD SATURATED ABSORBENT(S). AVOID PROLONGED
BREATHING OF VAPORS WHILE CLEANING UP SPILLS.

=====
Handling and Storage
=====

Handling and Storage

Precautions:AVOID OPEN FLAME, AND SPARK SOURCES.
PROVIDE ADEQUATE VENTILATION. AVOID EXCESSIVE HEAT.
Other Precautions:DO NOT TAKE INTERNALLY. AVOID PROLONGED OR REPEATED
CONTACT W/SKIN. AVOID PROLONGED OR REPEATED BREATHING
OF VAPORS.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:ORGANIC CANNISTER MASK OR AIR PACK IF
VENTILATION IS INADEQUATE.
Ventilation:MECHANICAL WITH APPROVED CLASS D, EXPLOSIVE PROOF MOTNE. &
SWITCHES.
P
rotective Gloves:NEOPRENE RUBBER GLOVES.
Eye Protection:CHEMICAL SAFETY GOGGLES.
Supplemental Safety and Health
NK

=====
===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:307F - 382F
Vapor Pres:100F
Vapor Density:5.0
Spec Gravity:1.47
Evaporation Rate & Reference:.13
Solubility in Water:NEG.
Appearance and Odor:HYDROCARBON ODOR
Percent Volatiles by Volume:41.05

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materi
als to Avoid:YES
AVOID STRONG OXIDIZING AGENTS
Hazardous Decomposition Products:CO,CO2,ACID FUMES, AND SMOKE WHEN
COMBUSTED

=====
===== Disposal Considerations =====

Waste Disposal Methods:DISPOSAL PROCEDURES MUST COMPLY WITH LOCAL,
STATE,AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner w

hatsoever,

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.