

VIMASCO CORPORATION -- LAGGING ADHESIVE & COATING, 713 WHITE & RED --
8040-00-273-8707

=====
===== Product Identification =====

Product ID:LAGGING ADHESIVE & COATING, 713 WHITE & RED

MSDS Date:06/07/1989

FSC:8040

NIIN:00-273-8707

MSDS Number: BHFPB

=== Responsible Party ===

Company Name:VIMASCO CORPORATION

Box:516

City:NITRO

State:WV

ZIP:25143

Country:US

Info Phone Num:304-755-3328

Emergency Phone Num:

304-755-3328

Preparer's Name:JOHN TIDQUIST

CAGE:DO737

=== Contractor Identification ===

Company Name:EASTERN STEEL RACK CO

Address:166 PLEASANT STREET

Box:City:BOSTON

State:MA

ZIP:02125-1530

Country:US

CAGE:19947

Company Name:VIMASCO CORPORATION

Address:PO BOX 516

Box:516

City:NITRO

State:WV

ZIP:25143

Phone:304-755-3328

CAGE:DO737

=====
===== Composition/Information on Ingredients =====

Ingred Name:ETHYLENE GLYCOL (SARA III)

CAS:107-21-1

RTECS #:KW2975000

Fraction by Wt: 2%

OSHA P

EL:C 50 PPM
ACGIH TLV:C 50 PPM,VAPOR; 9192
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

Ingred Name:CHLORINATED PARAFFIN
CAS:63449-39-8
RTECS #:RV0480000
Fraction by Wt: 10%

Ingred Name:VINYL ACETATE
CAS:108-05-4
RTECS #:AK0775000
Fraction by Wt: 0.2%
OSHA PEL:10 PPM/15 STEL
ACGIH TLV:10 PPM/15,A3 STEL;93
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:HEXYLENE GLYCOL
CAS:107-41-5
RTECS #:SA0810000
Fraction by Wt: 4%
OSHA PEL:C 25 PPM
ACGIH TLV:C 25 PPM; 9192

Ingred Name:VOC. ORGANIC CMPD 78.8 GM
S/L LESS WATER
NK
RTECS #:9999999VO

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ETHYLENE GLYCOL: SKIN/EYE IRRITATION.
INHALATION-NASAL/RESPIRATORY IRRITATION.
INGESTION-DRUNKENESS/COMA/KIDNEY INJURY/DEATH. CHLORINATED
PARAFFIN: SLIGHT HAZ WITH LIVER. VINYL ACETATE: EYE/RESPIRATORY
IRRITATION AT HIGH

H CONCENTRATIONS:HEXYLENE GLYCOL:HIGH
CONCENTRATIONS-IRRITANT EYES/SKIN/MUCOUS MEMBRANES/NARCOSIS
Medical Cond Aggravated by Exposure:NONE KNOWN.

===== First Aid Measures =====

First Aid:SKIN: WASH W/SOAP/WATER. EYES: FLUSH W/CLEAN WATER AT LEAST
15 MIN. IF IRRITA- TION PERSISTS, CONSULT PHYSICIAN. INHALATION:
REMOVE TO FRESH AIR. IF BREATHING IS DIFFICULT, ADMINISTER OXYGEN.
IF IRRI TATION PERSISTS, CONSULT PHYSICIAN.INGESTION: GIVE 2

GLASSES OF WATER, INDUCE VOMITING, CONSULT PHYSICIAN OR
POISONCONTROL CENTER. NEVER GIVE ANYTHING BY MOUTH TO AN
UNCONSCIOUS PERSON.

===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:212F 100C
Lower Limits:NOT AVAIL
Extinguishing Media:FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG.
Fire Fighting Procedures:PRODUCT WILL NOT BURN UNTIL WATER HAS
EVAPORA'D. FOR DRIED FILM/RESIDUAL SOLIDS,FULL PROTECTIVE EQUIP
RECOMMENDED INC
LUDING SELF-CONTAINED BREATHING APPARATUS.
Unusual Fire/Explosion Hazard:NONE KNOWN.

===== Accidental Release Measures =====

Spill Release Procedures:MAJOR SPILLS SHOULD BE COLLECTED FOR DISPOSAL.
MINOR SPILLS MAY BE FLUSHED TO SEWER IF REGULATIONS
PERMIT. BEFORE DRYING, PRODUCT MAY BE WASHED AWAY WITH WATER. AFTER
DRYING, REMOVE WITH A PAINT SCRAPER OR STRONG SOLVENT.

===== Handling and Storage =====

Handling a
nd Storage Precautions:AVOID BREATHING VAPORS. AVOID
APPLICATION TO HOT SURFACES. KEEP CONTAINER CLOSED. USE W/ADEQUATE
VENTILATION. STORE INDOORS AT TEMP OF 45F-90F.
Other Precautions:FOR INDUSTRY/PROFESSIONAL USE ONLY. NOT INTENDED FOR
RETAIL SALE OR USE BY INDIVIDUAL CONSUMERS. DO NOT REUSE
CONTAINER FOR POTABLES OR EDIBLES.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE APPROVED CHEMICAL VAPOR RESPIRATOR IN
RESTRICT

ED VENTILATION AREAS. IN AP- PPLICATIONS WHERE MISTS/SPRAY
MAY BE GENERATED, AVOID INHALATION OF AIRBORNE PAR-TICULATES BY
USING AN APPROVED RESPIRATO R W/ORGANIC VAPOR CARTRIDGE
W/PREFILTER.

Ventilation:GENERAL (MECHANICAL) ROOM VENTILATION IS EXPECTED TO BE
SATISFACTORY.

Protective Gloves:IMPERVIOUS GLOVES.

Eye Protection:GOGGLES, FACESHIELD, ETC. FOR SPLASH.

Other Protective Equipment:NONE

Work Hygienic Practices:THOROUGHLY CLEANSE HANDS AFTER HANDLING.
LAUNDER

CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

NK

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:212F

Decomp Temp:Decomp Text:240F 115C

Vapor Density: