

EVERSEAL MFG CO INC -- BLUE GLOSS ALKYD ENAMEL C-15102 -- 8010-00-597-7844
===== Product Identification =====

Product ID:BLUE GLOSS ALKYD ENAMEL C-15102

MSDS Date:10/21/1987

FSC:8010

NIIN:00-597-7844

MSDS Number: BHFRC

=== Responsible Party ===

Company Name:EVERSEAL MFG CO INC

Address:475 BROAD AVE

City:RIDGFIELD

State:NJ

ZIP:07657-2329

Country:US

Info Phone Num:201-943-4986 / FAX 201-943-1123

E

mergency Phone Num:201-943-4986

CAGE:72988

=== Contractor Identification ===

Company Name:EVERSEAL MFG CO INC

Address:475 BROAD AVE

Box:City:RIDGFIELD

State:NJ

ZIP:07657-2329

Country:US

Phone:201-943-4986

CAGE:72988

===== Composition/Information on Ingredients =====

Ingred Name:RESIN

Fraction by Wt: 35%

Ingred Name:TITANIUM DIOXIDE

CAS:13463-67-7

RTECS #:XR2275000

Fraction by Wt: 13%

OSHA PEL:15 MG/M3 TDUST

ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:COMPLEX INORGANIC PIGMEN

T
CAS:14038-43-8
Fraction by Wt: 4%

Ingred Name:MINERAL SPIRITS
(VAPOR PRESSURE 2)
CAS:64742-88-3
Fraction by Wt: 46%

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Effects of Overexposure:EYE: IRRITATION
SKIN: IRRITATION
INHAL: DIZZINESS,
NAUSEA, POSSIBLE UNCON SCIOUSNESS

=====
First Aid Measures
=====

First Aid:EYE: FLUSH
WITH WATER CONSULT PHYSICIAN
SKIN: WASH WITH SOAP AND WATER
INHAL: REMOVE TO FRESH AIR, APPLY
ARTIFI CIAL RESPIRATION IF NECESSARY

=====
Fire Fighting Measures
=====

Flash Point:105F/40.56C
Lower Limits:0.7
Extinguishing Media:FOAM, CO2, DRY CHEMICAL
Fire Fighting Procedures:FIREFIGHTERS SHOULD WEAR SELF CONTAINED
BREATHING APPARATUS.
Unusual Fire/Explosion Hazard:WATER NOT A SUITABLE EXTINGUISHING MEDIUM

=====
Accidental Release Measures
=====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. ABSORB SMALL
SPILLON DRY ABSORPTION MATERIAL. USE SPARK PROOF SCOOP FOR LARGER
SPILLS. ENSURE ADEQUATE VENTILATION.

=====
Handling and Storage
=====

Handling and Storage Precautions:AVOID EXCESSIVE HEAT AND OPEN IGNITION
SOURCES.
Other Precautions:NPCA/HMIS RATING 3,2,0,H

=====
Exposure Controls/Personal Protection
=====

===

Respiratory Protection:CARTRIDGE FUME MASK
Ventilation:SUFFICIENT TO ENSURE LEL NOT ACHIEVED
Protective Gloves:IMPERVIOUS
Eye Protection:SAFETY GOGGLES
Other Protective Equipment:PROTECT SKIN WITH CLOTHING OR BARRIER CREAM
Supplemental Safety and Health
NK

===== Physical/Chemical Properties =====

HCC:F4
Boiling Pt:B.P. Text:323-390F
Vapor Density:> AIR
Evaporation Rate & Reference:SLOWER THAN ETHER
Percent Volatiles by Volume:62

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS
Hazardous Decomposition Products:CARBON MONOXIDE/DIOXIDE ON COMBUSTION

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF AS PER LOCAL AND FEDERAL REGULATIONS
FOR HAZARDOUS WASTE.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.