

BAKER SEALANTS & COATING COMPANY -- ADHESIVE FOR ACOUSTICAL MATL P/N X-973B --  
8040-00-656-0929

===== Product Identification =====

Product ID:ADHESIVE FOR ACOUSTICAL MATL P/N X-973B

MSDS Date:10/31/1989

FSC:8040

NIIN:00-656-0929

MSDS Number: BHFRL

=== Responsible Party ===

Company Name:BAKER SEALANTS & COATING COMPANY

Address:234 SUYDAM AVENUE

Box:B

City:JERSEY CITY

State:NJ

ZIP:07304

Country:US

Info Phone Num:201-333-6986

Emergency Phone Num:800-424-9300 (24 HOURS)

CAGE:FO833

=== Contractor Identification ===

Company Name:BAKER SEALANTS & COATINGS CO., INC.

Address:234 SUYDAM AVENUE

Box:B

City:JERSEY CITY

State:NJ

ZIP:07304-3306

Phone:(201) 333-6986

CAGE:FO833

Company Name:BAKER SEALANTS AND COATINGS CO

Address:234 SUYDAM AVE

Box:City:JERSEY CITY

State:NJ

ZIP:07304-3306

Country:US

Phone:201-333-6986

CAGE:34094

===== Composition/Information on Ingredients =====

Ingre

d Name:ISOPROPYL ALCOHOL (SARA III)  
CAS:67-63-0  
RTECS #:NT8050000  
Fraction by Wt: 5%  
OSHA PEL:400 PPM/500 STEL  
ACGIH TLV:400 PPM/500STEL;9192

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Effects of Overexposure:EYE: CAN CAUSE IRRITATION REDNESS AND TEARING  
SKIN: PROLONGED/REPEATED CONTACT  
CANCAUSE MODERATE IRRITATION INHAL: EXCESSIVE  
INHAL  
ATION OF VAPORS MA Y CAUSE NASAL & RESPIRATORY  
IRRITATIONINGST: CAN CAUSE GASTROINTESTINAL IRRITATION

===== First Aid Measures =====

First Aid:EYES: FLUSH WITH WATER FOR 15 MINUTES.  
SKIN: WASH WITH SOAP AND WATER  
INHAL: REMOVE TO FRESH AIRINGST:  
DRINK WATER AND INDUCE VOMITING

===== Fire Fighting Measures =====

Flash Point Method:TCC  
Flash Point:140F/60C  
Lower Limits:2.0  
Upper Lim  
its:12  
Extinguishing Media:FOAM, CARBON DIOXIDE, DRY POWDER  
Unusual Fire/Explosion Hazard:NONE

===== Accidental Release Measures =====

Spill Release Procedures:DIKE AND CONTAIN SPILL TRANSFER INTO  
CONTAINERS

===== Handling and Storage =====

Handling and Storage Precautions:NORMAL PRECAUTIONS

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT NECESSARY  
Ventilation:LOCAL EXHAUST  
Pr

Protective Gloves: RUBBER  
Eye Protection: PROTECTIVE GOGGLES  
Supplemental Safety and Health  
NK

===== Physical/Chemical Properties =====

Boiling Pt: B.P. Text: 180F/82.2C  
Vapor Pres: 33  
Vapor Density: 2.0  
Spec Gravity: 1.366  
pH: 7.0  
Viscosity: 220-240  
Evaporation Rate & Reference: 1.4  
Solubility in Water: COMPLETE  
Appearance and Odor: BROWNISH SEMI SOLID CHARACTERISTIC ODOR  
Percent Volatiles by Volume: 5

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES  
STRONG OXIDIZING AGENTS

===== Disposal Considerations =====

Waste Disposal Methods: PER LOCAL, STATE, OR FEDERAL REGULATIONS

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.