

CORONADO PAINT CO -- ALKYD ENAMEL G277-1,WHITE -- 8010-00-664-4761

=====
Product Identification
=====

Product ID:ALKYD ENAMEL G277-1,WHITE

MSDS Date:01/01/1987

FSC:8010

NIIN:00-664-4761

MSDS Number: BHFZJ

=== Responsible Party ===

Company Name:CORONADO PAINT CO

Address:308 OLD COUNTY RD

Box:308

City:EDGEWATER

State:FL

ZIP:32032-1812

Country:US

Info Phone Num:904-428-6461 / FAX 904-427-7130

Emerge

ncy Phone Num:904-428-6461

CAGE:33200

=== Contractor Identification ===

Company Name:CORONADO PAINT COMPANY, INC.

Address:308 OLD COUNTY ROAD

Box:City:EDGEWATER

State:FL

ZIP:32132-1812

Country:US

Phone:904-428-6461

CAGE:33200

=====
Composition/Information on Ingredients
=====

Ingred Name:ALIPHATIC HYDROCARBONS

Fraction by Wt: 42.8%

Other REC Limits:100 PPM

OSHA PEL:N/K

ACGIH TLV:N/K

Ingred Name:VEHICLE

Fraction by Wt: 31.1%

Other REC Limits:N/K

OSHA PEL:N/K

ACGIH TLV:N/K

Ingred Name:PIGMENTS
Fraction by Wt: 26.1%
Other REC Limits:N/K
OSHA PEL:N/K
ACGIH TLV:N/K

===== Hazards Identification =====

LD50 LC50 Mixture:N/K
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:SEE SIGNS AND SYMPTOMS OF
OVEREXPOSURE.
Explanation of Carcinogenicity:NONE
Effects of Overexposure:EYES:PRODUCES SEVERE IRRITATION.SKIN:CAUSES
DRYING OF THE SKIN.INHALATION:EXCESSIVE INHALATION CAUSES
HEADACHES
,DIZZINESS,AND NAUSEA.INGESTION:N/K
Medical Cond Aggravated by Exposure:N/K

===== First Aid Measures =====

First Aid:EYES:FLUSH WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15
MIN.SKIN:WASH WITH MILD SOAP AND WATER AND APPLY SKIN
CREAM.INGESTION:CALL MD IMMEDIATELY .INHALATION:REMOVE TO FRESH AIR
AND CALL PHYSICIA N;GIVE ARTIFICIAL RESPIRATION IF NECESSARY.

===== Fire Fighting Measures =====

Flash Point Method:
SCC
Flash Point:104F,40C
Lower Limits:1.1
Upper Limits:6.0
Extinguishing Media:FOAM,DRY CHEMICAL,CARBON DIOXIDE.
Fire Fighting Procedures:USE NIOSH/MSHA APPROVED SCBA AND FULL
PROTECTIVE EQUIPMENT .WATER IS NOT ORDINARILY EFFECTIVE BECAUSE IT
TENDS TO SCATTER AND SPREAD FIRE.
Unusual Fire/Explosion Hazard:VAPORS MAY FORM EXPLOSIVE MIXTURES WITH
AIR.THERMAL DECOMPOSITION MAY YIELD CARBON MONOXIDE.

===== Accidental Release Measures =====

Spill Release Proc

edures:WEAR A RESPIRATOR.FLUSH WITH WATER INTO
RETAINING AREA OR CONTAINER.AVOID EXPOSURE TO SPARKS,FIRE OR HOT
METAL SURFACES.
Neutralizing Agent:N/K

=====
===== Handling and Storage =====

Handling and Storage Precautions:KEEP AWAY FROM HEAT,SPARKS,OPEN
FLAME,TRANSPORTATION PRECAUTIONS;DO NOT ALLOW STORAGE FOR PROLONGED
PERIODS IN NON-INSULATED TRAILER.

Other Precautions:USE WITH ADEQUATE VENTILATION.AVOID PROLONGED SKIN
CONTACT.

=====
= Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA APPROVED RESPIRATOR APPROPRIATE FOR
EXPOSURE OF CONCERN .

Ventilation:LOCAL AND GENERAL VENTILATION NECESSARY TO KEEP AIR
CONCENTRATION BELOW TLV .

Protective Gloves:NEOPRENE GLOVES.

Eye Protection:CHEMICAL WORKERS GOGGLES .

Other Protective Equipment:EYE BATH AND SAFETY SHOWER.

Work Hygienic Practices:N/K

Supplemental Safety and Health
TLV 200 PPM (MFR)

=====
===== Physical/Chemical Prop
erties =====

HCC:F4

Boiling Pt:B.P. Text:300F,148.9C

Melt/Freeze Pt:M.P/F.P Text:N/K

Decomp Temp:Decomp Text:N/K

Vapor Pres:2 MMHG

Vapor Density:>1 (AIR=1)

Spec Gravity:1.125 (WATER=1)

Evaporation Rate & Reference: