

DYKEM COMPANY -- DX-100 DYKEM STEEL BLUE -- 6850-01-276-5396

=====  
Product Identification  
=====

Product ID:DX-100 DYKEM STEEL BLUE

MSDS Date:10/05/1989

FSC:6850

NIIN:01-276-5396

MSDS Number: BHGCF

=== Responsible Party ===

Company Name:DYKEM COMPANY

Address:8501 DELPORT DRIVE

City:ST LOUIS

State:MO

ZIP:63114

Info Phone Num:314-423-0100

Emergency Phone Num:314-423-0100

CAGE:EO153

=== Contractor Ide

ntification ===

Company Name:DYKEM COMPANY

Address:8501 DELPORT DRIVE

City:ST. LOUIS

State:MO

ZIP:63114-5905

Country:US

Phone:314-423-0100

CAGE:EO153

Company Name:ITW DYKEM/ DYMON

Address:805 E OLD 56 HWY

Box:City:OLATHE

State:KS

ZIP:66061

Country:US

Phone:800-443-9536

CAGE:98148

=====  
Composition/Information on Ingredients  
=====

Ingred Name:N-BUTYL ACETATE (SARA III)

CAS:123-86-4

RTECS #:AF7350000

Fraction by Wt: 30-40%

OSHA PEL:150 PPM/200 STEL

ACGIH TLV:150 PPM/200STEL;91

92

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:ETHYL ALCOHOL (ETHANOL)

CAS:64-17-5

RTECS #:KQ6300000

Fraction by Wt: 50-60%

OSHA PEL:1000 PPM

ACGIH TLV:1000 PPM; 9192

Ingred Name:N-BUTYL ALCOHOL (SARA III)

CAS:71-36-3

RTECS #:EO1400000

Fraction by Wt: 3-6%

OSHA PEL:100 PPM

ACGIH TLV:S, C 50 PPM; 9293

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:METHYL VIOLET

CAS:8004-87-3

RTECS #:GC8425000

Fraction by Wt: 6-12%

Ingred Name:CELLULOSE NITRATE (PROPORTIONAL 70/30 WITH ISOPRO  
PANOL)

CAS:9004-70-0

RTECS #:QW0970000

Fraction by Wt: 2.1-4.2%

Ingred Name:ISOPROPYL ALCOHOL (SARA III)

CAS:67-63-0

RTECS #:NT8050000

Fraction by Wt: 0.9-1.8%

OSHA PEL:400 PPM/500 STEL

ACGIH TLV:400 PPM/500STEL;9192

=====  
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:PRODUCT IS IRRITATING TO BODY TISSUES.

PROLONGED/REPEATED SKIN

CONTACT MAY CAUSE DERMATITIS. INHALATION  
MAY PRODUCE CENTRAL NERVOUS SYSTEM EFFECTS. NO INFORMATION WAS  
READILY AVAILABLE ON CHRONIC EFFECTS.

Effects of Overexposure:EYE:IRRITATION,BURNING. SKIN:DRYING,DERMATITIS  
WITH PROLONGED/REPEATED CONTACT. INHALED:RESPIRATORY  
IRRITATION,DIZZINESS,HEADACHE,NAUSEA. INGESTED:G/I  
IRRITATION,NAUSEA.

Medical Cond Aggravated by Exposure:NONE REPORTED

=====  
===== First Aid Measures =====

First Aid:EYE:FLUSH WITH  
WATER 15 MIN. SKIN:REMOVE CONTAMINATED  
CLOTHING. WASH AREA WITH SOAP AND WATER. LAUNDRY CLOTHING BEFORE  
REUSE. INHALED:REMOVE FROM EXPOSURE. GIVE ARTIFICIAL RESPIRATION OR  
OXYGEN IF NEEDED. INGESTED:DO NOT INDUCE VOMITING. GIVE WATER OR  
MILK. (NOTHING BY MOUTH IF UNCONSCIOUS) GET IMMEDIATE MEDICAL CARE.  
IF SYMPTOMS PERSIST OR ARE SEVERE,GET MEDICAL CARE.

=====  
===== Fire Fighting Measures =====

Flash Point Method:TCC  
Flash Point:57F/14C  
Lower  
Limits:1.4  
Upper Limits:11.2  
Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL,FOAM,WATER FOG  
Fire Fighting Procedures:WEAR SELF CONTAINED BREATHING APPARATUS. WATER  
MAY BE USED TO COOL FIRE EXPOSED CONTAINERS.  
Unusual Fire/Explosion Hazard:VAPORS ARE HEAVIER THAN AIR AND FLASHBACK  
ALONG VAPOR TRAIL MAY OCCUR

=====  
===== Accidental Release Measures =====

Spill Release Procedures:WIPE UP,WITH PAPER,CLOTH. STORE IN CLOSED  
CONTAINER. USE APPROPRIATE PRECAUTIONS TO PROTECT PERSONNEL AND  
PREVENT IGNITION.  
Neutralizing Agent:NONE- USE ALCOHOL AS SOLVENT FOR CLEANING.

=====  
===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A COOL,DRY,WELL VENTILATED  
AREA. KEEP AWAY FROM HEAT,SPARKS,OTHER IGNITION SOURCES.

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE EXPECTED TO BE NECESSARY. USE NIOSH/MSHA  
RESPIRATOR IF SYMPTOMS OCCUR OR PEL/TLV ARE EXCEEDED.

Ventilation:NORMAL ROOM VENTILATION LOCAL EXHAUST MAY BE REQUIRED UNDER SOME CONDITIONS.

Protective Gloves:NONE SHOULD BE NEEDED

Eye Protection:SAFETY GLASSES.

Other Protective Equipment:AS NECESSARY TO PREVENT PROLONGED/REPEATED CONTACT.

Work Hygienic Practices:USE GOOD INDUSTRIAL HYGIENE PRACTICE. AVOID UNNECESSARY CONTACT.

Supplemental Safety and Health

MFR DATES MSDS ON DAY MAILED,NOT DAY REVISED.

===== Physical/Chemical Properties =====

HCC:F2

Boili

ng Pt:=71.1C, 160.F

Vapor Pres:36 MM

Vapor Density:>1

Spec Gravity:0.86

Evaporation Rate & Reference:>1 BUAC

Solubility in Water:APPRECIABLE

Appearance and Odor:INTENSE BLUE COLOR,SWEET SOLVENT ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid:HEAT,IGNITION SOURCES

Hazardous Decomposition Products:CARBON MONOXIDE,CARBON DIOXIDE.

===== Disposal Considerati  
ons =====

Waste Disposal Methods:DISPOSE I/A/W FEDERAL,STATE,LOCAL,REGULATIONS.  
MFR SUGGESTS INCINERATION.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek compet

ent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.