

HOLLISTER INCORPORATED -- HOLLIHESIVE PASTE TUBES 7920 -- 6510-01-220-5054

=====
Product Identification
=====

Product ID:HOLLIHESIVE PASTE TUBES 7920

MSDS Date:03/11/1987

FSC:6510

NIIN:01-220-5054

MSDS Number: BHLQK

=== Responsible Party ===

Company Name:HOLLISTER INCORPORATED

Address:2000 HOLLISTER DRIVE

City:LIBERTYVILLE

State:IL

ZIP:60048

Info Phone Num:(312) 680-1000

Emergency Phone Num:(312)

680-1000

CAGE:09309

=== Contractor Identification ===

Company Name:HOLLISTER INCORPORATED

Address:2000 HOLLISTER DRIVE

Box:City:LIBERTYVILLE

State:IL

ZIP:60048

Country:US

Phone:(312) 680-1000

CAGE:09309

=====
Composition/Information on Ingredients
=====

Ingred Name:ETHANOL (ETHYL ALCOHOL), TECSOL, ALCOHOL

CAS:64-17-5

RTECS #:KQ6300000

Fraction by Wt: 26.55%

Other REC Limits:1900 MG/CUM

OSHA PEL:1000 PPM

ACGIH TLV:1000 PPM

Ingred Name:BUTANOL, N-BUTYL ALCOHOL, PROPYL CARBINO

L, BUTYL ALCOHOL
CAS:71-36-3
RTECS #:EO1400000
Fraction by Wt: 2.95%
Other REC Limits:300 MG/CUM
OSHA PEL:100 PPM
ACGIH TLV:C 152 MG/CUM
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

=====
Hazards Identification
=====

Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYES: SEVERE IRRITATION, IRITIS,
CONJUNCTIVITIS, & CORNEAL OPACITY. SKIN: IRRITATION & DERMATITIS.
Explanation of Carcinogenicity:NONE
Effects of Overexposure:EYES: SEVERE IRRITATION, IRITIS,
CONJUNCTIVITIS, & CORNEAL OPACITY. SKIN: PROLONGED/REPEATED CONTACT
MAY CAUSE IRRITATION OR DERMATITIS.
Medical Cond Aggravated by Exposure:DERMATITIS

=====
First Aid Measures
=====

First Aid:EYES: FLUSH W/PLENTY OF WATER. SKIN: WASH AREA W/SOAP &
WATER. INHALATION: REMOVE FROM EXPOSURE TO FRESH AIR. CONSULT
PHYSICIAN.

=====
Fire Fighting
Measures
=====

Lower Limits:3.3%
Upper Limits:19.0%
Extinguishing Media:WATER, FOAM, CO2, DRY CHEMICAL
Fire Fighting Procedures:NONE ANTICIPATED.
Unusual Fire/Explosion Hazard:KEEP CONTAINERS AWAY FROM HEAT, SPARKS, &
OPEN FLAMES. VAPORS ARE >AIR.

=====
Accidental Release Measures
=====

Spill Release Procedures:MECHANICAL CLEAN-UP FOR DISPOSAL.

=====
Handling and Storage
=====

Handling and Storage Precautio

ns:AVOID CONTACT W/EYES. KEEP AWAY FROM HEAT, SPARKS, & OPEN FLAMES. USE ONLY W/ADEQUATE VENTILATION.
Other Precautions:AVOID CONTACT W/SEVERELY IRRITATED/EXCORIATED SKIN, OR DIRECTLY OVER OPEN CUTS OR SORES.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE ANTICIPATED.
Ventilation:USE ONLY W/ADEQUATE VENTILATION.
Protective Gloves:NONE
Eye Protection:NONE
Work Hygienic Practices:NO REACTIONS ANTICIPATED WHEN USED AS DIRECTED.
Supplemental
Safety and Health

=====
===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:78.5C
Vapor Pres:40.00
Vapor Density:>AIR
Spec Gravity:1.150
Solubility in Water:EXPANDS
Appearance and Odor:CREAM-COLORED VISCOUS PASTE, SWEET ALCOHOLIC ODOR.

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
OXIDIZING AGENTS
Stability Condition to Avoid:HEAT, SPARKS, & OPEN FLAMES
Hazardous Decomposition Products:CO, CO2

=====
===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORDANCE W/APPLICABLE GOVERNMENT REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.