

BAKER SEALANTS & COATINGS CO. -- PROMOTOR X-512A -- 8040-00-526-1910

=====
Product Identification
=====

Product ID:PROMOTOR X-512A

MSDS Date:05/06/1986

FSC:8040

NIIN:00-526-1910

MSDS Number: BHLSV

=== Responsible Party ===

Company Name:BAKER SEALANTS & COATINGS CO.

Address:234 SUYDAM AVE.

City:JERSEY CITY

State:NJ

ZIP:07304

Info Phone Num:(201) 333-6986

Emergency Phone Num:(201) 333-6986

Preparer

's Name:CHARLES S.

CAGE:FO833

=== Contractor Identification ===

Company Name:BAKER SEALANTS & COATINGS CO., INC.

Address:234 SUYDAM AVENUE

Box:B

City:JERSEY CITY

State:NJ

ZIP:07304-3306

Phone:(201) 333-6986

CAGE:FO833

Company Name:BAKER SEALANTS AND COATINGS CO

Address:234 SUYDAM AVE

Box:City:JERSEY CITY

State:NJ

ZIP:07304-3306

Country:US

Phone:201-333-6986

CAGE:34094

=====
Composition/Information on Ingredients
=====

Ingred Name:XYLIDINE

CAS:1300-73-8

RTECS #:ZE8575000

Fract

ion by Wt: 2%
Other REC Limits:0.5 PPM A2 IC
OSHA PEL:S, 5 PPM
ACGIH TLV:S, 0.5 PPM; A2; 9293

Ingred Name:METHYL METHACRYLATE (SARA III)
CAS:80-62-6
RTECS #:OZ5075000
Fraction by Wt: 98%
Other REC Limits:100 PPM
OSHA PEL:100 PPM
ACGIH TLV:100 PPM; 9192
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:INHALATION: NOSE & THROAT IRRITATION.
SKIN/EYES: IRRITATION & CORNEAL INJURY.
Explanation of Carcinogenicity:DIMETHYL ANILINE IS CONSIDERED TO BE A2
CARCINOGEN BY ACGIH.
Effects of Overexposure:INHALATION: NOSE & THROAT IRRITATION.
SKIN/EYES: IRRITATION & CORNEAL INJURY.

=====
===== First Aid Measures =====

First Aid:INHALATION: REMOVE TO FRESH AIR, GIVE OXYGEN. EYE/SKIN: FLUSH
W/WATER. INGESTION: DILUTE BY GIVING 2 GLASSES OF WATER TO
DRINK.
INDUCE VOMITING. GET A PHYSICIAN IN ALL CASES.

=====
===== Fire Fighting Measures =====

Flash Point Method:SCC
Flash Point:49F
Lower Limits:2.12%
Upper Limits:12.5%
Extinguishing Media:ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER SPRAY
Fire Fighting Procedures:WEAR SELF CONTAINED BREATHING APPARATUS. USE
WATER SPRAY TO COOL CONTAINERS. FIGHT FIRE FROM MAXIMUM DISTANCE.
Unusual Fire/Explosion Hazard:HEATED SEALED CONTAINERS CAN EXPLODE.

=====

Accidental Release Measures =====

Spill Release Procedures:ELIMINATE ALL SOURCES OF IGNITION. USE SELF-CONTAINED BREATHING APPARATUS. DIKE & CONTAIN SPILL. ADD EXTRA INHIBITOR TO PREVENT POLYMERIZATION. STAY UP WIND: AVOID SMOKE & FUMES. REPORTABLE TQTY - 100 0 LBS.

===== Handling and Storage =====

Handling and Storage Precautions:STORE AT AMBIENT TEMPERATURES. GROUND ALL CONTAINERS WHEN TRANSFERRING MATERIAL. DIMETHYL ANILINE IS

POISONOUS.

Other Precautions:IT IS ADVISABLE TO USE MATERIAL WITHIN 6 MONTHS. MATERIAL STORED IN BULK SHOULD BE TESTED FOR STABILITY EVERYDAY. DRUMS & PAILS EVERY 3 MONTHS. AVOID SMOKE & FUMES.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:WEAR SELF CONTAINED BREATHING APPARATUS.

Ventilation:MECHANICAL

Protective Gloves:IMPERVIOUS

Eye Protection:CHEMICAL SPLASH GOGGLES

Other Protective Equipment:IMPERVIOUS CLOTHING

Supplemental Safety a

nd Health

DIMETHYL ANILINE IS IN POISON CLASS B, 6.1

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:214F

Melt/Freeze Pt:M.P/F.P Text:-54F

Vapor Pres:20

Vapor Density:3.5

Spec Gravity:0.94

Evaporation Rate & Reference:(BU AC = 1): >1

Solubility in Water:MODERATE

Appearance and Odor:CLEAR LIQUID, ACRID, FRUITY ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

OXIDIZING AGENTS, ACIDS

, & BASES, UV LIGHT, CONTAMINATION.

Stability Condition to Avoid:HEAT, AGING, CONTAMINATION, OXYGEN-FREE ATMOSPHERE, SUNLIGHT.

Conditions to Avoid Polymerization:HEAT, OXYGEN-FREE ATMOSPHERE, SUNLIGHT

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE, AND FEDERAL REGULATIONS. FLAMMABLE LIQUID, CLASS B POISON.

Disclaimer (provided with this information by the compiling agencies):

This information

is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.