

SUPERIOR PRODUCTS COMPANY, INC. -- SUPERSEAL 333,444,777,1614,1614A,4000 --  
8030-00-141-6568

===== Product Identification =====

Product ID: SUPERSEAL 333,444,777,1614,1614A,4000

MSDS Date: 07/05/1988

FSC: 8030

NIIN: 00-141-6568

MSDS Number: BHMJFJ

=== Responsible Party ===

Company Name: SUPERIOR PRODUCTS COMPANY, INC.

Address: 445 CONEY ISLAND DRIVE SOUTH

City: SPARKS

State: NV

ZIP: 89431

Country: US

Info P

Phone Num: 602-276-0406

Emergency Phone Num: 800-528-8242

CAGE: 6E653

=== Contractor Identification ===

Company Name: SUPERIOR PRODUCTS COMPANY, INC.

Address: 445 CONEY ISLAND DRIVE SOUTH

Box: City: SPARKS

State: NV

ZIP: 89431

Country: US

Phone: 602-276-0406

CAGE: 6E653

===== Composition/Information on Ingredients =====

Ingred Name: PETROLEUM DISTILLATE

CAS: 65996-93-2

Other REC Limits: 8 HOUR TWA

OSHA PEL: NA

ACGIH TLV: NA

Ingred Name: PETROLEUM DISTILLATES (NAPHTHA OR RUBBER SOLVENT)

CAS: 800

2-05-9  
RTECS #:SE7449000  
OSHA PEL:400 PPM  
ACGIH TLV:400 PPM; 8990

Ingred Name:VINYL CHLORIDE (SARA III)  
CAS:75-01-4  
RTECS #:KU9625000  
Other REC Limits:8 HOUR TWA  
OSHA PEL:SEE 1910.1017  
ACGIH TLV:5 PPM, A1; 9293  
EPA Rpt Qty:1 LB  
DOT Rpt Qty:1 LB

=====  
Hazards Identification  
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO  
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES  
Health Hazards Acute and Chronic:ACUTE: BREATHING FUMES OR VAPORS

INCREASES EXPOSURE TO COAL TAR PITCH VOLATILES ANDPETROLEUM  
DISTILLATE. IMMEDIATE SYMTOMS: HEADACHE, NAUSEA AND DIZZINESS.  
Explanation of Carcinogenicity:COAL TAR PITCH VOLATILES, VINYL CHLORIDE  
MONOMER % COMPOSITION LESS THAN .1  
Effects of Overexposure:IRRITATION OF SKIN,EYES AND RESPIRATORY TRACT,  
HEADACHE. CHRONIC: INCREASED RISK OF BRONCHITIS, CANCER OF THE  
LUNGS, SKIN BLADDER, KIDNEYS.  
Medical Cond Aggravated by Exposure:RESPIRATORY AILMENTS AND SKIN  
SENSITIZATION BY  
ACUTE AND CHRONIC INHALATION AND SKIN CONTACT.

=====  
First Aid Measures  
=====

First Aid:SKIN CONTACT: REMOVE WITH SOAP AND WATER. EYE CONTACT: FLUSH  
WITH PLENTY OF WATER.

=====  
Fire Fighting Measures  
=====

Flash Point:>300  
Lower Limits:NA  
Upper Limits:NA  
Extinguishing Media:DRY CHEMICAL  
Fire Fighting Procedures:WEAR SELF CONTAINED BREATHING APPARARUS AND  
FULL PROTECTIVE EQUIPMENT  
Unusual Fire/Explosion Hazard:USE

# OF WATER COULD CAUSE FROTHING

## ===== Accidental Release Measures =====

Spill Release Procedures:AVOID BREATHING FUMES AND CONTACT WITH SKIN AND EYES. AVIOD SOURCES OF IGNITION. CONTAIN WITH ABSORBENT SOLIDS,SUCH AS SAND,EARTH,ECT.

## ===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A COOL DRY AREA AWAY FROM SOURCES OF IGNITION.

Other Precautions:KEEP LIDS CLOSED ON THE MELTERS AS MUCH AS POSSI BLE TO PREVENT VAPOR RELEASE

## ===== Exposure Controls/Personal Protection =====

Respiratory Protection:1 OR 2 CARTRIDGE AIR PURIFYING RESPIRATOR WITH ORGANIC VAPOR AND PARTICULATE CARTRIDGE WHEN VAPOR CANNOT BE AVOIDED.

Ventilation:TO MAINTAIN FUME LEVEL BELOW TLV

Protective Gloves:YES NON POROUS TYPE

Eye Protection:SAFETY GLASSES AND GOGGLES

Other Protective Equipment:FULL CLOTHING AND EXPOSED SKIN PROTECTON. USE APPROVED BARRIER CREAMS.

Work Hygienic Practice

s:AVOID VAPORS AND SKIN CONTACT SHOWER AFTER WORK

DAILY, CLEAN CLOTHES SHOULD BE WORN TO WORK EACH WORKING DAY.

Supplemental Safety and Health

NK

## ===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:420F

Melt/Freeze Pt:M.P/F.P Text:.05

Vapor Pres:NA

Vapor Density:NA

Spec Gravity:1.27

Evaporation Rate & Reference:1.0

Solubility in Water:NEGLIGIBLE

Appearance and Odor:VISCOUS, BLACK WITH TAR ODOR.

## ===== Stability and Reactivity Data =====

=====

Stability Indicator/Materials to Avoid: YES

NK

Conditions to Avoid Polymerization: BURNING MATERIAL CAN PRODUCE  
HAZARDOUS DECOMPOSITION PRODUCTS

===== Disposal Considerations =====

Waste Disposal Methods: BURY IN APPROVED LAND FILL OR BURN IN APPROVED  
INCINERATOR.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department  
of Defense. The United States of Am

erica in no manner whatsoever,

expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.