

HYSAN CORPORATION -- POLISH FURNITURE LIQ EMUL CLEAR & POL W/OIL -- 7930-00-205-2876

=====
Product Identification
=====

Product ID:POLISH FURNITURE LIQ EMUL CLEAR & POL W/OIL

MSDS Date:09/30/1986

FSC:7930

NIIN:00-205-2876

MSDS Number: BHMGW

=== Responsible Party ===

Company Name:HYSAN CORPORATION

Address:4309 S. MORGAN STREET

City:CHICAGO

State:IL

ZIP:60609

Country:US

Info Phone Num:312-376-8981

Emergency Phone Num:312-523-1010

CAGE:HYSAN

=== Contractor Identification ===

Company Name:HYSAN CORP (BOUGHT BY HYSAN/AMP-NONE IN CHICAGO)

Address:919 W 38TH ST

Box:City:CHICAGO

State:IL

ZIP:60609-1419

Country:US

Phone:NONE

CAGE:27689

Company Name:HYSAN CORPORATION

Address:2929 ALLEN PARKWAY, SUITE 2130

City:HOUSTON

State:TX

ZIP:77019

Country:US

Phone:713-620-7740

CAGE:HYSAN

=====
Composition/Information on Ingredients
=====

Ingred Name:PETROLEUM DISTILLATE

CAS:64742-53-6

RT

ECS #:PY8036000
Fraction by Wt: 40-50%
Other REC Limits:500 PPM

===== Hazards Identification =====

Routes of Entry: Inhalation:NO Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYES: MAY CAUSE IRRITATION. SKIN: MAY
CAUSE IRRITATION UPON PROLONGED CONTACT. INGESTION: HARMFUL OR
FATAL IF SWALLOWED. ASPIRATION OF LIQUID MAY CAUSE CHEMICAL
PNEUMONITIS.
Explanation of Carcinogenicity:
NO
Effects of Overexposure:POSSIBLE IRRITATION.

===== First Aid Measures =====

First Aid:EYES: FLUSH WITH WATER. CALL PHYSICIAN IF IRRITATION
PERSISTS.

===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:NONE
Lower Limits:1
Upper Limits:7
Extinguishing Media:FOAM, CO2 OR DRY CHEMICAL
Fire Fighting Procedures:FIGHT AS A HYDROCARBON FIRE.
Unusual Fire/Explosion Hazard:TOXIC VAPORS FORMED UPON COMBUSTI
ON.

===== Accidental Release Measures =====

Spill Release Procedures:WIPE UP SPILLS THEN WASH WITH CLEANER. FLOORS
MAY BE SLIPPERY; USE CAUTION TO AVOID FALLS.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A DRY COOL AREA. KEEP OUT OF
REACH OF CHILDREN. KEEP FROM FREEZING.
Other Precautions:READ ENTIRE LABEL BEFORE USING.

===== Exposure Controls/Personal Protection =====

Re

Respiratory Protection:NONE REQUIRED.

Ventilation:LOCAL EXHAUST NONE REQUIRED. MECHANICAL, MAINTAIN ADEQUATE VENTILATION.

Protective Gloves:NONE REQUIRED.

Eye Protection:SAFETY GLASSES.

Other Protective Equipment:NONE REQUIRED.

Work Hygienic Practices:NA

Supplemental Safety and Health

NK

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:212 F

Melt/Freeze Pt:M.P/F.P Text:32 F

Vapor Pres:18

Vapor Density:< 1

Spec Gravity:0.96

Evaporation Rate & Refe

rence:< 1 (BUTYL ACETATE=1)

Solubility in Water:DISPERSIBLE

Appearance and Odor:OPAQUE, VISCOUS WHITE LIQUID PLEASANTLY SCENTED.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

NONE

Stability Condition to Avoid:NONE

Hazardous Decomposition Products:OXIDES OF CARBON FORMED UPON COMBUSTION.

===== Disposal Considerations =====

Waste Disposal Methods:REPLACE CAP AND DISCARD CONTAINER IN TRASH.

Di

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.

