

BEVERLY MANUFACTURING COMPANY -- FAMOWOOD -- 8010-00-262-9172

=====
Product Identification
=====

Product ID:FAMOWOOD

MSDS Date:04/01/1989

FSC:8010

NIIN:00-262-9172

MSDS Number: BHMHS

=== Responsible Party ===

Company Name:BEVERLY MANUFACTURING COMPANY

Box:73233

City:LOS ANGELES

State:CA

ZIP:90003

Country:US

Info Phone Num:213-755-8564

Emergency Phone Num:800-458-3805

Preparer's Name:TIM AYERS

CAG

E:DO074

=== Contractor Identification ===

Company Name:BEVERLY MANUFACTURING COMPANY

Address:PO BOX 73233

Box:73233

City:LOS ANGELES

State:CA

ZIP:90003

Phone:800-458-3805

CAGE:DO074

Company Name:BEVERLY MFG CO

Address:9118 S MAIN ST

Box:City:LOS ANGELES

State:CA

ZIP:90003-3723

Country:US

Phone:213-755-8564

CAGE:21766

=====
Composition/Information on Ingredients
=====

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS:78-93-3

RTECS #:EL6475000

Fraction by Wt: 8

%
OSHA PEL:200 PPM/300 STEL
ACGIH TLV:200 PPM/300STEL 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:ACETONE (SARA III)
CAS:67-64-1
RTECS #:AL3150000
Fraction by Wt: 8%
OSHA PEL:1000PPM
ACGIH TLV:750PPM/1000STEL;9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:PARAFFINIC, NAPHTHENIC, & AROMATIC BLEND
(VAPOR PRESSURE 80 MMHG @ 100F)
CAS:64742-89-8
OSHA PEL:200 PPM
ACGIH TLV:100 PPM

Ingred Name:ISOPROPYL ALCOHOL (SARA III)
CAS:67-63-0
RTECS #:NT8050000
OSHA
PEL:400 PPM/500 STEL
ACGIH TLV:400 PPM/500STEL;9192

Ingred Name:VOC. ORGANIC CMPD 3.15 LB/GAL LESS WATER & NPRS* 377 G/L
LESS WATER VOC. 3.15 LB/GAL SOLIDS 377 G/L SOLIDS CALCU
RTECS #:9999999VO

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:HIGH VAPOR CONCENTRATIONS MAY PRODUCE
CENTRAL NERVOUS SYSTEM DEPRESSION IF INHA
LOR INGESTED.

Effects of Overexposure:EYE: LIQUID IS SEVERLY IRRITATING. HIGH VAPOR
CONCENTRATIONS ARE ALSO IRRITATINGSKIN: LIQUID IS MILDLY
IRRITATING. PROLONGED/REPEATED CONTACT CAN RESULT IN DEFATTING OF
SKIN.INHAL/INGST: GIDDINESS, DI ZZINESS & NAUSEA, IN EXTREME CASES
UNCONSCIOUS & DEATH

Medical Cond Aggravated by Exposure:PREEXISTING LIVER OR KIDNEY DISEASE

===== First Aid Measures =====

First Aid:EYE: IMMED. FLUSH W/PLENTY OF WTR FOR

15 MINS. HOLDING

EYELIDS,GET MED. ATTN. SKIN: FLUSH WITH WATER, GET MEDICAL ATTENTION IF IRRITATION PERSISTS INHAL: REMOVE TO FRESH AIR & PROVIDE OXY GEN, GET MEDICAL ATTENTIONINGST: DONOT GIVE LIQ IF UNCONS. OR VERY DROWSY.GIVE 2 OR MORE GLASSES OF WTR & INDUCE VOMITING KEEP VICTIMS HEAD BELOW HIPS WHILE VOMITING, GET MEDICAL ATTN.

=====
===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:-1F/-18.33C

Lower Limits:1

Upper

Limits:13

Extinguishing Media:ALCOHOL FOAM, CO2, DRY CHEMICAL

Fire Fighting Procedures:EXTREMELY FLAMMABLE. COOL FIRE EXPOSED CONTAINERS WITH WATER. CLEAR AREA OF PERSONNEL & ISOLATE. DO NOT ENTER CONFINED FIRE SPACE W/O FULL BUNKER GEAR OR SCBA.

Unusual Fire/Explosion Hazard:CONTAINERS EXPOSED TO INTENSE HEAT FROM FIRES SHOULD BE COOLED WITH WATER TO PREVENT VAPOR PRESSURE BUILD UP WHICH COULD RESULT IN CONTAINER RUPTURE

=====
===== Accidental Release Measures =====

Spill Release Procedures:EXTREMELY FLAMMABLE. REMOVE ALL SOURCES OF IGN. HANDLING EQUIP. MUST BE GROUNDED TO PREVENT SPARK-ING. PLACE IN NON LEAKING CONTAINERS FOR PROPER DISPOSAL.

=====
===== Handling and Storage =====

Handling and Storage Precautions:KEEP LIQ./VAPOR AWAY F/HEAT,SPARKS, & FLAMES.VAPORMAY ACCUM. & TRAVEL TO IGN. SOURCES DISTANT FROM HANDLING SITE. KEEP CONTNRS CLSD W/NOT IN USE.

Other Precautions:CONTAINERS EVEN EM

PTIED ONES CONTAIN EXPLOSIVE

VAPORS. DONOT CUT,DRILL,GRIND,WLDOR PERFORM SIMILAR OPER. ON/NEAR CONTNRS. GROUND FIXED EQUIP. BOND & GROUND TRANSFER CONTAINERS & EQUIP. STATIC ELEC. MA Y ACCUMULATE & CREATE A FIRE HAZARD.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF EXPOSURE EXCEEDS OCCUPATIONAL EXPOSURE LIMITS, USE A NIOSH APPRVD RESPIRATOR TO PREVENT OVEREXPOSURE. IN ACCORDANCE W/29CFR1910.134. USE EITHER AN ATMOSPHERESUPPLYI

NG

RESPIRATOR OR AN AIR PURIFYING RESPIRATOR FOR ORGANIC VAPORS.

Ventilation:EXPLOSION PROOF VENTILATION AS REQUIRED TO CONTROL VAPOR CONCENTRATIONS.

Protective Gloves:RUBBER OR VINYL COATED

Eye Protection:CHEMICAL GOGGLES

Other Protective Equipment:WEAR IMPERVIOUS CLOTHING. EYEWASH FOUNTAINS & SAFETY SHOWERS SHOULD BE EASILY ACCESSIBLE.

Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING, AND BEFORE EATING, DRINKING, OR SMOKING.

Supplemental Safety and Health

NK

=====

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P. Text:133-206F

Vapor Density:> AIR

Spec Gravity:1.5

Evaporation Rate & Reference:SLOWER THAN ETHER

Solubility in Water:NIL

Appearance and Odor:COLORED PASTE APPEARANCE WITH SOLVENT ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS, ALKALINE MATERIALS, & STRONG ACIDS.

Stability Condition to Avoid:HEAT, SPARKS, FLAME, AND PRE

VENT VAPOR

ACCUMULATION

Hazardous Decomposition Products:CARBON MONOXIDE, OXIDES OF NITROGEN & UNIDENTIFIED ORGANIC COMPOUNDS.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE, AND LOCAL REGULATIONS. IF PRODUCT BECOMES A WASTE MATERIAL IT WOULD BE CONSIDERED A HAZARDOUS WASTE.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by

elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.