

SHEFFIELD BRONZE PAINT CORPORATION -- PRUSSIAN BLUE(IRON)2A OIL COLORS 10-860 --  
8010-00-281-2734

===== Product Identification =====

Product ID:PRUSSIAN BLUE(IRON)2A OIL COLORS 10-860

MSDS Date:09/27/1989

FSC:8010

NIIN:00-281-2734

MSDS Number: BHMJK

=== Responsible Party ===

Company Name:SHEFFIELD BRONZE PAINT CORPORATION

Address:17814 S. WATERLOO ROAD

City:CLEVELAND

State:OH

ZIP:44119

Country:US

Info Phone Num:216-481-8300

Emergency Phone Num:216-481-8300

CAGE:91071

=== Contractor Identification ===

Company Name:SHEFFIELD BRONZE PAINT CORP

Address:17814 S WATERLOO RD

Box:City:CLEVELAND

State:OH

ZIP:44119-3221

Country:US

CAGE:91071

===== Composition/Information on Ingredients =====

Ingred Name:LINSEED OIL

CAS:8001-26-1

RTECS #:QI9690000

Fraction by Wt: 40.5%

Other REC Limits:NONE

Ingred Name:IRON BLUE

CAS:10438-43-8

Fraction by Wt: 34.3%

Other REC Limits:NONE

Ingred

Name:ALIPHATIC NAPTHA, VMP 66  
CAS:6472-48-9  
Fraction by Wt: 25.0%  
Other REC Limits:NONE  
OSHA PEL:300 PPM  
ACGIH TLV:300 PPM

===== Hazards Identification =====

Effects of Overexposure:EYES: CAN CAUSE SEVERE IRRITATION, REDNESS, TEARING, BLURRED VISION. SKIN: PROLONG OR REPEATED CONTACT CAN CAUSE MODERATE IRRITATION, DEFATTING,DERMATITIS. BREATHING CAN CAUSE NASAL AND RESPIRATOR Y IRRITATION. SWALLOWING: CAN CAUSE GASTROINTESTINAL IRRITATION,NAU  
SEA, VOMITING, AND DARRHEA.

===== First Aid Measures =====

First Aid:IF SWALLOWED DO NOT INDUCE VOMMITTING. CALL DR IMMEDIATELY.  
SKIN: WASH THOROUGHLY WASH EXPOSED AREA WITH SOAP AND WATER. IF IN EYES:FLUSH WITH LARGE AMOUNTS OF WATER. IF BREATHED : IF AFFECTED, REMOVE INDIVIDUAL TO FRESH AIR. IF BREATHING DIFFICULT, ADMINISTER OXYGEN. KEEP PERSON WARM, QUIET, GET MEDICAL ATTENTION.

===== Fire Fighting Measures =====  
=====

Flash Point Method:TCC  
Flash Point:106F.  
Lower Limits:1 PERCENT  
Extinguishing Media:CO-2, DRY CHEMICAL, FOAM, FOG  
Fire Fighting Procedures:DO NOT ENTER AREA WITHOUT PROTECTIVE EQUIPMENT  
Unusual Fire/Explosion Hazard:VAPORS ARE HEAVIER THAN AIR. THEY MAY TRAVEL ALONG GROUND OR ACCUMULATE IN LOW, UNVENTILATED AREAS.  
PRODUCT WILL FLOAT AND CAN BE REIGNITED ON SURFACE OF WATER.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE  
ALL SOURCES OF IGNITION,VENTILATE,  
AVIOD BREATHING VAPORS. REMOVE WITH INERT ABSORBENT.

===== Handling and Storage =====

Handling and Storage Precautions:HANDLE AS A CONBUSTIBLE STORE IN A COOL DRY PLACE.USE ADEQUATE VENTILATION EQUIVALENT TO THE OUTDOORS  
Other Precautions:KEEP AWAY FROM HEAT, SPARKS, OPEN FLAMES, SMOKING  
SHOULD BE PROHIBITED WHERE USED

===== Exposure Controls/Personal Protection =====

Respiratory Protection:N

OISH APPROVED SCBA  
Ventilation:LOCAL EXHAUST EXPLOSION PROOF EQUIPMENT  
Protective Gloves:(BUNA-N)  
Eye Protection:SAFETY GLASSES WITH SIDESHIELDS  
Other Protective Equipment:SAFETY SHOWER  
Supplemental Safety and Health  
NK

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:325F-385F  
Vapor Density:>AIR  
Evaporation Rate & Reference:SLOWER THEN ETHER  
Percent Volatiles by Volume:33.5

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
STRONG OXIDIZING MATERIAL  
Hazardous Decomposition Products:CARBON MONOXIDE &/OR CARBON DIOXIDE ON COMBUSTION.  
Conditions to Avoid Polymerization:IT WILL NOT OCCUR

===== Disposal Considerations =====

Waste Disposal Methods:DESTROY BY LIQUID INCINERATION. DISPOSE IN ACCORDANCE WITH FEDERAL, STATE, AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.