

DAVLIN PAINT COMPANY -- DECK ENAMEL (F20L) -- 8010-00-285-4871

===== Product Identification =====

Product ID:DECK ENAMEL (F20L)

MSDS Date:02/15/1989

FSC:8010

NIIN:00-285-4871

MSDS Number: BHMJV

=== Responsible Party ===

Company Name:DAVLIN PAINT COMPANY

Address:1401 E 14TH

City:OAKLAND

State:CA

ZIP:94606-4401

Country:US

Preparer's Name:PATRICIA SHAW

CAGE:HO931

=== Contractor Identification ===

Com

pany Name:DAVLIN PAINT CO

Address:1401 E 14TH

Box:City:OAKLAND

State:CA

ZIP:94606-4401

Country:US

CAGE:91007

Company Name:DAVLIN PAINT COMPANY

Box:2308

City:BERKELEY

State:CA

ZIP:94702

Country:US

Phone:415-848-2863

CAGE:HO931

===== Composition/Information on Ingredients =====

Ingred Name:MINERAL SPIRITS (HYDROCARBON MIXTURE

VAPOR PRESSURE 2 MMHG @ 68F

CAS:64741-41-9

Fraction by Wt: 30%

OSHA PEL:500 PPM

ACGIH TLV:100 PPM

Ingred Name:TALC (CONTAINING NO ASBESTOS)

CAS:14807-96-6
RTECS #:WW2710000
Fraction by Wt: 35%
OSHA PEL:2 MG/M3 RDUST
ACGIH TLV:2 MG/M3 RDUST; 9192

Ingred Name:LEAD COMPOUNDS (56% PB) REPRODUCTIVE TOXIN
CAS:70084-67-2
Fraction by Wt: .37%
OSHA PEL:0.05 MG/M3 (PB)
ACGIH TLV:0.15 MG/M3 (PB);8990

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:YES OSHA:NO
Health Hazards Acute and Chronic:EXPOSURE TO LIQUIDS, VAPORS, M
ISTS OR
FUMES SHOULD BE MINIMIZED. EXPOSURE MAY CAUSE CENTRAL NERVOUS
SYSTEM, RESPIRATORY SYSTEM, LUNGS, EYES, SKIN, GASTROINTESTINAL
TRACT, LIVER, SPLEEN & KIDNEYS. CH RONIC EXPOSURE TO LEAD CAN LEAD
TO LEADPOSITIONING.
Explanation of Carcinogenicity:CRYSTALLINE SILICA IS LISTED AS A
CARCINOGEN.
Effects of Overexposure:EYE: SEVERE IRRITATION, TEARING, REDNESS &
BLURRED VISION. SKIN: MODERATE
IRRITATION,DEFATTING, & DERMITITIS.
INHL: NASAL,RESPIRATORY IR
RIT.,DIZZINESS ,WEAKNESS,FATIGUE,NAUSEA,&
HEADACHE.INGST: IRRIT. DIGEST. TRACT,CONSTIPATION,SLEEP
DIST.,FATIGUE,HDACHE,LS APPETITE.
Medical Cond Aggravated by Exposure:CHRONIC LUNG DISEASE,
DERMATOLOGICAL CONDITIONS, NAUSEA.

===== First Aid Measures =====

First Aid:EYE: FLUSH W/WTR FOR 15 MINS.OCCASIONALLY LIFTING
EYELIDS.OBTAIN MED. ATTENTION.SKIN:REMOVE CONTAMINATED
CLOTHING,WASH THOROUGHLY W/SOAP & WTR. SEE PHYSICIAN. INHL: REMOVE

VICTIM TO FRESH AIR. APPLY ARTIFICIAL RESPIRATION OR OXYGEN IF NEEDED. CONSULT A PHYSICIAN.; INGEST: DO NOT INDUCE VOMITING. GIVE WATER OR MILK TO DRINK & GET MEDICAL ADVICE. IF NEEDED TAKE PERSON TO NEAREST HOSPITAL.

===== Fire Fighting Measures =====

Flash Point Method:SCC

Flash Point:105F/40.56C

Lower Limits:1.0

Upper Limits:6.1

Extinguishing Media:FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG

Fire Fighting Procedures:WATER MAY BE INEFFECTIV

E BUT MAY BE USED AS

FOG FOR COOLING. FIRE FIGHTERS AND OTHERS EXPOSED TO PRODUCTS SHOULD WEAR SELF CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY EXPLODE WHEN

EXPOSED TO EXTREME HEAT. ISOLATE FROM HEAT, ELECTRICAL EQUIPMENT, SPARKS, AND OPEN FLAME.

===== Accidental Release Measures =====

Spill Release Procedures:EVACUATE ALL PERSONNEL. REMOVE ALL IGNITION SOURCES. DIKE AROUND THE SPILL AREA. COVER SPILL

WITH INERT

ABSORBANT & TRANSFER USING NON SPARKING TOOLS.

===== Handling and Storage =====

Handling and Storage Precautions:STORE BELOW 80F. STORE IN ORIGINAL CONTAINER. DO NOT STORE NEAR OXIDIZING AGENTS OR ACIDS. MAY TRAVEL CONSID. DISTANCE TO SOURCE OF IGN. & FLSHBK

Other Precautions:DO NOT TAKE INTERNALLY. GROUND ALL CONNECTIONS, CONTAINERS, WHEN POURING OR TRANSFERING TO MINIMIZE STATIC. KEEP AWAY FROM FEED & FOOD PRODUCTS. K

KEEP AWAY FROM CHILDREN. THIS

PRODUCT IS INTENDED FOR INDUSTRIAL USE ONLY.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE AIR SUPPLIED RESPIRATOR OR A SELF CONTAINED BREATHING APPARATUS.

Ventilation:SUFFICIENT VENTILATION TO CONTROL EXPOSURE.

Protective Gloves:PROTECTIVE GLOVES

Eye Protection:CHEMICAL SAFETY GLASSES

Other Protective Equipment:IMPERMEABLE APRONS & PROTECTIVE CLOTHING.

USE OF HEAD CAPS IS STRONGLY RECOMMENDED.

Work Hy

gienic Practices:WASH BEFORE EATING, TOILETING OR SMOKING.
Supplemental Safety and Health
NK

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:315F
Vapor Density:> AIR
Spec Gravity:1.2
Evaporation Rate & Reference:SLOWER THAN ETHER
Solubility in Water:INSOLUBLE
Appearance and Odor:PIGMENTED LIQUID. SOLVENT ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS
Stab
ility Condition to Avoid:DO NOT EXPOSE TO HEAT OR IGNITION SOURCES.
Hazardous Decomposition Products:CARBON DIOXIDE/MONOXIDE, ORGANIC ACIDS

===== Disposal Considerations =====

Waste Disposal Methods:KEEP OUT OF DRAINS,SEWERS & WATERWAYS. DISPOSE
OF IN ACCORDANCE WITH FEDERAL, STATE, AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense.

The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.