

CHEMRAY COATING CORP -- ENAMEL, ALKYD, GLOSS, LOW VOC CONTENT -- 8010-00-286-7749

=====
Product Identification
=====

Product ID:ENAMEL, ALKYD, GLOSS, LOW VOC CONTENT

MSDS Date:09/26/1989

FSC:8010

NIIN:00-286-7749

MSDS Number: BHMJZ

=== Responsible Party ===

Company Name:CHEMRAY COATING CORP

Address:209 N MICHIGAN AVE

Box:NA

City:KENILWORTH

State:NJ

ZIP:07033

Country:US

Info Phone Num:201-245-1111

Emergency Phone Num:201-245-1111

Preparer's Name:FRED ARMSTRONG

CAGE:33832

=== Contractor Identification ===

Company Name:CHEMRAY COATING CORP

Address:209 N MICHIGAN AVE

Box:City:KENILWORTH

State:NJ

ZIP:07033

Country:US

Phone:201-245-1111

CAGE:33832

=====
Composition/Information on Ingredients
=====

Ingred Name:PETROLEUM SOLVENT, M.S. 66

CAS:8052-41-3

Fraction by Wt: 15%

OSHA PEL:500 PPM

ACGIH TLV:100 PPM; 9293

Ingred Name:SUPER HIFLASH NAPHTHA, PETROLEUM SOLVENT

CAS:64742-95

-6
Fraction by Wt: 6%
OSHA PEL:200 PPM
ACGIH TLV:100 PPM

Ingred Name:PM ACETATE, (ESTER SOLVENT)
CAS:108-65-6
RTECS #:AI8925000
Fraction by Wt: 9%
OSHA PEL:100 PPM
ACGIH TLV:100 PPM

Ingred Name:VOC. ORGANIC CMPD 3.0 LB/GAL LESS WATER & NPRS* 360 G/L
MAX VOC. AFTER THINNING = 3.4 LBS/GLS OR 408 GRAMS/LITER
RTECS #:9999999VO

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Health Hazards Acute and Chronic:OVEREX
POSURE-NAUSEA, HEADACHE,
DIZZINESS CAUSED BY OVER INHALATION.
Effects of Overexposure:OVEREXPOSURE-NAUSEA, HEADACHE, DIZZINESS CAUSED
BY OVER INHALATION.
Medical Cond Aggravated by Exposure:NONE GENERALLY KNOWN

=====
First Aid Measures
=====

First Aid:EYE CONTACT: FLUSH WITH WATER 15 MINUTES OR UNTIL IRRITATION
SUBSIDES. IF IRRITATION PERSISTS, CALL PHYSICIAN. SKIN CONTACT:
REMOVE CONTAMINATED CLOTHING & WASH THOROUGHLY WITH SOAP & WATER.
INHALATION : IF OVERCOME BY VAPORS, REMOVE TO FRESH AIR, CALL
PHYSICIAN. AND INGESTION: DO NOT INDUCE VOMITING, CALL PHYSICIAN.

=====
Fire Fighting Measures
=====

Flash Point Method:SCC
Flash Point:103 F/ 40 C
Autoignition Temp:Autoignition Temp Text:***
Lower Limits:0.7
Upper Limits:13.1
Extinguishing Media:CARBON DIOXIDE, FOAM, WATER FOG, DRY CHEMICAL
Fire Fighting Procedures:USE AIR SUPPLIED BREATHING EQUIPMENT FOR
ENCLOSED CONTAINERS WITH WATER SP

RAY. AVOID BREATHING VAPORS
AND/OR FUMES.

Unusual Fire/Explosion Hazard:IF LEAK OR SPILL HAS IGNITED, USE WATER
SPRAY TO DISPERSE THE VAPORS FROM FIRE FIGHTERS.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL IGNITION SOURCES. KEEP FROM HEAT,
SPARK& OPEN FLAME. ADD ABSORBENT (SAND, EARTH, SAWDUST)TO SPILL.
VENTILATE AREA (OPEN WINDOW, DOORS). IF LARGE SPILL KEEP FROM
ENTERING SEWERS/WATERCOURSES BY DIKING. ADVISE AUT
HORITIES IF
PRODUCT ENTERS.
Neutralizing Agent:NA

===== Handling and Storage =====

Handling and Storage Precautions:STORE AWAY FROM IGNITION SOURCES. KEEP
COOL, DRY, WELL VENTILATED. AVOID DIRECT SUNLIGHT & EXTREME
TEMPERATURES, HOT OR COLD.
Other Precautions:AVOID EYE AND/OR SKIN CONTACT. AVOID INHALATION
AND/OR INGESTION OF MISTS, SPRAYOR VAPORS. AVOID BREATHING SANDING
OR BLASTING DUST.

===== Exposure Controls/Personal Protec
tion =====

Respiratory Protection:USE HYDROCARBON VAPOR CANISTER OR SUPPLIED AIR
RESPIRATOR IN CONFINED AREAS.
Ventilation:LOCAL EXHAUST-FACE VELOCITY 60FPM, SPECIAL-USE ONLY WITH
ADEQUATE VENTILATION. MECHANICAL-USE EXPLOSION PROOF EQUIPMENT
Protective Gloves:CHEMICAL RESISTANT GLOVES
Eye Protection:SPLASH GOGGLES OR FACE SHIELD
Other Protective Equipment:USE CHEMICAL RESISTANT APRON OR CLOTHING
Supplemental Safety and Health
NK

===== Physical/Chemical Propertie
s =====

HCC:F4
Boiling Pt:B.P. Text:308F/155C
Melt/Freeze Pt:M.P/F.P Text:0F/-17.8C
Decomp Temp:Decomp Text:600F/316C
Vapor Pres: