

PRATT & LAMBERT, INC. -- EN ALKYD GLOSS YELLOW 13613 ID742316 -- 8010-00-297-2010
===== Product Identification =====

Product ID:EN ALKYD GLOSS YELLOW 13613 ID742316

MSDS Date:03/22/1988

FSC:8010

NIIN:00-297-2010

MSDS Number: BHMMB

=== Responsible Party ===

Company Name:PRATT & LAMBERT, INC.

Address:16116 E 13TH ST

Box:2153

City:WICHITA

State:KS

ZIP:67201

Country:US

Preparer's Name:W.A. ELLISON

CA

GE:FO127

=== Contractor Identification ===

Company Name:PRATT & LAMBERT, INC/BUFFALO, NY 14240

Box:22

CAGE:FO127

Company Name:PRATT AND LAMBERT INC

Address:Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

===== Composition/Information on Ingredients =====

Ingred Name:VM&P NAPHTHA (LIGROINE)

CAS:8032-32-4

RTECS #:OI6180000

OSHA PEL:300 PPM/400 STEL

ACGIH TLV:300 PPM; 9192

Ingred Name:TITANIUM DIOXIDE

CAS:13463-67-7

RTECS #:XR2275000

OSH

A PEL:15 MG/M3 TDUST
ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:MINERAL SPIRITS
(VP 2 MM HG @ 20 DEG.C)
CAS:64475-85-0
RTECS #:PY8240000
OSHA PEL:500 PPM 2950 MG/CU.M
ACGIH TLV:100 PPM 525 MG/CU.M.

Ingred Name:VOC. ORGANIC CMPD 3.7 LB/GL LESS WATER & NPRS* 444 G/L
LESSWATER VOC 8.8 LB/GAL SOLIDS 1056 G/L SOLIDS CALCULATED
RTECS #:9999999VO

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Report

s of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:SWALLOWING: GASTROINTESTINAL
IRRITATION, NAUSEA, VOMITING. ASPIRATION OF MATERIAL INTO LUNG MAY
CAUSE CHEMICAL PNEUMONITIS. INHALATION: NOSE/THROAT IRRITATION. MAY
CAUSE ACUTE CENTRAL NERVOUS SYSTEM DEPRESSION. EYE: MAY CAUSE EYE
IRRITATIONSKIN: MAY CAUSE DEFATTING AND IRRITATION OF THE SKIN.

Explanation of Carcinogenicity:NONE LISTED

Effects of Overexposure:REPORTS HAVE ASSOCIATED PROLONGED AND REPE
ATED

OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND
NERVOUS SYSTEM DAMAGE. INTENTIONAL MISUSE BY DELIVERATELY INHYALING
THE CONTENTS MAY BE HA RMFUL OR FATAL.

=====
First Aid Measures
=====

First Aid:SWALLOWING: CALL POISON CONTROL CENTER OR EMERGENCY ROOM OR
PHYSICIAN IMMED. INHALATION: REMOVE TO FRESH AIR. IF BREATHING
HAS STOPPED GIVE CPR. KEEP WARM & QUIET. GET MED ATTN IMMED. EYE:
FLUSH W ITH LARGE AMOUNTS OF W
ATER LIFTING UPPERAND LOWER LIDS FOR
15 MIN. GET MED ATTN. SKIN: REMOVE CONTAMINATED CLOTHING. WA SH
WITH SOAP AND WATER. GET MED ATTN. IF IRRITATION PERSISTS.

=====
Fire Fighting Measures
=====

Flash Point:>102F/ 39C

Extinguishing Media:CLASS B FIRE EXTINGUISHERS TO EXTINGUISH FLAMMABLE
LIQUID FIRES. POLYMER FOAM IS PREFERRED FOR LARGE FIRES.

Fire Fighting Procedures:WEAR SELF CONTAINED BREATHING APPARATUS. USE
WATER TO COOL EXPOSED CONTAINER

S TOPREVENT PRESSURE BUILD-UP AND
POSSIBLE EXPLOSION. FOG NOZZLE PREFERRED W/WATER.
Unusual Fire/Explosion Hazard:OVEREXPOSURE TO DECOMPOSITION PRODUCTS
MAY CAUSE HEALTH HAZARD. OBTAIN MEDICAL ATTENTION. WARNING
FLAMMABLE.

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE ALL SOURCES ELECTRICAL AND IGNITION
SOURCES. DIKE SPILL WITH INERT MATERIAL. TRANSFER OR RECOVER IN
METAL CONTAINERS, FOR DISPOSAL. USE ONLY NON-SPARK
ING TOOLS.
PREVENT CONTAMINATION OF SE WERS, STREAMS, GROUNDWATER W/SPILLED
MATERIAL.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABOVE 95 F. STORE LARGE
QUANTITIES IN COMPLIANCE WITH OSHA 29CFR1910.106.
Other Precautions:CLOSE CONTR AFTER EACH USE. DO NOT BREATHE SANDING
DUST. EMPTY CONTR NOT TO BE REUSED ANY PURPOSE. CONTRS SHOULD BE
GROUNDED & BONDED TO THE REC CONTR. DO NOT WELD/BRAZE/CUT ON CONTR.
NEVER USE PRESSURE TO EMPTY. DRUM NOT A PRESSURE VESSEL.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:GEN EXP MAY NOT REQ THE USE OF RESP PROT. RESTR
VENT AREAS A NIOSH APP CHEM CARTRIDGE RES MAY BE REQ.SEE OSHA STD
FOR SPEC RESP PROT REQ FOR LEAD. 29CFR1910.1025 COND SUCH AS
SPRAYING A A MECHANICAL PREFILTER MAY BE REQUIRED. CONFINED
Ventilation:GENERAL DILUTION AND LOCAL EXHAUSE VENTILATION TO MAINTAIN
HAZ SUBSTANCES BELOW LOWE
ST EXPOSURE LIMITS.
Protective Gloves:SOLVENT IMPERMEABLE GLOVES
Eye Protection:SAFETY SPECTACLES
Other Protective Equipment:NOT LIKELY TO BE NEEDED
Supplemental Safety and Health
RESPIRATION PROTECTION CONTINUED: AREAS USE A NIOSH/MSHA APPROVED AIR
SUPPLIED RESPIRATOR.

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:280 TO 388F
Vapor Density:>AIR
Evaporation Rate & Reference:SLOWER THAN ETHER
Percent Volatiles by Volume:60

=====

Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

STRONG ACIDS OR ALKALINE MATERIALS. OXIDIZING MATERIALS.

Stability Condition to Avoid: AVOID EXCESSIVE HEAT AND SOURCES OF IGNITION.

Hazardous Decomposition Products: WILL NOT OCCUR

Conditions to Avoid Polymerization: KEEP AWAY FROM HEAT SPARKS AND FLAME.

===== Disposal Considerations =====

Waste Disposal Methods: INCINERATE ONLY IN EPA PERMITTED FACILITY. RCRA

CLASSIFICATION D001. CONTAMINATED ABSORBANT DISPOSED IN A HAZARDOUS WASTE LANDFILL. DO NOT INCINERATE CLOSED CONTAINERS. DISPOSE ONLY IAW FEDERAL, STATE LOCAL REG.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.