

PRATT AND LAMBERT INC -- ENAMEL ALKYD LUST GRAY 36440 ID741634 -- 8010-00-515-0800
===== Product Identification =====

Product ID:ENAMEL ALKYD LUST GRAY 36440 ID741634

MSDS Date:03/11/1988

FSC:8010

NIIN:00-515-0800

MSDS Number: BHMQF

=== Responsible Party ===

Company Name:PRATT AND LAMBERT INC

Address:16116 E 13TH ST

Box:2153

City:WICHITA

State:KS

ZIP:67201

Country:US

Info Phone Num:316-733-1361

E

mergency Phone Num:716-873-6000 DOT EMER 8002553924

Preparer's Name:W.A. ELLISON

CAGE:61196

=== Contractor Identification ===

Company Name:PRATT AND LAMBERT INC

Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

===== Composition/Information on Ingredients =====

Ingred Name:NO INGREDIENT FOR THIS FORMULATION_INGREDIENT

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingesti

on: YES

Health Hazards Acute and Chronic: SWALLOWING: GASTROINTESTINAL IRRITATION/NAUSEA/VOMITING. ASPIRATION OF MATERIAL INTO LUNG MAY CAUSE CHEMICAL PNEUMONITIS. INHALATION: NOSE/THROAT IRRITATION. ACUTE CENTRAL NERVOUS SYSTEM DEPRESSION. EYE: MAY CAUSE IRRITATION. SKIN: DEFATTING AND IRRITATION OF THE SKIN.

Explanation of Carcinogenicity: AT THE TLV THE TIO₂ MANUFACTURER CONCLUDES THAT THERE IS NO SIGNIFICANT HAZARD FOR MAN.

Effects of Overexposure: PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE.

INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS MAY BE HARMFUL OR FATAL. OVEREXPOSURE TO CRYSTALLINE SILICA MAY CAUSE PNEUMOCONIOSIS A DISABLING LUNG DISEASE.

Medical Cond Aggravated by Exposure: RESPIRATORY CONDITIONS AGGRAVATED BY CRYSTALLINE SILICA.

=====
===== First Aid Measures =====

First Aid: SWALLOW: DO NOT INDUCE VOMITING. GET MED ATTN. INHALATION REMOVE TO FRESH AIR. GIVE CPR IF REQUIRED. GET MED ATTN. EYE FLUSH WITH WATER 15 MIN. SKIN. REMOVE CONTAMINATED CLOTHING AND WASH GET MED ATTN IF IRRITATION PERSISTS. NOTE TO DR: ANY TREATMENT THAT MIGHT BE REQUIRED FOR OVEREXPOSURE SHOULD BE DIRECTED AT THE CONTROL OF SYMPTOMS AND THE CLINICAL CONDITIONS.

=====
===== Fire Fighting Measures =====

Flash Point Method: SCC

Flash Point: >102F / 39C

Extinguishing Media: USE NFPA CLASS B FIRE EXTINGUISHERS. POLYMER FOAM IS PREFERRED FOR LARGE FIRES.

Fire Fighting Procedures: WEAR SCBA. WATER MAY BE INEFFECTIVE, BUT MAY BE USED TO COOL EXPOSED CONTAINERS TO PREVENT PRESSURE BUILD-UP & POSSIBLE AUTO IGNITION/EXPLOSION/EXP TO EXT HEAT.

Unusual Fire/Explosion Hazard: ISOLATE FROM HEAT/ELEC EQUIP SPARKS/FLAME. KEEP CONT CLOSED. CONT MAY EXP WHEN EXPOSED TO EXTREME HEAT. OVEREXPOSURE TO DECOMPOSITION MAY CAUSE HEALTH HAZARD.

=====
===== Accidental Release Measures =====

Spill Release Procedures: DIKE AND CON

CONTAIN THE SPILL WITH INERT MATERIAL. TRANSFER THE LIQUIDS TO COVERED METAL CONTAINERS FOR RECOVERY OR DISPOSAL.

=====
===== Handling and Storage =====

Handling and Storage Precautions: DO NOT STORE ABOVE 120F. STORE IN LARGE QUANTITIES IN COMPLIANCE WITH OSHA 29CFR1910.106
Other Precautions: DO NOT TAKE INTERNALLY, CLOSE CONTAINER AFTER EACH USE. DO NOT BREATHE SPRAYING DUST, EMPTY CONTAINERS MUST NOT BE WASHED AND RE-USED FOR ANY PURPOSE.

=====
=== Exposure Controls/Personal Protection =====

Respiratory Protection: WHEN SPRAYING OUT DOORS, OR IN OPEN OR WELL-VENTILATED AREAS, USE NIOSH APPROVED RESPIRATOR TO REMOVE OVER SPRAY.
Ventilation: PROVIDE GENERAL DILUTION AND LOCAL EXHAUST VENTILATION IN SUFFICIENT VOLUME
Protective Gloves: IMPERMEABLE GLOVES
Eye Protection: WEAR SAFETY SPECTACLES
Other Protective Equipment: NOT LIKELY TO BE NEEDED
Supplemental Safety and Health
NK

=====
===== Physical/Chemical Properties =====

HCC: F4
Boiling Pt: B.P. Text: 280 - 388F
Vapor Density: >AIR
Evaporation Rate & Reference: SLOWER THAN ETHER
Percent Volatiles by Volume: 55

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES
STRONG ACIDS OR ALKALINE MATERIALS.
Stability Condition to Avoid: AVOID EXCESSIVE HEAT AND SOURCES OF IGNITION
Hazardous Decomposition Products: BURNING/WELDING/CUTTING WILL PRODUCE SMOKE, CARBON MONOXIDE AND CARB

ON DIOXIDE.

Conditions to Avoid Polymerization:KEEP AWAY FROM HEAT SPARKS AND
FLAME.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH FEDERAL, STATE &
LOCAL LAWS. INCINERATE ONLY IN EPA PERMITTED FACILITY. DO NOT
INCINERATE CLOSED CONTAINERS. CONTAMINATED ABSORBANT MAY BE
DISPOSED OF IN A HAZARDOUS WASTE LAND.

Disclaimer (provided with this information by the compiling agencies):

This information is formu
lated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.