View NSN Online: https://aerobasegroup.com/nsn/8010-00-515-2258

ELDORADO CHEMICAL COMPANY, INC. -- ELDORADO PR3404, PAINT REMOVER,ID PR-3404 --

8010-00-515-2258

============ Product Identification =========================

Product ID:ELDORADO PR3404, PAINT REMOVER, ID PR-3404

MSDS Date:09/15/1988

FSC:8010

NIIN:00-515-2258

MSDS Number: BHMQM === Responsible Party ===

Company Name: ELDORADO CHEMICAL COMPANY, INC.

Box:34837

City:SAN ANTONIO

State:TX ZIP:78265 Country:US

Info Phone Num:512-6

53-9323

Emergency Phone Num:1-800-531-1088

Preparer's Name: PAT E. SMITH

CAGE:55208

=== Contractor Identification ===

Company Name: ELDORADO CHEMICAL COMPANY, INC.

Address:14350 LOOKOUT ROAD

Box:34837

City:SAN ANTONIO

State:TX

ZIP:78265-4837 Country:US

Phone:800-531-1088/210-653-2060

CAGE:55208

======= Composition/Information on Ingredients ========

Ingred Name: METHYLENE CHLORIDE (SARA III)

CAS:75-09-2

RTECS #:PA8050000 Fraction by Wt: 70%

OSHA PEL:500 PPM/C,1000; Z2

ACGIH TLV:50 P

PM, A2; 9192

EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name:METHYL ALCOHOL (METHANOL) (SARA III)

CAS:67-56-1

RTECS #:PC1400000 Fraction by Wt: 1%

OSHA PEL:S,200PPM/250STEL ACGIH TLV:S,200PPM/250STEL; 93

EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name: METHYL ALCOHOL (METHANOL) (SARA III)

CAS:67-56-1

RTECS #:PC1400000 Fraction by Wt: 10%

OSHA PEL:S,200PPM/250STEL ACGIH TLV:S,200PPM/250STEL; 93

EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name: SODIUM CHROMATE (SARA III)

CAS:7 775-11-3

RTECS #:GB2955000 Fraction by Wt: .7%

OSHA PEL:0.1 PPM CRO3;CEILING ACGIH TLV:0.05 MG CR/M3; 9192

EPA Rpt Qty:10 LBS DOT Rpt Qty:10 LBS

Ingred Name: AMMONIUM HYDROXIDE

CAS:64-11-7

Fraction by Wt: 4% OSHA PEL:25 PPM ACGIH TLV:25 PPM

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Health Hazards Acute and Chronic: INHAL: ACUTE/HIGH ABSORBED IN LUNGS.

CHRONIC:LOW, NO CUMULATIVE EFFECT SKIN: ACUTE/HIGH,

CORROSIVE TO SKIN. CHRONIC:LOW, NO LONG TERM EYE: ACUTE/HIGH, CORROSIVE TO EYES. CH RONIC:LOW, NO LONG TERM Effects of Overexposure:EYE: CORROSIVE TO EYES ON CONTACT, SHORT EXPOSURE WILL CAUSE HAZY VISION. SKIN: CORROSIVE TO SKIN, WILL CAUSE SCARRING WHICH DISAPPEARS IN 1-2 YEARS. INHL: INDUCES CARCOSIS, DIZZINESS, NAUSE A, NO LONG TERM HAZARD.

======================================
First Aid:EYE: FLUSH WITH WATER FOR 15 MINUTES, SE EK MEDICAL ATTENTION. SKIN: FLUSH WITH WATER FOR 10 MINUTES, WASH WITH SOAP AND WATER. INHALATION: REMOVE TO FRESH AIR, IF UNCO NSCIOUS, GIVE OXYGEN & SEEK MEDICAL ATTN
======================================
Flash Point:NONE Lower Limits:NONE Upper Limits:NONE Extinguishing Media:NA Fire Fighting Procedures:SELF CONTAINED BREATHING APPARATUS. Unusual Fire/Explosion Hazard:CONTACT WITH FLAME MAY PRODUCE TOXIC CHLORIDE FUMES AND/OR PHOSGENE G AS.
========= Accidental Release Measures ===========
Spill Release Procedures:ALLOW TO EVAPORATE, SWEEP UP RESIDUE WITH SAWDUST OR SWEEPING COMPOUND.
====== Exposure Controls/Personal Protection ========
Ventilation:S.C.B.A. REQUIRED IF LIMITS EXCEEDED Protective Gloves:POLYETHYLENE Eye Protection:FACE SHIELD OR GOGGLES Other Protective Equipment:FULL WASH RACK GEAR Supplemental Safety and Health NK
======== Physical/Chemical Properties =====

Waste Disposal Methods: CONSULT FEDE RAL, STATE, AND LOCAT REGULATORY AGENCIES FOR PROPER DISPOSAL.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.