View NSN Online: https://aerobasegroup.de/nsn/6850-00-559-2836

OMEGA CHEMICAL CORPORATION -- CLEANING COMPOUND COMBUSTIBLE PC 44B TY I -- 6850-00-559-2836

Product ID:CLEANING COMPOUND COMBUSTIBLE PC 44B TY I MSDS Date:10/01/1989 FSC:6850 NIIN:00-559-2836 MSDS Number: BHMRG === Responsible Party === Company Name: OMEGA CHEMICAL CORPORATION Address:6935 W. 62ND ST. City:CHICAGO State:IL ZIP:60638 Country:US Info Phone Num:312-5 86-8000 Emergency Phone Num:312-586-8000 Preparer's Name:NONE LISTED CAGE:OB5U9 === Contractor Identification === Company Name: OMEGA CHEMICAL CORD; SUCCESSOR TO MSCI CAGE:OB5U9 Company Name: OMEGA CHEMICAL PROD GP, FINE ORGANICS CORP Address:6935 WEST 62ND STREET City:CHICAGO State:IL ZIP:60638 Country:US Phone:312-586-8000, 800-424-9300 CAGE:0B5U9

Ingred Name:PETROLEUM HYDROCARBONS CAS:64741-44-2 ACGIH TLV:100 PPM

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:INHALATION OF HIGH VAPOR CONCENTRATIONS MAY CAUSE DIZZINESS, WEAKNESS, NAUSEA. EXTREME CONCENTRATION IN CONFINED SPACE MAY CAUSE UNCONSCIOUNESS. EXCESS OR RE- PEATED CONTACT WITH SKIN MAY CAUSE IRRIT ATION. CAN CAUSE IRRITATION TO EYES ONCONTACT. Effects of Overexposure:DIZZINESS , WEAKNESS, AND NAUSEA

First Aid:INHALATION: REMOVE TO FRESH AIR. SKIN: WASH WITH SOAP & WATER. EYES: FLUSH WITH LARGE AMOUNTS OF WATER, CALL PHYSICIAN. AND FOR INGESTION: DO NOT INDUCE VOMIT- ING. CALL A PHYSICIAN.

Flash Point Method:TCC Flash Point:135 F/ 57.22 C Lower Limits:NOT EST. Upper Limits:NOT EST. Extinguishing Media:CO2, FOAM Fire Fight ing Procedures:AVOID EXCESSIVE WATER SPRAY APPLICATION Unusual Fire/Explosion Hazard:NONE, TREAT AS HYDROCARBON FIRE

Spill Release Procedures:OUTDOORS, ADD SAND, EARTH OR OTHER SUITABLE ABSOR-BENT TO SPILL AREA. KEEP PRODUCT OUT OF SEWER & WATER COURSES BY DIKING OR IMPOUNDING. INSIDE, ELIMINATE ALL IGNITION SOURCES & REMOVE WITH ABSOR BENT MATERIAL

 Handling and Storage Precautions:REASONABLE CARE AND PRECAUTIONS WHEN HANDLING IS STRONGLY RECOMMENDED.
Other Precautions:USE IN WELL VENTILATED AREAS. REMOVE AND LAUNDER CONTAMINATED CLOTHING BEFORE REUSE.

Respiratory Protection:CARTRIDGE TYPE FOR SOLVENTS REQUIRED WHEN CONCENTRATIONS ARE ABOVE TLV Ventilation:LOCAL EXHAUST RECOMMENDED AND MECHANICAL RECOMMENDED. Protective Gloves:NEOPRENE Eye Protection: SAFETY GOGGLES &/OR FACE SHIELD Other Protective Equipment:PROTECTIVE APRON OR SPLASH GUARD Work Hygienic Practices:REMOVE & LAUNDER ALL CONTAMINATED CLOTHING BEFORE REUSE Supplemental Safety and Health NK

Boiling Pt:B.P. Text:250 F Melt/Freeze Pt:M.P/F.P Text:- 20 F Vapor Pres:NOT DET Vapor Density:NOT DET Spec Gravity:0.86 Evaporation Rate & amp; Reference:< 1 Solubility in Water:MISCIBLE Appearance and Odor:AMBER LIQUID , SOLVENT ODOR

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS Hazardous Decomposition Products:PARTICIAL COMBUSTION MAY PRODUCE CARBON MONOXIDE

Waste Disposal Methods:DISOPOSE OF IN ACCORDANCE WITH 43USG3261 ET. SEQ. RECA & ANY LOCAL, STATE OR FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agenc ies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.