

S.L. GILLMAN PAINT COMPANY -- ALKYD SEMI GLOSS ENAMEL IVORY 27855 -- 8010-00-597-8195

===== Product Identification =====

Product ID:ALKYD SEMI GLOSS ENAMEL IVORY 27855

MSDS Date:11/01/1988

FSC:8010

NIIN:00-597-8195

MSDS Number: BHMRM

=== Responsible Party ===

Company Name:S.L. GILLMAN PAINT COMPANY

Address:2250 MORELAND AVE. SE.

Box:NA

City:ATLANTA

State:GA

ZIP:30315

Country:US

Info Phone Num:404-

622-1326

Emergency Phone Num:404-509-4400

CAGE:OO269

=== Contractor Identification ===

Company Name:S. L. GILLMAN PAINT CO

CAGE:SLGIL

Company Name:S.L. GILLMAN PAINT COMPANY

Address:2250 MORELAND AVENUE, S.E.

City:ATLANTA

Phone:404 622 1326

CAGE:OO269

===== Composition/Information on Ingredients =====

Ingred Name:VM&P NAPHTHA (LIGROINE)

CAS:8032-32-4

RTECS #:OI6180000

Fraction by Wt: 35-40%

OSHA PEL:300 PPM/400 STEL

ACGIH TLV:300 PPM; 9192

===== Hazards Iden

tification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO  
Health Hazards Acute and Chronic:ASPIRATION OF MATERIAL INTO THE LUNGS  
CAN CAUSE CHEMICAL PNEUMONHITIS WHICH CAN BE FATAL. EXCESSIVE  
INHALATION OF VAPORS CAN CAUSE NASAL AND RESPIRATORY IRRITATION.  
Effects of Overexposure:EYE:SEVERE IRRITATION, REDNESS, TEARING,  
BLURRED VISION SKIN:MODERATE IRRITATION,  
DEFATTING, DERMATITIS  
INHAL:DIZZINESS,WEAKNESS,FATIGUE,NAUSEA,  
HEADACHE  
S,UNCONSCIOUSNESS,& ASPHYXIATIONINGST:GASTROINTESTINAL  
IRRITATION,NAUSEA,VOMITING,AND DIARRHEA.  
Medical Cond Aggravated by Exposure:NONE

===== First Aid Measures =====

First Aid:EYE: FLUSH W/LG AMNTS OF WTR,LIFTING EYELIDS OCCASIONALLY,GET  
MEDICAL ATTENTION SKIN: THOROUGHLY WASH EXPOSED AREA W/SOAP &  
WTR.REMOVE CONTAMINATED CLOTHING,GETMEDICAL ATTENTION.;INHAL:REMOVE  
TO FRESH AIR, ADMINISTER OXYGEN, KEEP WARM/QUIETGIVE ARTIFICAL  
RESPIR  
ATION IF NEEDED, GET MEDICAL ATTENTION.  
INGST:DONOT INDUCE VOMITING, KEEP PERSON WARM/QUIET, GET MEDICAL  
ATTENTION.

===== Fire Fighting Measures =====

Flash Point Method:TCC  
Flash Point:105F/40.56C  
Lower Limits:1.0  
Extinguishing Media:FOAM, CO2, DRY CHEMCIAL  
Fire Fighting Procedures:WEAR SCBA WITH FULL FACEPIECE OPERATED IN  
PRESSURE DEMAND OR OTHER POSTIVE PRESSURE MODE WHEN FIGHTING  
FIRES. WATER SPRAY MAY BE INEFFECTIVE.  
Unusual Fire/E  
xplosion Hazard:CONTAINERS MAY EXPLODE WHEN EXPOSED TO  
EXTREME HEAT. VAPORS ARE >AIR & MAY TRVL ALONG GRND,MAYBE MOVED BY  
VENTL & IGNT BY PILOT LHTS,SPRKS,HTRS,ELEC.MTRS,SMOKNG

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE ALL SOURCES OF IGNITION FROM  
AREA.ABSORBLIQ ON PAPER,VERMICULITE,FLR ABSORBENT & TRANSFER TO  
HOOD.DIKE AREA OF SPILL TO PREVENT SPREADING, PUMP LIQ TO SALVAGE  
TANK.REMAINING INTO CONTAINERS PREVENT

RUN OFF TO SEWERS,STREAMS,OR  
BODIES OF WTR

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT USE OF STORE NEAR  
HEAT,SPARK,OPEN FLAME,SUNOR HIGH TEMP.KEEP CLOSURE TIGHT,CONTAINERS  
UPRIGHTTO PREVENT LEAKAGE.AVOID BREATHING SANDING DUST.  
Other Precautions:DONOT WELD OR FLAME CUT AN EMPTY DRUM. DRUMS OF THIS  
MATL SHOULD BE GROUNDED ANDBONDED WHEN POURING.CONTAINERS OF THIS  
MATL MAY BE HAZARDOUS WHEN EMPTIED. EMPTY  
CONTAINERS RETAIN  
PRODUCT RESIDUES .

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF TLV IS EXCEEDED A NIOSH/MSHA JOINTLY APPROVED  
AIR SUPPLIED RESPIRATOR IS ADVISED IN THE ABSENCE OF PROPER  
ENVIRONMENTAL CONTROL. OSHA REGULATIONS ALSO PERMITOTHER NIOSH/MSHA  
RESPIRATORS UNDER SPECI FIED CONDITIONS.  
Ventilation:LOCAL EXHAUST OR SUFFICIENT MECHANICAL TO MAINTAIN EXPOSURE  
BELOW TLV'S  
Protective Gloves:NITRILE RUBBER OR NEOPRENE  
Eye  
Protection:CHEMICAL SPLASH GOGGLES,SAFETY GLASSES  
Other Protective Equipment:IMPERVIOUS CLOTHING AND BOOTS  
Work Hygienic Practices:WASH HANDS BEFORE EATING OR USING WASHROOM  
SMOKE IN SMOKING AREAS ONLY  
Supplemental Safety and Health  
AVOID REPEATED OR PROLONGED CONTACT WITH SKIN.

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:300F  
Vapor Density:> AIR  
Evaporation Rate & Reference:SLOWER THAN ETHER  
Percent Volatiles by Volume:48

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
STRONG OXIDIZING AGENTS  
Stability Condition to Avoid:HIGH TEMPERATURES, OPEN FLAME, AND SPARKS  
Hazardous Decomposition Products:CARBON DIOXIDE,CARBON MONOXIDE,AND  
VARIOUS HYDROCARBONS

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE, AND  
FEDERAL REGULATIONS. REMOVE PERSONS NOT WEARING PROTECTIVE  
EQU

IPMENT FROM AREA UNTIL CLEAN UP HAS BEEN COMPLETED.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.