

CHEMRAY COATINGS, CORP. -- PRIMER FOR WOOD AND METAL -- 8010-00-664-6302

===== Product Identification =====

Product ID:PRIMER FOR WOOD AND METAL

MSDS Date:11/01/1989

FSC:8010

NIIN:00-664-6302

MSDS Number: BHMSY

=== Responsible Party ===

Company Name:CHEMRAY COATINGS, CORP.

Address:209 N. MICHIGAN AVE.

Box:NA

City:KENILWORTH

State:NJ

ZIP:07033

Country:US

Info Phone Num:201-245-1111

Emergency Phone

Num:201-245-1111

CAGE:OBRN9

=== Contractor Identification ===

Company Name:CHEMRAY COATING CORP

Address:209 N MICHIGAN AVE

Box:City:KENILWORTH

State:NJ

ZIP:07033

Country:US

Phone:201-245-1111

CAGE:33832

Company Name:CHEMRAY COATINGS CORP.

Address:209 N. MICHIGAN AVE.

Box:NA

City:KENILWORTH

State:NJ

ZIP:07033

Country:US

Phone:800-924-9300

CAGE:OBRN9

===== Composition/Information on Ingredients =====

Ingred Name:STODDARD SOLVENT

CAS:8052-41-3

RTECS #:WJ8925000

Fraction by Wt: 3

9%  
OSHA PEL:500 PPM  
ACGIH TLV:100 PPM; 9293

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO  
Health Hazards Acute and Chronic:OVEREXPOSURE - NAUSEA, HEADACHE,  
DIZZINESS CAUSED BY OVER INHALATION  
Effects of Overexposure:OVEREXPOSURE - NAUSEA, HEADACHE, DIZZINESS  
CAUSED BY OVER INHALATION  
Medical Cond Aggravated by Exposure:NONE GENERALLY KNOWN

===== First Aid Measures =====

First Aid:EYE: FLUSH W/WATER 15 MIN. UNTIL IRRI SUBSIDES, IF IRRI  
PERSISTS CALL PHYSICIAN.SKIN: REMOVE CONTAMINATED CLOTHING & WASH  
THROUGHLY WITH SOAP & WATER. INHAL: IF OVERCOME BY VAPORS,  
REMOVE TO FRESH AIR, CALL PHYSICIAN.INGST: DO NOT INDUCE VOMITING  
CALL PHYSICIAN.

===== Fire Fighting Measures =====

Flash Point Method:SCC  
Flash Point:103 F/40 C  
Lower Limits:0.9  
Upper Limits:7  
Extinguishing Media:CARBON DIOXIDE, FOAM, WATER FOG, DRY C  
HEMICAL  
Fire Fighting Procedures:USE AIR SUPPLIED BREATHING EQUIPMENT FOR  
ENCLOSED CONTAINERS WITH WATER SPRAY. AVOID BREATHING VAPORS AND  
FUMES.  
Unusual Fire/Explosion Hazard:IF LEAK OR SPILL HAS IGNITED, USE WATER  
SPRAY TO DISPERSE THE VAPORS FROM FIRE FIGHTERS

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL IGNITION SOURCES. KEEP FROM HEAT  
SPARKS& OPEN FLAMES. ADD ABSORBENT (SAND, EARTH, ETC.) VENT AREA.  
IF LG SP

ILL KEEP PRODUCT FROM ENTERING SEWERS/WATERCOURSES BY  
DIKING. ADVISE AUTHORITIES IF PRODUCT ENTERS WATER SYSTEM

===== Handling and Storage =====

Handling and Storage Precautions:STORE AWAY FROM IGNITION SOURCES. KEEP  
IN COOL, DRY, WELL VENTILATED AREAS. AVOID DIRECT SUNLIGHT &  
EXTREME TEMPERATURES HOT OR COLD  
Other Precautions:AVOID EYE, SKIN CONTACT, INHALATION & INGESTION OF  
MISTS, SPRAY OR VAPORS. AVOIDBREATHING SANDING OR BLASTING DUST.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE HYDROCARBON VAPOR CANISTER OR SUPPLIED AIR  
RESPIRATOR IN CONFINED AREA.  
Ventilation:LOCAL EXHAUST-FACE VELOCITY 60FPM SPECIAL-USE ONLY WITH  
ADE-QUATE VENTILATION. MECH-USE EXPLOSION PROOF EQUIPMENT  
Protective Gloves:CHEMICAL RESISTANT  
Eye Protection:SPLASH GOGGLES OR FACE SHIELD  
Other Protective Equipment:USE CHEMICAL RESISTANT APRON OR CLOTHING  
Supplemental Safety and Health  
NK

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:308 F  
Decomp Temp:Decomp Text:600 F  
Vapor Pres:< 10 @ 77F  
Vapor Density:4.8  
Spec Gravity:1.234  
pH:NA  
Evaporation Rate & Reference:0.09  
Solubility in Water:NEGLIGIBLE  
Appearance and Odor:WHITE LIQUID WITH KEROSENE ODOR  
Percent Volatiles by Volume:62  
Corrosion Rate:NA

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
CAN REACT W/OXIDIZING MATERIAL WHEN H

EATED TO DECOMPOSTION.  
Stability Condition to Avoid:HIGH TEMPERATURE  
Hazardous Decomposition Products:CARBON MONOXIDE

===== Disposal Considerations =====

Waste Disposal Methods:ASSURE CONFORMITY WITH APPLICABLE DISPOSAL REG  
DISPOSE OF ABSORBED MATERIAL AT AN APPROVED DISPOSAL SITE OR  
FACILITY. DISPOSE IN COMFORMITY WITH STATEAND FEDERAL REGULATIONS

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated fo  
r use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.