View NSN Online: https://aerobasegroup.de/nsn/8010-00-811-1922

Product ID: ENAMEL ALKYD S.G. GRN 24260 ID745430 MSDS Date:03/31/1986 FSC:8010 NIIN:00-811-1922 MSDS Number: BHMVZ === Responsible Party === Company Name: PRATT & LAMBERT, INC. Address:16116 E 13TH ST Box:2153 City:WICHITA State:KS ZIP:67201 Country:US Preparer's Name:W.A. ELLISON CAG E:FO127 === Contractor Identification === Company Name: PRATT & LAMBERT, INC/BUFFALO, NY 14240 Box:22 CAGE:FO127 Company Name: PRATT AND LAMBERT INC Address:Box:6027 City:CLEVELAND State:OH ZIP:44101-1027 Country:US Phone:216-566-2902 CAGE:61196

Ingred Name:MINERAL SPIRITS (VP 2 MM HG @ 20 DEG C) CAS:8032-32-4 OSHA PEL:500 PPM 2950 MG/CU.M ACGIH TLV:100 PPM 525 MG/CU.M.

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (S

ARA III) CAS:1330-20-7 RTECS #:ZE2100000 OSHA PEL:100 PPM/150 STEL ACGIH TLV:100 PPM/150STEL;9192 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name:TITANIUM DIOXIDE CAS:13463-67-7 RTECS #:XR2275000 OSHA PEL:15 MG/M3 TDUST ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:LEAD CHROMATE (OSHA PEL FOR LEAD FROM 29CFR 1910.1025),(CRO3 CEILING 0.1 MG/M3) CAS:7758-97-6 RTECS #:GB2975000 OSHA PEL:0.05 MG/M3 (PB) ACGIH TLV:0.05MG/M3(CR)A2;8990

Ingred Name:TALC (CONTAINING NO ASBESTOS) CAS:14807-96-6

RTECS #:WW2710000 OSHA PEL:2 MG/M3 RDUST ACGIH TLV:2 MG/M3 RDUST; 9192

Ingred Name:SILICA, CRYSTALLINE - CRISTOBALITE CAS:14464-46-1 RTECS #:VV7325000 OSHA PEL:SEE TABLE Z3 ACGIH TLV:0.05 MG/M3 RDUST9293

Ingred Name:VOC. ORGANIC CMPD 3.7 LB/GAL LESS WATER & NPRS* 444 G/L LESS WATER VOC. 8.3 LB/GAL SOLIDS 996 G/L SOLIDS CALCU RTECS #:9999999VO

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carci

nogenicity:NTP:YES IARC:YES OSHA:NO Health Hazards Acute and Chronic: ASPIR. OF MATL INTO LUNG MAY CAUSE CHEM. PNEUMONITIS CAN BE FATAL. INHL MAY CAUSEACUTE NERV. SYST. DEPRSN. PREPTD EXPSR TO CRYSTALLINE SILICA MAY CAUSE PNEUMOCONIOSIS, A PROGRS. DISABLING LUNG DISEASE. INSOL. CHROMATES MAY CAUSE LIVER DAMAGE. TOLUENE MAY CAUSE LIVER DAMAGE. LEAD MAY RESULT IN SEVR BLOOD, NERV, URNY, REPRODUCT Explanation of Carcinogenicity:CHROMIUM/CHROMIUM COMPOUNDS AND LEAD CHROMATE ARE LISTED AS A POTENTIAL CARCINOGENS Effects of Overexposure: EYE: MAY CAUSE IRRITATION. SKIN: MAY CAUSE DEFATTING & **IRRITATION OF SKIN.** INHAL: ANESTHETIC, NOSE & THROAT IRRIT., H EADACHE, DIZZINESS, CONFUSION, NAUSEA, UNCONSCIOUSNESS, & ASPHYXIATION; INGST: GASTROINTESTINAL IRRIT., NAUSEA, & VOMITING Medical Cond Aggravated by Exposure: PREXISTING RESPIRATORY CONDITIONS MAY BE AGGRAVAT-ED BY EXPOSURE TO CRYSTALLINE SILICA. KIDNEY CONDITIONS MAY BE AGGRAV ATED BY EXPOSURES TO LEAD.

First Aid:EYE: FLUSH W/LG AMNTS OF WTR FOR 15 MINS,LIFTING EYELIDS,GET MEDICAL ATTENTION SKIN: WASH AFFECTED AREA W/SOAP & WTR,REMOVE CONTAMINATED CLOTHES,GET MED. ATTN.INHAL: REMOVE TO FRESH AIR IMMEDIATELY,G IVE ARTIFCL RESPIRATION IF NEEDED, KEEPWARM & QUIET,GET MEDICAL ATTENTION IMMEDIATELY INGST: DO NOT INDUCE VOMITING, CALL A PHYSICIAN IMMEDIATELY!!

Flash Point:80F/26.67C

Extinguishing Media:USE NFPA CLASS BE FIRE EXTINGUISHERS. POLYMER FOAM IS PERFERRED FOR LARGE FIRES.

Fire Fighting Procedures:WEAR SCBA. WTR MAY BE INEFFECTIVE,MAY BE USED TO COOL EXPOSED CONTAINERS TO PRE-VENT PRESS. BUILDUP & POSS. IGN. W/EXPSD TO EXTRM HEAT.W/WTR FOG NOZZLES PREFERD

Unusual Fire/Explosion Hazard: EMERG COND OVEREXPOSURE DECOMP PROD CAUSE HEALTH HAZARD. SYMP MAY NOT BE IMMED. APPAREN

T. OBTAIN MEDICAL ATTENTION. WARNING!! FLAMMABLE

Spill Release Procedures: ELIMINATE ALL SOURCES OF IGNITION. DIKE & CONTAIN SPILL W/INERT MATERIAL. USE NON SPARKING TOOL ONLYPLACE ABSORBENT DIKING MATL IN COVERED METAL CONTAINER FOR DISPOSAL. PREVENT CONTAMINATION OF SEWERS STREAMS, GROUNDWATER W/SPILLED MATL OR USED ABSORB

Handling and St

orage Precautions:DO NOT STORE ABOVE 95 DEG F. STORE LG QTYS IN COM-PLIANCE W/OSHA 29CFR1910.106. CLOSE CONTAINERS AFTER EACH USE. NEVER USE PRESSURE TO EMPTY. Other Precautions:KEEP AWAY FROM CHILDREN. DO NOT BREATHE SANDING DUST. EMPTY CONTAINERS MUST NOT BE WASHED & REUSED FOR ANY PURPOSE. CONTAINERS SHOULD BE GROUNDED & BONDED TO THE RECEIVING CONTAINER. DO NOT WELD,BRA ZE OR CUT ON EMPTY CONTAINERS.

Respiratory Protection:RESTRICTED AREAS US NIOSH APPROVED CHEMICAL CARTRIDGE RESPIRATOR. SPRAYING USE AMECHANICAL FILTER RESPIRATOR. CONFINED AREAS USE A NIOSH APPROVED AIR SUPPLIED RESPIRATOR. Ventilation:LOCAL EXHAUST VENTILATION OR GENERAL DILUTION Protective Gloves:SOLVENT IMPERMEABLE GLOVES Eye Protection:SAFETY GLASSES W/SIDE SHIELDS Other Protective Equipment:NONE Work Hygienic Practices:WASH HANDS THOROUGHLY BEFORE EATING OR DRINKING Supplemental Safety and Health NK

Boiling Pt:B.P. Text:193-395F Vapor Density:> AIR Evaporation Rate & amp; Reference:SLOWER THAN ETHER Percent Volatiles by Volume:55

Stability Indicator/Materials to Avoid:YES STRONG ACIDS OR ALKALINE MATERIALS Stability Condition to Avoid:EXCESSIVE HEAT AND SOURCES OF IGNITION Hazardous Decomposition Products:BURNING, INCLUDE W/HEATED BY WELD OR CUTTING, WILL PROD

UCE SMOKE, CARBON MONOXIDE/DIOXIDE. Conditions to Avoid Polymerization: KEEP AWAY FROM HEAT SPARKS AND FLAME

Waste Disposal Methods:INCINERATE ONLY IN EPA PERMITTED FACILITY. DO NOT INCINERATE CLOSED CONTAINERS. ABSORBANT MAY BE DISPOSED IN A HAZARDOUS WASTE LANDFILL. DISPOSE IN ACCORDANCE WITH FEDERAL, STATE, & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This inform

ation is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.