

WOOLSEY MARINE INDUSTRIES -- TT-E-509B,SAND 23617 -- 8010-00-901-8042

=====  
Product Identification  
=====

Product ID:TT-E-509B,SAND 23617

MSDS Date:11/01/1989

FSC:8010

NIIN:00-901-8042

MSDS Number: BHMXS

=== Responsible Party ===

Company Name:WOOLSEY MARINE INDUSTRIES

Address:480 FRELINGHUYSEN AVENUE

Box:NA

City:NEWARK

State:NJ

ZIP:07114

Country:US

Info Phone Num:800-221-4466

Emergency Phone Num:80

0-548-0489

Preparer's Name:C.A. HOPE

CAGE:OO325

=== Contractor Identification ===

Company Name:WOOLSEY MARINE INDUSTRIES

Box:NA

Phone:212-947-3070

CAGE:OO325

=====  
Composition/Information on Ingredients  
=====

Ingred Name:STODDARD SOLVENT

CAS:8052-41-3

RTECS #:WJ8925000

Fraction by Wt: 30-35%

OSHA PEL:500 PPM

ACGIH TLV:100 PPM; 9293

Ingred Name:TALC (CONTAINING NO ASBESTOS)

CAS:14807-96-6

RTECS #:WW2710000

Fraction by Wt: 5-10%

OSHA PEL:2 MG/M3 RDUST

ACGIH TLV:2 MG/M3 RDUST;

Ingrid Name:TITANIUM DIOXIDE  
 CAS:13463-67-7  
 RTECS #:XR2275000  
 Fraction by Wt: 15-20%  
 OSHA PEL:15 MG/M3 TDUST  
 ACGIH TLV:10 MG/M3 TDUST; 9293

Ingrid Name:BARIUM SULFATE  
 CAS:7727-43-7  
 RTECS #:CR0600000  
 Fraction by Wt: 10-15%  
 OSHA PEL:15 MG/M3 TDUST  
 ACGIH TLV:10 MG/M3 TDUST; 9293

Ingrid Name:ZINC OXIDE  
 CAS:1314-13-2  
 RTECS #:ZH4810000  
 Fraction by Wt: 1-5%  
 OSHA PEL:15MG/M3 TDUST/5 FUME  
 ACGIH TLV:10MG/M3 TDUST; 9293

===== Hazards Identification =====

Routes o

f Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:HIGH CONCENTRATIONS OF VAPORS MAY CAUSE RESPIRATORY TRACT IRRITATION, CENTRAL NERVOUS SYSTEM DEPRESSION, & MAY LEAD TO LUNG CHANGES. ASPIRATION INTO THE LUNG MAY CAUSE CHEMICAL PNEUMONITIS WHICH CAN BE FATAL.

Effects of Overexposure:EYE: MAY CAUSE IRRITATION

SKIN: DEFATTING, REDNESS, CRACKING, BLISTERING, IRRITATION, & DERMAT

ITIS INHAL: HEADACHE,

WEAKNESS, DIZZINESS, IN COORDINATION & POSSIBLE COLLAPSEINGST: GASTROINTESTINAL, NAUSEA, VOMITING, DIARRHEA.

Medical Cond Aggravated by Exposure:INDIVIDUALS W/SKIN,EYE,RESPIRATORY TRACT,LIVER, KIDNEY, & CENTRAL NERVOUS SYSTEM ARE AT A >NORMAL RISK OF DEVELOPING ADVERSE EFFECTS WHEN EXPOSED TOTHIS MATERIALS.

===== First Aid Measures =====

First Aid:EYE: IMMEDIATELY FLUSH W/LG AMNTS OF WTR FOR 15 MINS.,GET MEDICAL

ATTENTION. SKIN: WASH THOROUGHLY W/SOAP & WTR,GET MED.  
AID IF REDNESS,ITCHING,BURNING DEVELOP OR PERSIST.INHAL: REMOVE TO  
FRESH AIR, GIVE ARTIFICIAL RESP. IF NEEDED, GET MED. ATTN.  
INGST:DONOT INDUCE VOMITING,GIVE 1 GLASS OF MILK/ACTWETED  
CHARCOL,MED. ATTN IMMED.

===== Fire Fighting Measures =====

Flash Point Method:CC

Flash Point:102F/39C

Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, FOAM, WTR SPRAY,  
ALCOHOL FOAM

Fire Fighting Pr

cedures:WEAR SCBA. USE WATER TO COOL FIRE EXPSD

CONTAINERS/STRUCTURE/PROTECT PERSONNEL CLOSED CONTAINERS MAY  
EXPLODE WHEN EXPOSED TO EXTRM HEAT.

Unusual Fire/Explosion Hazard:UNDER FIRE CONDITION MAY EMIT

IRRITANT/TOXIC GAS OR FUMES. VAPORS FORM FLAMMABLEEXPLOSIVE  
MIXTURES IN AIR. VAPORS MAY TRAVEL ALONG GROUND TO IGNITION  
SOURCES.

===== Accidental Release Measures =====

Spill Release Procedures:STOP LEAK IF NO RISK INVOLVED. ELIMINATE ALL

SOURCES OF IGNITION.AVOID CONTACT W/HOT LIQ. & FUMES. TAKE UP  
CAREFULLY TO AVOID HEAT/SPARKS. USE AN INERT ABSORBENT TO  
COMPLETE A CLEAN UP. THIS MATL REACT W/OXIDIZING MATERIALS.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP IN A CLSD CONTNR IN COOL,DRY  
VENTILATED AREA.KEEP FROM PHYSCL DAMG.KEEP CONTAINERS CLOSED WHEN  
MATL IS NOT IN USE. GROUND/BOND DRUMS.

Other Precautions:DO NOT USE PRESSURE TO EMPTY CONTAINERS

. DO NOT WEAR

CONTAMINATED CLOTHING. DISCARD CONTAMINATED FOOTWEAR. KEEP AWAY  
FROM HEAT & OPEN FLAME. HANDLE AND USE IN ACCORDANCE W/OSHA  
29CFR1910.106/LOCAL CODES. AVOID SKIN/EYE CONTACT

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE MSHA/NIOSH APPROVED UNITS IF EXPOSURE IS  
ABOVE PEL/TLV. IF WITHIN OSHA PRO-TECTION FACTOR, AIR PURIFYING  
OV/FILTER UNITS OK.

Ventilation:LOCAL EXHAUST OR GENERAL VENTILATION TO KEEP LVLS BE

LW

LIMIT FOR INHALATION OR FLAMMABLE VAPORS.

Protective Gloves: INDUSTRIAL RESIS FLEX TYPE/HVY DTY NEOPRENE

Eye Protection: SAFETY GLASSES/GOGGLES W/SIDESHIELDS

Other Protective Equipment: MAY NEED PROTECTIVE GARMENTS SUCH AS HEAD/NECK COVER, APRONS, PANTJACKETS, COVERALLS, BOOTS, ETC.

Work Hygienic Practices: WASH EXPOSED AREA PROMPTLY/THOROUGHLY AFTER CONTACT W/MATL. WASH BEFORE EATING, DRINKING, SMOKING, OR USING RESTROOMS

Supplemental Safety and Health

DO NOT WEAR CONTACT LENS WITHOUT PROPER EYE PROTECTION WHEN USING THE PRODUCT.

===== Physical/Chemical Properties =====

Vapor Density: > AIR

Spec Gravity: 10.5 LBS/GAL

Viscosity: 67-77 KU

Solubility in Water: NEGLIGIBLE

Appearance and Odor: VISCOUS LIQUID WITH A TYPICAL SOLVENT ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

OXIDIZING AGENTS, HEAT, SPARKS, AND OPEN FLAMES

Hazardous Decomposition Products: CARBON MONOXIDE/DIOXIDE UPON THERMAL

DECOMPOSITION

===== Disposal Considerations =====

Waste Disposal Methods: DISPOSE OF AS AN IGNITABLE HAZARDOUS WASTE IN ACCORDANCE WITH FEDERAL, STATE, & LOCAL REGULATION

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and

di

sclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.