

PRATT & LAMBERT, INC. -- LACQUER ACRYLIC GREEN 14187 ID794430 -- 8010-00-935-7071
===== Product Identification =====

Product ID:LACQUER ACRYLIC GREEN 14187 ID794430

MSDS Date:10/14/1988

FSC:8010

NIIN:00-935-7071

MSDS Number: BHMYY

=== Responsible Party ===

Company Name:PRATT & LAMBERT, INC.

Box:2153

City:WICHITA

State:KS

ZIP:67201

Country:US

Info Phone Num:316-733-1361

Emergency Phone Num:316-733
-1361

Preparer's Name:W.A. ELLISON

CAGE:FO127

=== Contractor Identification ===

Company Name:PRATT & LAMBERT, INC/BUFFALO, NY 14240

Box:22

CAGE:FO127

Company Name:PRATT AND LAMBERT INC

Address:Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

===== Composition/Information on Ingredients =====

Ingred Name:LEAD CHROMATE (OSHA PEL FOR LEAD FROM 29CFR
1910.1025),(CRO3 CEILING 0.1 MG/M3)

CAS:7758-97-6

RTECS #:GB2975000

OSHA PEL:0.05 MG/M3

(PB)
ACGIH TLV:0.05MG/M3(CR)A2;8990

Ingred Name:CYCLOHEXANONE (SARA III)
CAS:108-94-1
RTECS #:GW1050000
OSHA PEL:S, 50 PPM
ACGIH TLV:S, 25 PPM; 9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)
CAS:78-93-3
RTECS #:EL6475000
OSHA PEL:200 PPM/300 STEL
ACGIH TLV:200 PPM/300STEL 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:ISOPROPYL ALCOHOL (SARA III)
CAS:67-63-0
RTECS #:NT8050000
OSHA PEL:400 PPM/500 STEL
ACGIH TLV:400
PPM/500STEL;9192

Ingred Name:TOLUENE (SARA III)
CAS:108-88-3
RTECS #:XS5250000
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:VOC. ORGANIC CMPD 6.0 LB/GAL LESS WATER & NPRS* 720 G/L
LESS WATER VOC. 19.7 LB/GAL SOLIDS 2364 G/L SOLIDS CALCU
RTECS #:9999999VO

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:YES IARC:YES

OSHA:NO

Health Hazards Acute and Chronic:REPEAT/PROLONGED OVEREXP TO RELATIVELY INSOLUBLE CHROMATES-LUNG CANCER. TOLUENE-LIVER DAM. CHRONIC OVEREXP TO LEAD-SEVERE DAMAGE TO BLOOD FORMING, NERV, URINARY& REPROD SYS. CHAR: LOSS APPETITE, METAL LIC TASTE, ANXIETY, CONSITP, NAUSEA, WEAK, INSOMNIA, HEADACHE, MUSCLE & JOINT PAIN, FINE TREMORS, NUMBNESS, DIZZ, HYPER

Explanation of Carcinogenicity:IN LAB ANIMALS: KIDNEY, LUNG & SPLEEN DAMAGE.

Effects of Overexposure:SWALLOW: GAS TROINTESTINAL IRRI, NAUSEA, VOMIT, ASPIRATION INTO LUNG, CHEM PNEUMONITITS, CAN BE FATAL. INHAL: NOSE/THROAT IRRI. HIGH CONCENT CAUSE ACUTE CENT NERV SYS DEPRESSION CHAR HEADACHE, DIZZ, NA USEA & CONFUSION. EYE: IRRI. SKIN: DEFATTNG AND IRRITATION OF THE SKIN. INHAL OF CAN CAUSE ASPHYXIATION OR ANESTHETIC.

Medical Cond Aggravated by Exposure:PREEXISTING KIDNEY CONDITIONS MAY BE AGGRAVATED BY EXPOSURES TO LEAD. PROLONGED/REPEATED OCCUP OVEREXP TO SOLVENTS WITH PERMANENT BRAIN & NERV SYS DAMAGE. MISUSE MAY BE HARMFUL AND/OR FATAL

=====
===== First Aid Measures =====

First Aid:SWALLOW: DO NOT INDUCE VOMIT. CALL POISON CONTROL CENTER/HOSPITAL EMERG ROOM/PHYSICIAN IMMED. INHAL: REMOVE TO FRESH AIR IMMED. BREATH HAS STOPPED, GIVE CPR. KEEP WARM, QUIET. GET MED ATTN IMMED. EYE: FLUSH W/LARGE AMTS OF WATER, LIFTING LIDS OCCAS, FOR AT LEAST 15 MIN. GET MED ATTN. SKIN: REMOVE CONTAM CLOTHES. WASH AFFECT AREA W/ SOAP & WTR. OBTAIN MED ATTN. IRRI PERSISTS.

=====
===== Fire Fighting Measures =====

Flash Point:24 F/-4.44 C

Extinguishing Media:NFPA CL B FIRE EXTING (CARBON DIOXIDE, ALL PUR DRY CHEM OR ALCOHOL FOAM) FOR EXTING FLAMM LIQ FIRES. POLYMER FOAM PERFER

Fire Fighting Procedures:SELF CONTAIN BREATH APPARATUS. WTR MAY BE INEFFECT, USED TO COOL TO PREVENT PRESSURE BUILD-UP/AUTO-IGNITE/EXPLOSION FROM HEAT. IF WTR USED, FOG NOZZLES PREFERR

Unusual Fire/E

xplosion Hazard:EMERG COND, OVEREXP TO DECOMP MAY CAUSE
HEALTH HAZARD. SYMP MAY NOT BE IMMED APPARENT. OBTAIN MED ATTN.
WARNING! FLAMMABLE

===== Accidental Release Measures =====

Spill Release Procedures:KEEP SPECTATORS AWAY. ELIM ALL IGNITE SOURCES.
DIKE & CONTAIN SPILL W/INERT MATERIAL. TRANSFER LIQ TO COVER METAL
CONTAIN FOR RECOVERY/DISPOSAL. USE NON-SPARK TOOLS. PREVENT CONTAM
OF SEWERS, STREAMS & GROUNDWATER WITH SPILLED MATERIAL OR USED

ABSORB

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABOVE 95 DEG F. STORE
LARGE QUANTITIES IN COMPLIANCE WITH OSHA 29CFR1910.106 DO NOT TAKE
INTERNALLY. CLOSE CONTAINER AFTER EACH USE.

Other Precautions:KEEP AWAY FROM CHILDREN. DO NOT BREATHE SANDING DUST.
WASH HANDS & FACE THOROUGHLY BEFORE EATING/DRINKING. EMPTY CONT
MUST NOT BE WASHED & RE-USED FOR ANY PURPOSE. CONT GROUNDED/BONDED
TO RECEIVING CO NT.
DO NOT WELD/BRAZE/CUT EMPTY CONT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:GEN EXP TO ORGANIC CHEM MAY NOT REQUIRE RESPIR
PROTECT IF WELL VENT AREA. RESTRICTED VENT AREA NIOSH APPROVED CHEM
CARTRIDGE RESPIR MAY BE REQUIRED. SPRAYNG: MECH PREFILTER MAY ALSO
BE REQUIRED. CONF NED: NIOSH APPR AIR SUPPLIED RESPIRATOR

Ventilation:GEN DILUTION & LOCAL EXHAUST VENT SUFFICIENT VOL/PATTERN
KEEP CONCEN HAZARD INGRED BELOW THE LOWEST EXPO
SURE LIMIT

Protective Gloves:PROLONGED USE, SOLVENT IMPERMEABLE GLOVE

Eye Protection:SAFETY GLASSES/CHEM GOGGLES/FACE SHIELDS

Other Protective Equipment:AS REQUIRED TO PREVENT SKIN CONTACT. NOT
LIKELY TO BE NEEDEDSEE OSHA STANDARD FOR LEAD.

Work Hygienic Practices:GOOD PERSONAL HYGIENE PRACTICES

Supplemental Safety and Health

THIS PRODUCT, IF DISCARDED DIRECTLY, WOULD BE CLASSIFIED A HAZARDOUS
WASTE BASEDON ITS IGNITABILITY CHAR. THIS PRODUCT CONTAINS LEAD,
WHICH, IF PRESENT IN WASTE

AT 5.0 MG/1 OR MORE AFTER BEING EXTRACTED, IS CONSIDERED EP TOXIC, AND THEREFORE A HAZARDOUS WASTE UNDER RCRA REGULATIONS. HAZARD WASTE NO. D008

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:175-232 F
Vapor Density:> AIR
Evaporation Rate & Reference:SLOWER THAN ETHER
Percent Volatiles by Volume:69

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
AVOID EXCESSIVE HEAT & SOURCES
OF IGNITION. STRONG ACIDS OR ALKALINE
MATERIALS
Stability Condition to Avoid:NORMALLY STABLE
Hazardous Decomposition Products:BURNING, INCLUDE WHEN HEATED BY
WELD/CUTTING, WILL PRODUCE SMOKE, CARBON MONOXIDE, CARBON DIOXIDE.
OXIDES OF LEAD-GENERATED
Conditions to Avoid Polymerization:KEEP AWAY FROM HEAT SPARKS AND FLAME

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF ACCORD TO FEDERAL, STATE & LOCAL LAWS. INCINERATE ONLY EPA PERMITTED FACILITIES. DO NOT INCINERATE CLOSED CONTAINERS. OBSERVE PRECAUTIONS FOR FLAMMABLE DISPOSAL. CONTAMINANTS ABSORBED DISPOSE IN HAZARDOUS WASTE LANDFILL. IN ACCORD WITH FEDERAL, STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use.
Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.