

NILES CHEMICAL PAINT COMPANY -- N 1207A EARTH YELLOW CAMO TYPE IV -- 8010-01-131-0612

===== Product Identification =====

Product ID:N 1207A EARTH YELLOW CAMO TYPE IV

MSDS Date:10/11/1989

FSC:8010

NIIN:01-131-0612

Kit Part:Y

MSDS Number: BHNDR

=== Responsible Party ===

Company Name:NILES CHEMICAL PAINT COMPANY

Address:225 FORT STREET

Box:307

City:NILES

State:MI

ZIP:49120

Country:US

Info Phone Num:6

16-683-3377 (INFORMATION)

Emergency Phone Num:219-236-5856 (24 HOURS)

Preparer's Name:MIKE LICHATOWICH

CAGE:02388

=== Contractor Identification ===

Company Name:NILES CHEMICAL PAINT

Address:225 FORT STREET

Box:307

City:NILES

State:MI

ZIP:49120

Country:US

Phone:616-683-3377/219-236-5856

CAGE:02388

===== Composition/Information on Ingredients =====

Ingred Name:PM ACETATE

(VAPOR PRESSURE 3.7 MM @ 20C)

CAS:108-65-6

RTECS #:AI8925000

Fraction by Wt: 17%

OSHA PEL:N

E  
ACGIH TLV:NE

Ingred Name:POLYESTER RESIN  
Fraction by Wt: 16%

Ingred Name:N-BUTYL ACETATE (SARA III)  
CAS:123-86-4  
RTECS #:AF7350000  
Fraction by Wt: 9%  
OSHA PEL:150 PPM/200 STEL  
ACGIH TLV:150 PPM/200STEL;9192  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)  
CAS:78-93-3  
RTECS #:EL6475000  
Fraction by Wt: 7%  
OSHA PEL:200 PPM/300 STEL  
ACGIH TLV:200 PPM/300STEL 9192  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:XYLENES (O-,M-,P- ISO  
MERS) (SARA III)  
CAS:1330-20-7  
RTECS #:ZE2100000  
Fraction by Wt: 3%  
OSHA PEL:100 PPM/150 STEL  
ACGIH TLV:100 PPM/150STEL;9192  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:CHROMIUM (III) OXIDE  
CAS:1308-38-9  
RTECS #:GB6475000  
Fraction by Wt: 1%  
OSHA PEL:0.5 MG/M3 (CR)  
ACGIH TLV:0.5 MG/M3 (CR); 8990

Ingred Name:VOC. ORGANIC CMPD 4.33 LB/GAL  
RTECS #:9999999VO

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Repo

rts of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:HISTOLOGIC FIBROSIS OF LUNGS,  
INCOHERENCE, CORNEAL VACUOLIZATION, ANOREXIA. TARGET ORGANS:  
CNS,LUNGS,EYES,SKIN,RESPIRATORY SYSTEM,GI TRACT,BLOOD,LIVER, AND  
KIDNEYS. IF INHAL. CAN CAUSE NASAL/RESPI RATORY IRRITATION, CNS  
DEPRESS,DIZZINESSDROWSINESS,WEAKNESS, FATIGUE, CONFUSION, POSS.  
UNCONSCIOUSNESS,OR ASPHYXIATION  
Effects of Overexposure:EYE: SEVERE IRRITATION, LACRIMATION, REDNESS,  
BLUR  
RED VISION SKIN: REDNESS, IRRITATION,  
DEFATTING OF SKIN LEADING TO DERMATITIS. INHL: NAUSEA,  
HEADACHE, VERTIGOINGST: GA STROINTESTINAL IRRITATION,ABDOMINAL  
PAIN,NAUSEA,VOMITING,DIARRHEA  
Medical Cond Aggravated by Exposure:NONE

===== First Aid Measures =====

First Aid:EYE: IMMED. FLUSH W/LG AMNTS OF WTR FOR 15 MINS. LIFTING  
EYELIDS,GET MED ATTN SKIN: IMMED FLSH W/WTR,IMMED REMOVE CONTAM.  
CLOTHING, GET MEDICAL ATTN IMMED. INHL:  
REMOVE TO FRESH AIR,GIVE  
ARTIFICIA L RESP. IF NEEDED,GET MEDICAL ATTENTIONINGST: DRINK 1-2  
GLS OF WTR. DO NOT INDUCE VOMITING. CONSULT A PHYSICIAN IMMED.

===== Fire Fighting Measures =====

Flash Point Method:TCC  
Flash Point:20F/-6C  
Lower Limits:1.0  
Upper Limits:10  
Extinguishing Media:DRY CHEMICAL, FOAM, CO2  
Fire Fighting Procedures:WEAR SCBA W/FULL FACEPIECE OPERATED W/POSTV  
PRESS MODE & FULL PROTECTIVE CLTHNG.WATER MAY BE USED TO COOL CLSD  
C  
ONTNR TO PREVNT PRESS BUILDUP/IGN. OR EXPLSN  
Unusual Fire/Explosion Hazard:KEEP CONTAINERS TIGHTLY CLOSED. CLSD  
CONTNR MAY EXPLD W/EXPSD TO EXTRM HEAT. VAPORS ARE >AIR & MAY  
TRVL ON GRND TO AN IGN SOURCE. ISOLATE FROM HT,ELEC,FLAME.

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE ALL IGNITION SOURCES. ABSORB W/INERT  
MATL SUCH AS CLAY,SOIL,OR COMMERCIALY AVAIL ABSRBSHOVEL  
RECLAIMED LIQUID & ABSORBENT INTO RECOVERY OR

# SALVAGE DRUMS FOR DISPOSAL.

## ===== Handling and Storage =====

Handling and Storage Precautions: AVOID STORAGE IN HIGH TEMP AREAS OR NEAR FIRE OR OPEN FLAME. KEEP CONTAINERS CLOSED WHEN NOT IN USE. AVOID ROUGH HANDLING. CONTNRS MAYBE HAZARD. W/EMPTY

Other Precautions: DO NOT WELD OR FLAME CUT ON EMPTY DRUMS. CONTACT LENSES SHOULD NOT BE WORN WHEN WORKING WITH THIS MATERIAL. IF MATL PENETRATES THE CLOTHING, IMMEDIATELY REMOVE THE CONTAMINATED

CLOTHING.

## ===== Exposure Controls/Personal Protection =====

Respiratory Protection: WEAR APPROPRIATE PROPERLY FITTED RESPIRATOR DURING & AFTER APPLICATION UNLESS AIR MONITORING DEMONSTRATES VAPOR/MIST LVLS ARE BELOW APPLICABLE LIMITS.

Ventilation: SUFFICIENT VENTL IN VOLUME & PATTERN SHOULD BE PROVIDED TO KKEEP THE AIR CONCENTRATION BELOW CURRENT TLV LIMIT.

Protective Gloves: CHEMICAL RESISTANT GLOVES

Eye Protection: CHEM GOGGLES/SAFETY GLASSES/FACESHIELDS

Other Pro

ective Equipment: CLOTHING AS NEEDED TO PREVENT SKIN CONTACT.

Work Hygienic Practices: WASH HANDS BEFORE EATING, SMOKING, OR USING RESTROOMS. WASH CLOTHING AND SHOES BEFORE REUSE.

Supplemental Safety and Health

EMPLOYEES SHOULD WASH PROMPTLY WHEN SKIN BECOMES CONTAMINATED. REMOVE ANY CLOTH-ING THAT BECOMES WET (TO AVOID FLAMMABILITY HAZARD).

## ===== Physical/Chemical Properties =====

Boiling Pt: B.P. Text: \*\*\*

Vapor Density: > AIR

Viscosity: 70-85 KU

Evaporation Ra

te & Reference: SLOWER THAN ETHER

Solubility in Water: SLIGHT

Appearance and Odor: LIQUID, ODOR OF SOLVENTS

Percent Volatiles by Volume: 57.72

## ===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

STRONG OXIDIZERS, NITRATES, ALKALIES, ACIDS

Stability Condition to Avoid: HIGH TEMPERATURES, SHOCK FROM DROPPING

Hazardous Decomposition Products: CAN PRODUCE CARBON MONOXIDE/DIOXIDE

Conditions to Avoid Polymerization: \*\*\* BOIL PT: 175-302F/79-150

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE W/FEDERAL, STATE, AND  
LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person uti  
lizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.