

PRATT & LAMBERT, INC. -- COATING, POLYURETHANE BLACK 37030 ID754203 -- 8010-01-141-2419
===== Product Identification =====

Product ID:COATING, POLYURETHANE BLACK 37030 ID754203

MSDS Date:11/08/1989

FSC:8010

NIIN:01-141-2419

Kit Part:Y

MSDS Number: BHNFK

=== Responsible Party ===

Company Name:PRATT & LAMBERT, INC.

Address:16116 E 13TH ST

Box:2153

City:WICHITA

State:KS

ZIP:67201

Country:US

Preparer

's Name:W.A. ELLISON

CAGE:FO127

=== Contractor Identification ===

Company Name:PRATT & LAMBERT, INC/BUFFALO, NY 14240

Box:22

CAGE:FO127

Company Name:PRATT AND LAMBERT INC

Address:Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

===== Composition/Information on Ingredients =====

Ingred Name:PROPYLENE GLYCOL METHYL ETHER ACETATE

VAPOR PRESSURE 2 MM HG @ 20 DEG C

CAS:108-65-6

RTECS #:AI8925000

OSHA PEL:NONE ESTABLISHED

ACGIH T

LV:NONE ESTABLISHED

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

OSHA PEL:200 PPM/150 STEL

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS:78-93-3

RTECS #:EL6475000

OSHA PEL:200 PPM/300 STEL

ACGIH TLV:200 PPM/300STEL 9192

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:SILICA, CRYSTALLINE - CRISTOBALITE

CAS:14464-46-1

RTECS #:VV7325000

OSHA PEL:SEE TABLE Z3

ACGIH TLV:0.05 MG/M3 RDUST929

3

Ingred Name:SILICA, AMORPHOUS, DIATOMACEOUS EARTH, CONTAINING LESS THAN
1% CRYSTALLINE SILICA

CAS:61790-53-2

RTECS #:HL8600000

OSHA PEL:20 MPPCF

ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:SILICA, CRYSTALLINE - QUARTZ

CAS:14808-60-7

RTECS #:VV7330000

OSHA PEL:SEE TABLE Z3

ACGIH TLV:0.1 MG/M3 RDUST;9293

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Health Hazards Acute and Chronic:SWALLOWING-GASTROINTESTINAL

IRRITATION, ASPIRATION OF MATERIAL INTO LUNG MAY CAUSE CHEMICAL PNEUMONITIS. EYE AND SKIN-IRRITATION. HIGH CONCENTRATIONS MAY CAUSE ACUTE CENTRAL NERVOUS SYSTEM DEPRESSION CHARACTERIZED BY HEADACHED, DIZZINESS,NAUSEA AND CONFUSTION.

Explanation of Carcinogenicity:NONE LISTED

Effects of Overexposure:REPEATED EXPOSURE TO CRYSTALLINE SILICA MAY CAUSE LUNG DISEASE. (PNEUMOCONIOSIS)OVEREXPOSURE TO TOLUENE MAY CAUSE LIVER DAMAGE. OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRA

IN/NERVOUS SYSTEM DAMAGE.

Medical Cond Aggravated by Exposure:PREEXISTING RESPIRATORY CONDITIONS MAY BE AGGRAVATED BY EXPOSURE TO CRYSTALLINE SILICA.

=====
===== First Aid Measures =====

First Aid:SWALLOWING-DO NOT INDUCE VOMITING. GET MED ATTN.
INHALATION-REMOVE TO FRESH AIR AND GET MED ATTN. EYE-FLUSH WITH WATER FOR 15 MIN. GET MED ATTN. SKIN REMOVE CONTAMINATED CLOTHING, WASH AFFECTED AREA I F IRRITATION PERSISTS GET MED ATTN: NOTETO PHYSIC

IAN-ANY TREATMENT THAT MIGHT BE REQUIRED FOR OVEREXPOSURE SHOULD BE DIRECTED AT THE CONTROL OF SYMPTOMS AND THE CLINICAL CONDITIONS.

=====
===== Fire Fighting Measures =====

Flash Point:24F/-4.44C

Extinguishing Media:USE CLASS B FIRE EXTINGUISHERS. POLYMER FOAM IS PREFERRED FOR LARGE FIRES.

Fire Fighting Procedures:WEAR SELF CONTAINED BREATHING APPARATUS. USE WATER TO COOL EXPOSED CONTAINERS TOPREVENT POSSIBLE AUTO IGNITION/EXPLOSION. USE FOG NOZ ZLES IF WATER IS USED.

Unusual Fire/Explosion Hazard:OVEREXPOSURE TO DECOMPOSTION MAY CAUSE HEALTH HAZARD. SYMPTOMS MAY NOT BE IMMEDIATELY APPARENT. OBTAIN MEDICAL ATTENTION. WARNING FLAMMABLE

=====
===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE ALL IGNITION SOURCES.EVACUATE PERSONNEL.DIKE & CONTAIN SPILL W/INERT MATERIAL SAND,EARTH. USE ONLY NON-SPARKING TOOLS.PLACE ABSORBENT DIKINGMATERIALS IN COVERED METAL CNT FOR DISPOSA

L.PREVENT CONTAMINATION OF SEWERS, STREAMS &
GROUNDWATERS.

=====
Handling and Storage
=====

Handling and Storage Precautions: DO NOT STORE ABOVE 95°F. STORE LARGE
QUANTITIES IN COMPLIANCE WITH OSHA 29CFR 1910.106.

Other Precautions: DO NOT TAKE INTERNALLY. CLOSE CONTAINER AFTER EACH USE. DO
NOT BREATHE SANDING DUST. EMPTY CONTAINERS MUST NOT BE WASHED & RE-USED
FOR ANY PURPOSE. CONTAINERS SHOULD BE GROUNDED & BONDED TO THE RECEIVING
CONTAINER. DO NOT WELD, CUT, OR BRAZE ON EMPTY CONTAINER.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection: RESPIRATORS RECOMMENDED WITH THIS PRODUCT DURING
AND AFTER THE ADDITION OF CATALYST: PROPERLY FITTED POSITIVE
PRESSURE (TC 19C NIOSH/MSHA) WHILE EXPOSED. IF NOT AVAILABLE USE
VAPOR PARTICULATE, THAT IS EFFECTIVE FOR ISOCYANATE VAPORS AND

Ventilation: GENERAL DILUTION AND LOCAL EXHAUST VENT IN SUFFICIENT
VOLUME & PATTERN TO MAINTAIN CONCENTRATIONS OF HAZARDOUS SUBSTANCES

Protective Gloves: SOLVENT
IMPERMEABLE GLOVES ARE REQUIRED

Eye Protection: WEAR SAFETY SPECTACLES.

Other Protective Equipment: NOT LIKELY TO BE NEEDED.

Work Hygienic Practices: NONE LISTED

Supplemental Safety and Health

RESPIRATORY PROTECTION: MISTS. WEAR RESPIRATOR FOR THE WHOLE TIME WHILE
MIX SPRAYING AND UNTIL VAPORS AND MISTS ARE GONE. THIS URETHANE
BASE IS ONE PART OF A TWO COMPONENT MIXTURE. INTENDED TO BE MIXED
WITH AN ACTIVATOR. THE CONTENTS OF THIS PACKAGE MUST BE BLENDED WITH
OTHER COMPONENTS BEFORE THE
PRODUCT CAN BE USED.

=====
Physical/Chemical Properties
=====

HCC: F2

Boiling Pt: B.P. Text: 175°F / 281°F

Vapor Density: >AIR

Evaporation Rate & Reference: SLOWER THAN ETHER

Percent Volatiles by Volume: 75

=====
Stability and Reactivity Data
=====

Stability Indicator/Materials to Avoid: YES
STRONG ACIDS OR ALKALINE MATERIALS

Stability Condition to Avoid: AVOID EXCESSIVE HEAT AND SOURCES OF
IGNITION.

Hazardous Decomposition Products: BURN

ING/WELDING/CUTTING WILL PRODUCE

SMOKE, CARBON MONOXIDE AND CARBON DIOXIDE.

Conditions to Avoid Polymerization:KEEP AWAY FROM HEAT SPARKS AND
FLAME.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORDANCE W/FEDERAL,STATE & LOCAL
LAWSINCINERATE ONLY IN EPA PERMITTED FACILITY.DO NOT INCINERATE
CLOSED CONTAINERS.OBSERVE PRECAUTIONS FOR DISPOSAL OF FLAMMABLE
MATERIALS.CONTAM ABSORBEN T MAY BE DISPOSED OF IN HAZARDOUS

WASTELANDFILL.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their

particular situation.