View NSN Online: https://aerobasegroup.de/nsn/7510-01-126-2497

Product ID:RED FILMOPQUER INK MSDS Date:01/01/1990 FSC:7510 NIIN:01-126-2497 MSDS Number: BHPMT === Responsible Party === Company Name:MARK-TEX CORPORATION Address:161 COOLIDGE AVE City:ENGLEWOOD State:NJ ZIP:07631-4523 Country:US Info Phone Num:201-567-4111 Emergency Phone Num:800-222-0876 CAGE:04457

=== Contractor Identification === Company Name:MARK-TEX CORPORATION Address:161 COOLIDGE AVENUE Box:City:ENGLEWOOD State:NJ ZIP:07631 Country:US Phone:800-222-0876/201-567-4111 CAGE:04457

Ingred Name:PROPYLENE GLYCOL MONOMETHYL ETHER CAS:107-98-2 RTECS #:UB7700000 Fraction by Wt: 45.0% OSHA PEL:100 PPM/150 STEL ACGIH TLV:100 PPM/150STEL;9192

Ingred Name:DIACETONE ALCOHOL (4-HYDROXY-4-METHYL-2-PENTANONE) CAS:123-42-2 RTECS # :SA9100000 Fraction by Wt: 30.0% OSHA PEL:50 PPM ACGIH TLV:50 PPM; 9192

Ingred Name:RED PIGMENT CAS:1103-38-4 Fraction by Wt: 10.0% Other REC Limits:15MG/M3 FOR DUST

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:ACUTE:IRRITATION OF EYES,SKIN,RESPIRATORY OR G.I.TRACTS;CNS EFFECTS LIKE HEADACHE,DIZZINESS,NAUSEA,VOMITING AND POSSIBLE UNCONSCIOUSNESS;REDNESS OR BURNS OF EYES/SKIN POSSIBLE.CHRONIC:DRYING OF SKIN,D EFATTING OR DERMATITIS. Explanation of Carcinogenicity:DATA PER MSDS Effects of Overexposure:SEE HEALTH HAZARDS DATA. Medical Cond Aggravated by Exposure:PERSONS WITH A HISTORY OF AILMENTS OR WITH A PRE-EXISTING DISEASE INVOLVING THE EYES, SKIN, OR RESPIRATORY TRACT MAY BE AT INCREASED RISK FROM EXPOSURE.

First Aid:INHALA

TION:REMOVE TO FRESH AIR. RESUSCITATE IF NOT BREATHING. GET MEDICAL ATTENTION. EYES:IMMEDIATELY FLUSH WITH PLENTY OF WATER FOR 15 MINUTES HOLDING EYELIDS OPEN. GET MEDICAL ATTENTION. SKIN:REMOVE CONTAMINATED CLOTHING. WASH WITH SOAP AND WATER. IF IRRITATION PERSISTS, GET MEDICAL ADVICE. INGESTION:DO NOT INDUCE VOMITING. GIVE NOTHING BY MOUTH IF UNCONSCIOUS. GET IMMEDIATE MEDICAL ATTENTION.

Flash Poin

t Method:TCC Flash Point:=31.7C, 89.F Extinguishing Media: USE CARBON DIOXIDE, FOAM, DRY CHEMICAL, OR WATER FOG. Fire Fighting Procedures: FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA & FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE. Unusual Fire/Explosion Hazard:NONE EXPECTED Spill Release Procedures: USE PROPER PERSONAL PROTECTION: REMOVE ALL IGNIT ION SOURCES; CONTAIN FREE MATERIAL IF POSSIBLE; USE SUITABLE INERT ABSORBENT MATERIAL AND RECOVER FOR PROPER DISPOSAL IN AN APPROVED CONTAINER. Neutralizing Agent:NOT APPLICABLE. Handling and Storage Precautions: STORE IN A COOL, DRY, WELL VENTILATED AREA. KEEP CONTAINERS TIGHTLY CLOSED WHEN NOT IN USE. PROTECT CONTAINERS FROM PHYSICAL DAMAGE.KEEP AWAY FROM HEA Other Precautions: DO NOT TAKE INTERNALLY. DO NOT BREA THE MIST. AVOID PROLONGED OR REPEATED BREATHING OF VAPOR. AVOID CONTACT WITH EYES. USE WITH ADEQUATE VENTILATION. WASH THOROUGHLY AFTER HANDLING. Respiratory Protection: USE NIOSH/MSHA APPROVED RESPIRATOR FOR ORGANIC VAPORS/MIST AS REQUIRED IF ABOVE PEL/TLV. Ventilation:LOCAL/GENERAL TO MAINTAIN PEL/TLV. Protective Gloves: NEOPRENE, NITRILE, OR NATURAL RUBBER Eye Protection: SAFETY GOGGLES WITH OPTIONAL FACE SHIELD Ot her Protective Equipment: EYE WASH STATION AND SAFETY SHOWER, WORK CLOTHING AND APRON AS REQUIRED. Work Hygienic Practices: OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. DO NOT WEAR CONTAMINATED CLOTHING OR FOOTWEAR. Supplemental Safety and Health AVOID PROLONGED OR REPEATED EXPOSURE. DO NOT GET ON SKIN OR IN EYES. DO NOT BREATHE VAPORS OR MISTS. HCC:F3 Boiling Pt:=116.1C, 241.F Vapor Pres:1

0 Vapor Density:3-4 Spec Gravity:1.0 Evaporation Rate & Reference: