View NSN Online: https://aerobasegroup.de/nsn/3439-01-213-0203

FEDERATED-FRY METALS INC DIV OF COOKSON AMERICA -- FLOWCREAM SOLDER PASTES -- 3439-01-213-0203

============= Product Identification ========================

Product ID:FLOWCREAM SOLDER PASTES

MSDS Date:06/16/1989

FSC:3439

NIIN:01-213-0203

MSDS Number: BHPNB === Responsible Party ===

Company Name: FEDERATED-FRY METALS INC DIV OF COOKSON AMERICA

Address:6TH AVE AND 41ST ST

City:ALTOONA

State:PA ZIP:16602 Country:US Info Phone

Num:814-946-1611

Emergency Phone Num:814-946-1611

CAGE:65172

=== Contractor Identification ===

Company Name: FRY TECHNOLOGY DIV OF COOKSON AMERICA INC

Address:6TH AVE AND 41ST ST

Box:City:ALTOONA

State:PA ZIP:16602 Country:US

Phone:814-946-1611

CAGE:65172

======= Composition/Information on Ingredients ========

Ingred Name:TIN CAS:7440-31-5

RTECS #:XP7320000 Fraction by Wt: 0-92% OSHA PEL:2 MG/M3

ACGIH TLV:2 MG/M3; 9192

Ingred Name:LEAD (SARA III)

CAS:7439-92-1

RTECS #:OF7525000

F

raction by Wt: 0-90%

OSHA PEL:0.05 MG/M3;1910.1025 ACGIH TLV:0.15 MG/M3;DUST 9192

EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

Ingred Name: SILVER (SARA III)

CAS:7440-22-4

RTECS #:VW3500000 Fraction by Wt: 0-5% OSHA PEL:0.01 MG/M3 ACGIH TLV:0.1 MG/M3; 9192

EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

Ingred Name: ROSIN ACID

CAS:8050-09-7 Fraction by Wt: 4-8%

Ingred Name:OTHER COMPONENTS (TYPE NOT SPECIFIED)

Ingred Name:BISMUTH

CAS:7440-69-9

RTECS #:EB2600000 Fraction by Wt: 0-50%

Ingred Name: DIETHYLENE GLYCOL MON

**OBUTYL ETHER ACETATE** 

CAS:124-17-4

RTECS #:KJ9275000 Fraction by Wt: 4-8%

========== Hazards Identification ================

Routes of Entry: Inhalation:YES Skin:UNKNOWN Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE:IRRITATION OF EYES,SKIN AND
RESPIRATORY TRACT;LEAD MAY CAUSE CNS EFFECTS AND KIDNEY
DAMAGE,STOMACH PAIN OR CRAMPS AND NAUSEA POSSIBLE.

Explanation of Carcinogenicity: DATA PER MSDS

Effects of Over

exposure:EXPOSURE TO WELDING FUMES MAY RESULT IN
DISCOMFORT SUCH AS DIZZINESS, NAUSEA, FEVER, DRYNESS AND/OR
IRRITATION OF NOSE, THROAT AND EYES. SKIN SENSITIVITY MAY ALSO BE
NOTED. WATERY EYES, HEADACHE, BREA THING DIFFICULTY, FREQUENT
COUGHING AND/OR CHEST PAINS MAY OCCURE FROM ACUTE EXPOSURE. TOXIC
GASES CAN BE FATAL.

Medical Cond Aggravated by Exposure:SOME WORKERS MAY BE AFFECTED BY A PRE-EXISTING CONDITION OR OTHER OCCUPATIONAL ILLNESS BECAUSE OF THE WIDE VARIAT

ION IN INDIVIDUAL SUSCEPTIBILITIES.

-·	
 Firet /\id \\/\actir\c	
 I II SI AIU IVIEASULES	

First Aid:IN CASE OF ELECTRICAL SHOCK, TURN OFF POWER PRIOR TO REMOVAL FROM EXPOSURE AREA AND ADMINISTRATION OF FIRST AID. REMOVE FROM EXPOSURE AREA AND CALL FOR MEDICAL AID. ADMINISTER OXYGEN IF BREATHING IS D IFFICULT. IF NOT BREATHING, BEGIN ARTIFICIAL RESPIRATION. IF NO DETECTABLE PULSE, BEGIN EXTERNAL HEART MASSAGE. EMPLOY FIRST AID TECHNIQUES RECOMMENDED BY THE AME RICAN RED CROSS.

	Fire Fighting Measures	
--	------------------------	--

Flash Point Method:COC

Flash Point:240F,116C

Extinguishing Media:USE CARBON DIOXIDE, FOAM, DRY CHEMICAL, OR WATER FOG.

Fire Fighting Procedures:FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA & FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE.

Unusual Fire/Explosion Hazard:NONE EXPECTED ;FIRE OR EXCESSIVE HEAT MAY CAUSE PRODUCTION OF

HAZARDOUS DECOMPOSITION PRODUCTS.

Accidental Release Measures	_
 ACCIDENTAL RELEASED MESSELIFE	·
 Accidental Nelease Measure	S

Spill Release Procedures:CLEAN UP ANY GRINDING DUST OR WASTE RESIDUES AND PLACE IN SUITABLE DOT APPROVED CONTAINERS AND DISPOSE OF IN FULL COMPLIANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS. AVOID INHALATION AND SKIN EXPOSU RE.

I landalina a and Otamaa	e ============
 Handling and Storag	
 TIANUNING ANG SIGIAG	C

Handling and Storage Precautions:STORE IN COOL AND DRY AREA.KEEP AWAY FROM HEAT

OPEN FLAMES, SPARKS DIRECT SUNLIGHT.

Other Precautions:PROVIDE PROTECTIVE SCREENS TO SHIELD OTHERS. WHEN ELECTRODES AND FLUXES ARE CONSUMED, THE FUME AND GAS DECOMPOSITION PRODUCTS GENERATED ARE DIFFERENT IN FORM FROM THE INGREDIENTS LISTED. NEW COMPOUNDS NOT IN THE ELECTRODES MAY FORM.

====== Exposure Controls/Personal Protection ========

Respiratory Protection: USE WELD FUME RESPIRATOR OR AIR SUPPLIED RESPIRATOR WHEN CUTTING, GRINDING OR WELDING IN A CONFINED SP ACE OR

WHERE LOCAL EXHAUST OR GENERAL VENTILATION DOES NOT KEEP EXPOSURE BELOW RECOMMENDED LIMITS. USE ONLY NIOSH APPROVED RESPIRATORS.

Ventilation:USE ENOUGH VENTILATION WHEN CUTTING, GRINDING OR WELDING TO KEEP THE DUST, FUMES & GASES FROM THE WORKERS BREATHING ZONE

Protective Gloves: PVC OR RUBBER

Eye Protection: GOGGLES/FACE SHIELD W/LENS

Other Protective Equipment:FLAME RETARDANT CLOTHING WHEN CUTTING, GRINDING OR WELDING. DO NOT EXPOSE SKIN TO RADIATION WHEN HOT CUTTING

OR WELDING.

Work Hygienic Practices:WASH THOROUGHLY BEFORE EATING OR SMOKING. LAUNDER CONTAMINATIED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

WELDING AND HOT CUTTING FUMES & GASES CANNOT BE CLASSIFIED SIMPLY. THEIR COMPOSITION AND QUANTITY ARE DEPENDENT ON THE METAL BEING WELDED, THE PROCEDURES, PROCESSES AND THE TYPE OF WIRE OR ELECTRODES USED. OTHER INFLUENCING FACTORS ARE THEPRESENCE OF CONTAMINENTS. CHLORINATED SOLVENTS MAY DECOMPOSE TO TOXIC GASES.


====== Physical/Chemical Properties =========

HCC:N1

Boiling Pt:B.P. Text:>450F,>232C

Vapor Pres:0.01 Vapor Density:7

Solubility in Water:SLIGHT

Appearance and Odor: GREY PASTES

Percent Volatiles by Volume:4-8

======== Stability and Reactivity Data ==========

Stability Indicator/Materials to Avoid:YES

OXIDIZING AGENTS, REDUCING AGENTS, STRONG ACIDS.

Stability Condition to Avoid:HIGH TEMPERATURES

Hazardous Decomposition Products:MIXED ORGANICS,LEAD FUMES,ETC.

====

======= Disposal Considerations ============

Waste Disposal Methods:DISPOSE I/A/W FEDERAL, STATE & LOCAL REGULATIONS OR RETURN TO THE MFG FOR REPROCESSING OF METAL.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.