

MAGNAFLUX CORPORATION -- ZL-27A ZYGLO PENETRANT -- 6850-01-117-2971

=====
Product Identification
=====

Product ID:ZL-27A ZYGLO PENETRANT

MSDS Date:01/01/1991

FSC:6850

NIIN:01-117-2971

MSDS Number: BHQCX

=== Responsible Party ===

Company Name:MAGNAFLUX CORPORATION

Address:7300 W. LAWRENCE AVENUE

City:CHICAGO

State:IL

ZIP:60656-3504

Country:US

Info Phone Num:708-867-8000

Emergency Phone Num:708-867-

8000, CHEMTREC 800-424-9300

CAGE:37676

=== Contractor Identification ===

Company Name:ILLINOIS TOOL WORKS INC MAGNAFLUX DIV

Address:3624 WEST LAKE AVENUE

Box:City:GLENVIEW

State:IL

ZIP:60025

Country:US

Phone:847-657-5300/

CAGE:37676

=====
Composition/Information on Ingredients
=====

Ingred Name:WHITE MINERAL OIL (SLAB OIL)

CAS:8042-47-5

RTECS #:PY8047000

Fraction by Wt: 30.0%

Other REC Limits:NONE SPECIFIED BY M.

OSHA PEL:5 MG/M3 OIL MIST

ACGIH TLV:5MG/CUM OIL MIST

Ingred Na

me:KEROSENE
CAS:8008-20-6
RTECS #:OA5500000
Fraction by Wt: 10.0%
Other REC Limits:5 MG/M3 OIL MIST
ACGIH TLV:100MG/CUM

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:MAY IRRITATE EYES AND SKIN.
INHALATION:IRRITATION, DIZZINESS.
Effects of Overexposure:INHALATION:DIZZINESS, NAUSEA. EYES:MILD
IRRITATION, TEARING. SKIN:IRRITATI
ON, DRYING. INGESTION:GASTRIC
UPSET, VOMITING,DIARRHEA.
Medical Cond Aggravated by Exposure:NOT STATED BY MANUFACTURER.

===== First Aid Measures =====

First Aid:INHALATION:REMOVE TO FRESH AIR. IF BREATHING IS DIFFICULT,
GIVE OXYGEN; SKIN:REMOVE CONTAMINATED CLOTHES. WASH OFF WITH
FLOWING WATER. USE SOOTHING LOTION. IF IRRITATION PERSISTS, GET
MEDICAL ATTN. EY ES:IMMEDIATELY RINSE/FLUSH WITH COPIOUSAMOUNT OF
RUNNING WATER, AND GET MEDICA
L ATTENTION. INGESTION:GET MEDICAL
HELP.

===== Fire Fighting Measures =====

Flash Point Method:PMCC
Flash Point:200F/ 93C
Extinguishing Media:CARBON DIOXIDE,FOAM.
Fire Fighting Procedures:KEEP CONTAINERS COOL WITH WATER SPRAY.DO NOT
SPRAY ON BURNING PRODUCT.
Unusual Fire/Explosion Hazard:WHEN INVOLVED IN COMBUSTION, MAY EMIT
TOXIC GASES AT OR ABOVE DECOMPOSITION TEMPERATURE. CANS MAY BURST
IN FIRE.

===== Accidental Release Measur

es =====

Spill Release Procedures:REMOVE IGNITION SOURCES.SMALL SPILL:WIPE UP OR MOP UP BUT DO NOT BREATHE VAPORS.PLACE RAGS IN CLOSED DRUMS; LARGE SPILL:WEAR PERSONAL SAFETY EQUIPMENTS.DIKE AREA FAR AHEAD.ABSORB LIQUID WITH COMMERCIAL ABSORBENT.TRANSFER WASTE MATL IN SALVAGE TANKS.

===== Handling and Storage =====

Handling and Storage Precautions:STORE AWAY FROM HEAT SOURCES IN WELL VENTILATED AREA.AVOID AGAINST PHYSICAL DAMAGE TO CONTAINERS.KEEP CONTAINERS TIGHTLY CLOSED.

Other Precautions:DO NOT BREATHE VAPORS.DO NOT SMOKE WHILE USING.DO NOT HEAT ABOVE 130F(54C).AVOID FREQUENT OR PROLONGED SKIN CONTACT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:WEAR A RESPIRATOR WITH CHEMICAL CARTRIDGE. IN CONFINED AREAS,WEAR A FULL MASK WITH SEPARATE AIR SUPPLY.

Ventilation:GENERAL VENTILATION TO KEEP BELOW 350PPM LIMIT.

Protective Gloves:NITRILE RUBBER GLOVES.

Eye

Protection:FULL GOGGLES.WHEN SPRAYING OR POURING.

Other Protective Equipment:EITHER USE IN A SPRAY BOOTH OR NEXT TO AN EXHAUST VENT.

Work Hygienic Practices:AVOID SKIN CONTACT.WASH THOROUGHLY AFTER HANDLING OR USE.LAUNDER CONTAMINATED CLOTTES.

Supplemental Safety and Health

THIS REPRESENTS NEW FORMULATION OF ZL-27A; OLD FORMULATION DATA UNDER PNI "B",THIS NSN; THE ZL-27A PENETRANT IS A QUALIFIED PRODUCT OF QPL-25135-15 FOR TYPE I,METH B,LVL 3 FOR THE NSN; PER QPL-25135-15,

ZL-22D PENETRANT IS ALSO FOR TYPE I,METH B,LEVEL 3 FOR THE SAME NSN OF THE SPEC.

===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:410F/210C

Vapor Pres:0.5 @100F

Vapor Density:1.0

Spec Gravity:0.95

pH:NEUTRL

Solubility in Water:NEGLIGIBLE

Appearance and Odor:GREEN OILY LIQUID.

Percent Volatiles by Volume:5.0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

OXIDIZERS.

Stability Co

Condition to Avoid: HEAT, HIGH TEMPERATURES.

Hazardous Decomposition Products: OXIDES OF CARBON AND NITROGEN ON COMBUSTION.

===== Disposal Considerations =====

Waste Disposal Methods: INCINERATE OR DISPOSE OF AS EPA HAZARDOUS WASTE D001 (IGNITABLE WASTE), IN ACCORDANCE WITH ALL APPLICABLE FEDERAL, STATE, LOCAL REGULATIONS; IF LOCAL AUTHORITIES PROHIBIT DUMPING RINSINGS DOWN THE SEWER, PURIFY RINSINGS W/MAGNAFLUX WASTEWATER TREATMENT SYSTEM

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.