

BULK CHEMICALS DISTRIBUTORS, INC. -- CORROSION PREVENTIVE COMPOUND --
8030-00-262-7358

=====
Product Identification
=====

Product ID:CORROSION PREVENTIVE COMPOUND

MSDS Date:06/01/1987

FSC:8030

NIIN:00-262-7358

MSDS Number: BHQHY

=== Responsible Party ===

Company Name:BULK CHEMICALS DISTRIBUTORS, INC.

Address:80 FIRST STREET

City:GRETNA

State:LA

ZIP:70053

Country:US

Info Phone Num:(504) 362-3232 O

R 1-800-535-4095

Emergency Phone Num:(504) 362-3232

CAGE:56921

=== Contractor Identification ===

Company Name:BULK CHEMICALS DISTRIBUTORS,INC

Address:80 FIRST STREET

City:GRETNA,

State:LA

ZIP:70053

Country:US

Phone:504-362-3232 DISCONNECTED(2-20-92)

CAGE:56921

=====
Composition/Information on Ingredients
=====

Ingred Name:INHIBITOR BLEND INCLUDING THE BARIUM SOAP OF AN OXYGENATED
HYDROCARBON

Fraction by Wt: 50%

Ingred Name:SOLVENT 140-HI FLASH ALIPHATIC HYDROCARBON BLEN

D

Fraction by Wt: 50%

ACGIH TLV:25

=====
Hazards Identification
=====

Health Hazards Acute and Chronic:VAPORS MIGHT EFFECT CENTRAL NERVOUS
SYSTEM AND CAUSE RESPIRATORY IRRITATION.

Effects of Overexposure:VAPORS MIGHT EFFECT CENTRAL NERVOUS SYSTEM AND
CAUSE RESPIRATORY IRRITATION.

Medical Cond Aggravated by Exposure:CENTRAL NERVOUS SYSTEM AND
RESPIRATORY IRRITATION.

=====
First Aid Measures
=====

First Aid:SKI

N CONTACT: WASH WITH SOAP AND WATER. AN EMOLLIENT CREAM OR LOTION IS BENEFICIAL. EYE CONTACT: WASH WITH PLENTY OF WATER FOR 5 MINUTES. INHALATION PROVIDE FRESH AIR AND REST. AND INGESTION: DO NOT INDUCE VOMITING. CALL A PHYSICIAN.

=====
===== Fire Fighting Measures =====

Flash Point Method: COC

Flash Point: 163 F/ 73 C

Lower Limits: NA

Upper Limits: NA

Extinguishing Media: (1) MECHANICAL FOAM, (2) DRY CHEMICAL, (3) WATER FOG AND (4) CO2.

Fire Fighting

Procedures: STRAIGHT WATER STREAM WOULD SPREAD OIL FIRES.

Unusual Fire/Explosion Hazard: VAPOR ACCUMULATION WOULD FLASH AND/OR EXPLODE IF IGNITED.

=====
===== Accidental Release Measures =====

Spill Release Procedures: AVOID OPEN FLAME. PROVIDE ADEQUATE VENTILATION. COLLECT AND DISPOSE OF ALL SPILLED LIQUID.

Neutralizing Agent: NONE KNOWN.

=====
===== Handling and Storage =====

Handling and Storage Precautions: HANDLE AS COMBUSTIBLE LIQUID.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection: IN INADEQUATELY VENTILATED SPACE, USE SELF-CONTAINED BREATHING APPARATUS.

Ventilation: LOCAL EXHAUST, TO A FIRE SAFE AREA.

Protective Gloves: RECOMMENDED.

Eye Protection: RECOMMENDED.

Other Protective Equipment: AS REQUIRED TO AVOID WETTING CLOTHES.

Work Hygienic Practices: ALWAYS READ LABELS CAREFULLY BEFORE USING.

Supplemental Safety and Health

NK

=====
===== Physical/Chemical Properties =====

es =====

HCC:V4

Boiling Pt:B.P. Text:390 F

Melt/Freeze Pt:M.P/F.P Text:NC

Vapor Pres: .5/2.3

Vapor Density:6.2

Spec Gravity:857-859 (H2O=1)

Evaporation Rate & Reference: .05 (BUTYL ACETATE=1)

Solubility in Water:NEGLIGIBLE

Appearance and Odor:DARK AMBER WITH ORGANIC ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

NK

===== Disposal Considerations =====

Waste Disposal Methods:T

HIS IS A COMBUSTIBLE HYDROCARBON AND WILL BURN

IF IGNITED. USE THE SAME PRECAUTIONS FOR DISPOSAL AS YOU WOULD
KEROSENE OR DIESEL OIL.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should

seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.