

INDUSTRIAL FLOOR FINISHES -- METAL POLISH -- 7930-00-266-7136

=====
Product Identification
=====

Product ID:METAL POLISH
MSDS Date:05/01/1987
FSC:7930
NIIN:00-266-7136
MSDS Number: BHQJD
=== Responsible Party ===
Company Name:INDUSTRIAL FLOOR FINISHES
Address:605 SPRINGS RD
City:BEDFORD
State:MA
ZIP:01730
Country:US
Info Phone Num:1-617-667-5161
Emergency Phone Num:1-800-424-9300
Preparer's Name:T
. PITROFFY
CAGE:INDUS
=== Contractor Identification ===
Company Name:INDUSTRIAL FLOOR FINISHES
Address:605 SPRINGS RD
City:BEDFORD
State:MA
ZIP:01730
Country:US
Phone:1-617-667-5161
CAGE:INDUS

=====
Composition/Information on Ingredients
=====

Ingred Name:STODDARD SOLVENT
CAS:8052-41-3
RTECS #:WJ8925000
Fraction by Wt: 17%
OSHA PEL:500 PPM
ACGIH TLV:100 PPM; 9293

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:YES

Ingestion: YES

Health Hazards Acute and Chronic: PRIMARY EYE/SKIN IRRITANT WITH CONTACT. INHALATION MAY CAUSE HEADACHE, DIZZINESS AND NAUSEA. CHRONIC: NOT SUFFICIENT DATA, EXERCISE CARE, DO NOT USE ABOVE TLV. Effects of Overexposure: PRIMARY EYE/SKIN IRRITANT WITH CONTACT. INHALATION MAY CAUSE HEADACHE, DIZZINESS AND NAUSEA.

=====
First Aid Measures
=====

First Aid: EYE: FLUSH WITH WATER; SKIN: WASH WITH SOAP AND WATER, APPLY SKIN CREAM. INHAL: REMOVE TO FRESH AIR, RESTORE BREATHING IF NECESSARY CALL A PHYSICIAN. INGEST: DRINK WATER OR MILK, DO NOT INDUCE VOMITING.

=====
Fire Fighting Measures
=====

Flash Point Method: TCC
Flash Point: 104F/40C
Lower Limits: 0.8
Upper Limits: 6
Extinguishing Media: FOAM, CO2, DRY CHEMICAL
Fire Fighting Procedures: WATER MAY BE USED TO COOL CONTAINERS TO PREVENT PRESSURE BUILD-UP OR AUTO-IGNITION.
Unusual Fire/Explosion Hazard: ISOLATE FROM HEAT, CLOSED CONTAINERS MAY EXPLODE IF EXPOSED TO EXTREME HEAT.

=====
Accidental Release Measures
=====

Spill Release Procedures: REMOVE SOURCES OF IGNITION, SPRINKLE W/ABSORBENT. FOG WITH WATER FLUSH OR SCRAPE INTO RETAINING AREA OR CONTAINER. INCREASE VENTILATION AVOID BREATHING VAPORS.

=====
Handling and Storage
=====

Handling and Storage Precautions: KEEP AWAY FROM HEAT, SPARKS, AND OPEN FLAME. USE ADEQUATE VENTILATION. AVOID PROLONGED/REPEATED CONTACT. KEEP CONTAINER CLOSED.
Other Precautions: KEEP AWAY FROM CHILDREN. AVOID STATIC BUILD UP. EMPTY CONTAINERS MAY RETAIN FUME

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection: SELF CONTAINED BREATHING APPARATUS FOR CONCENTRATIONS ABOVE TLV
Ventilation: LOCAL EXHAUST
Protective Gloves: RUBBER GLOVES
Eye Protection: SAFETY GLASSES
Other Protective Equipment: EYE BATH, SAFETY SHOWER, PROTECTIVE CREAM
Supplemental Safe

ty and Health
NK

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:215F
Vapor Pres:2
Vapor Density:3.8
Spec Gravity:1.1
Evaporation Rate & Reference:0.8
Solubility in Water:PARTIAL
Appearance and Odor:PINK CREAMY LIQUID, AMMONIA ODOR
Percent Volatiles by Volume:74

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZERS
Stability Condition to Avoid:HEAT, SPARKS, OPEN FLAME, AND
FIRE
Hazardous Decomposition Products:THERMAL DECOMP PRODUCES FUMES MAY
YIELD CARBON MONOXIDE

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATE OR DISPOSE OF IN ACCORDANCE
W/FEDERAL, STATE, AND LOCAL REGULATIONS. EMPTY CONTAINERS MAY RETAIN
FUMES. DO NOT EXPOSE TO HEAT OR FLAME.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense.

The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.