View NSN Online: https://aerobasegroup.com/nsn/7930-00-489-5606

INDUSTRIAL FLOOR FINISHES -- PERMANIZE CREAM WAX -- 7930-00-489-5606

Product ID:PERMANIZE CREAM WAX MSDS Date:04/01/1985 FSC:7930 NIIN:00-489-5606 **MSDS Number: BHQKJ** === Responsible Party === Company Name: INDUSTRIAL FLOOR FINISHES Address:605 SPRING STREET City:BEDFORD State:MA ZIP:01730 Country:US Info Phone Num:617-667-5161 Emergency Phone Num:617-667-5161 Pre parer's Name: T. PITROLFFY CAGE:INDUS === Contractor Identification === Company Name: INDUSTRIAL FLOOR FINISHES Address:605 SPRINGS RD City:BEDFORD State:MA ZIP:01730 Country:US Phone:1-617-667-5161 CAGE:INDUS Company Name: PEMATEX INDUSTRIAL CORPORATION Address:30 TOWER LANE, AVON PARK SOUTH Box:City:AVON State:CT ZIP:06001 CAGE:PERMA

Ingred Name:STODDARD SOLVENT CAS:8052-41-3 RTECS #:WJ8925000 Fraction by Wt: 17% OSHA PEL:500 Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:ACUTE: PRIMARY EYE AND SKIN IRRITANT WITH CONTACT. INHALATION: MAY CAUSE HEADACHE, DIZZINESS & NAUSEA. CHRONIC: NOT SUFFICIENT DATA, EXERCISE CARE, DO NOT USE ABOVE TLV. Effects of Overexposure:ACUTE: PRIMARY EYE & SKIN IRRITANT WITH CONTACT. INH ALATION: MAY CAUSE HEADACHE, DIZZINESS & NAUSEA. CHRONIC: NOT SUFFICIENT DATA, EXERCISE CARE, DO NOT USE ABOVE TLV.

Medical Cond Aggravated by Exposure: PERSONS WITH A HISTORY OF SKIN AND RESPIRATORY DISORDERS MAY BE AT INCREASED RISK FROM EXPOSURE.

First Aid:INHALATION: REMOVE SUBJECT TO FRESH AIR. EYE: FLUSH WITH PLENTY OF WATER FOR 15 MINUTES. GET IMMEDIATE MEDICAL ATTENTION. SKIN: WASH WITH SOAP AND WATER.
INGESTION: DO NOT INDUCE VOMITING. GET IMMEDIA TE MEDICAL ATTENTION.

Flash Point Method:TCC Flash Point:104F/40C Lower Limits:0.8 Upper Limits:6.0 Extinguishing Media:FOAM - CO2 - DRY CHEMICAL Fire Fighting Procedures:WATER MAY BE USED TO COOL CONTAINERS TO PREVENT PRESSURE BUILD-UP OR AUTOIGNITION. Unusual Fire/Explosion Hazard:ISOLATE FROM HEAT, CLOSED CONTAINERS MAY EXPLODE IF EXPOSED TO EXTREME HEAT.

=======

Spill Release Procedures: REMOVE SOURCES OF IGNITION, SPRINKLE WITH ABSORBENT. FOG WITH WATER FLUSH OR SCRAPE INTO RETAINING AREA OR CONTAINER. INCREASE VENTILATION AVOID BREATHING VAPORS.

Handling and Storage Precautions: KEEP AWAY FROM HEAT, SPARKS, AND OPEN FLAME. USE ADEQUATE VENTILATION AVOID PROLONGED OR REPEATED CONTACT. KEEP CONTAINER CLOSED.

Ot

her Precautions: AVOID STATIC BUILD UP. KEEP AWAY FROM CHILDREN.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection:SELF CONTAINED BREATHING APPARATUS FOR CONCENTRATIONS ABOVE TLV Ventilation:LOCAL EXHAUST MECHANICAL EXHAUST FROM LOWER LEVELS. Protective Gloves:RUBBER GLOVES Eye Protection:CHEMICAL/SAFETY GOGGLES Other Protective Equipment:EYE BATH, SAFETY SHOWER, PROTECTIVE CREAM Supplemental Safety and Health NK

======== Physical/Chemica

I Properties =================

Boiling Pt:B.P. Text:215F,102C Decomp Temp:Decomp Text:ML Vapor Pres:2 Vapor Density:3.8 Spec Gravity:1.1 Evaporation Rate & amp; Reference:0.8 WATER Appearance and Odor:SOFT GREEN PASTE, SOLVENT COLOR Percent Volatiles by Volume:74

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZERS Stability Condition to Avoid:HEAT, SPARKS, OPEN FLAME AND FIRE Hazardous Decomposition Products:THERMAL DECOMPOSITION PRODUCES FUMES MAY YIELD CARBON MONOXIDE

Waste Disposal Methods:INCINERATE OR DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE, FEDERAL REGULATIONS. EMPTY CONTAINERS MAY RETAIN FUMES, DO NOTEXPOSE TO HEAT OR FLAME.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no man

ner whatsoever,

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.