

EVERSEAL MFG CO INC -- LIGHT GRAY GLOSS ALKYD ENAMEL 16376 -- 8010-00-298-2298
===== Product Identification =====

Product ID:LIGHT GRAY GLOSS ALKYD ENAMEL 16376

MSDS Date:04/11/1988

FSC:8010

NIIN:00-298-2298

MSDS Number: BHQSV

=== Responsible Party ===

Company Name:EVERSEAL MFG CO INC

Address:475 BROAD AVE

City:RIDGFIELD

State:NJ

ZIP:07657-2329

Country:US

Info Phone Num:201-943-4986 / FAX 201-94

3-1123

Emergency Phone Num:201-943-4986

CAGE:72988

=== Contractor Identification ===

Company Name:EVERSEAL MFG CO INC

Address:475 BROAD AVE

Box:City:RIDGFIELD

State:NJ

ZIP:07657-2329

Country:US

Phone:201-943-4986

CAGE:72988

===== Composition/Information on Ingredients =====

Ingred Name:RESIN

Fraction by Wt: 34%

OSHA PEL:NA

ACGIH TLV:NA

Ingred Name:TITANIUM DIOXIDE

CAS:13463-67-7

RTECS #:XR2275000

Fraction by Wt: 21%

OSHA PEL:15 MG/M3 TDUST

ACGIH TLV:10 MG/M3 TDUST; 9293

In

gred Name:MINERAL SPIRITS
VAPOR PRESSURE 2
CAS:64475-85-0
RTECS #:PY8240000
Fraction by Wt: 42%
OSHA PEL:120 PPM
ACGIH TLV:5 G/KG (ORAL)

Ingred Name:ADDITIVES
Fraction by Wt: 3%
OSHA PEL:NA
ACGIH TLV:NA

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Effects of Overexposure:INHALATION:DIZZINESS, NAUSEA & POSSIBLE
UNCONSCIOUSNESS.IRRITATION TO SKIN & EYES.

===== First Aid Measu
res =====

First Aid:INHALATION:REMOVE TO FRESH AIR.APPLY ARTIFICIAL RESPIRATION
IS NECESSARY.EYES:FLUSH W/WTR.SKIN:WASH W/SOAP & WTR. CONSULT
PHYSICIAN.

===== Fire Fighting Measures =====

Flash Point:105F 40.56C
Lower Limits:1.0
Extinguishing Media:FOAM, CARBON DIOXIDE, DRY CHEMICAL
Unusual Fire/Explosion Hazard:WATER NOT A SUITABLE EXTINGUISHING
MEDIUM.FIREFIGHTERS SHOULD WEAR SELF-CONTAINED BREATHING APPARATUS.

===== Accident Release Measures =====

Spill Release Procedures:REMOVE IGNITION SOURCES.ENSURE ADEQUATE
VENTILATION.ABSORB SMALL SPILLS ON DRY ABSORPTION MATERIAL.USE
SPARK-PROOF SCOOP FOR LARGER SPILLS.

===== Handling and Storage =====

Handling and Storage Precautions:AVOID EXCESSIVE HEAT & OPEN IGNITION
SOURCES.
Other Precautions:NPCA/HMIS RATING 3,2,O,H

===== Exposure Controls/Personal Protection =====

Respir

atory Protection:IF TLV MAY BE EXCEEDED USE CARTRIDGE MASK.

Ventilation:SUFFICIENT TO ENSURE LEL NOT ACHIEVED.

Protective Gloves:IMPERVIOUS

Eye Protection:GOGGLES

Other Protective Equipment:PROTECT SKIN W/CLOTHING OR BARRIER CREAM

Supplemental Safety and Health

NK

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:323 - 390F

Vapor Density:>AIR

Evaporation Rate & Reference: