

PRATT & LAMBERT, INC. -- LAC SPRAY CHEM RESIST WHITE 17875 ID799718 -- 8010-00-166-1667
===== Product Identification =====

Product ID:LAC SPRAY CHEM RESIST WHITE 17875 ID799718

MSDS Date:12/15/1988

FSC:8010

NIIN:00-166-1667

MSDS Number: BHRFX

=== Responsible Party ===

Company Name:PRATT & LAMBERT, INC.

Box:2153

City:WICHITA

State:KS

ZIP:67201

Country:US

Info Phone Num:316-733-1361

Emergency Phone

Num:316-733-1361

Preparer's Name:W.A. ELLISON

CAGE:FO127

=== Contractor Identification ===

Company Name:PRATT & LAMBERT, INC/BUFFALO, NY 14240

Box:22

CAGE:FO127

Company Name:PRATT AND LAMBERT INC

Address:Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

===== Composition/Information on Ingredients =====

Ingred Name:ISOBUTYL ACETATE

CAS:110-19-0

RTECS #:AI2025000

OSHA PEL:150 PPM 700 MG/CU.M.

ACGIH TLV:150 PPM 700 MG/CU.M.

EPA Rpt Qty:50

00 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:ISOPROPYL ALCOHOL
(VP 33 MM HG @ 20 DEG.C)
CAS:67-63-0
OSHA PEL:400 PPM 980 MG/CU.M.
ACGIH TLV:400 PPM 980 MG/CU.M.

Ingred Name:NITROCELLULOSE
CAS:9004-70-0
RTECS #:QW0970000
OSHA PEL:NONE ESTABLISHED
ACGIH TLV:NONE ESTABLISHED

Ingred Name:ISOBUTYL ALCOHOL (SARA III)
CAS:78-83-1
RTECS #:NP9625000
OSHA PEL:100 PPM
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:TITANIUM DIOXIDE
CAS:13463-67-7
RTECS #:XR22750
00
OSHA PEL:15 MG/M3 TDUST
ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:TOLUENE (SARA III)
CAS:108-88-3
RTECS #:XS5250000
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:VM&P NAPHTHA
(VP 40 MM HG @ 20 DEG.C)
CAS:8030-30-6
RTECS #:DE3030000
OSHA PEL:500 PPM
ACGIH TLV:300 PPM 1350 MG/CU.M

Ingred Name:DI-SEC-OCTYL PHTHALATE (DI-2-ETHYLHEXYL-PHTHALATE) (SARA III)
CAS:117-81-7
RTECS #:TI0350000
OSHA PEL:5 MG/M3/10 STEL
ACGIH

TLV:5 MG/M3; 9192
EPA Rpt Qty:100 LBS
DOT Rpt Qty:100 LBS

Ingred Name:N-HEPTANE
CAS:142-82-5
RTECS #:MI7700000
OSHA PEL:500 PPM/500 STEL
ACGIH TLV:400 PPM/500STEL;9293

Ingred Name:VOC. ORGANIC CMPD 5.7 LB/GL LESS WATER & NPRS* 684 G/L LESS
WATER VOC 32.7 LB/GAL SOLIDS 3924 G/L SOLIDS CALCULATED
RTECS #:9999999VO

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:YES IARC:NO OSHA
:NO

Health Hazards Acute and Chronic:SWALLOWING: GASTROINTESTINAL
IRRITATION, NAUSEA, VOMITING. ASPIRATION OF MATERIAL INTO LUNG MAY
CAUSE CHEMICAL PNEUMONITIS WHICH CAN BE FATAL. INHALATION: MAY
CAUSE NOSE, THROAT IRRITATION. EYE: MAY CAUSE EYE IRRITATION.
SKIN: PRIMARY SKIN IRRITANT. MAY CAUSE DEFATTING AND IRRITATION OF
THE SKIN.

Explanation of Carcinogenicity:DI(2-ETHYLHEXYL) PHTHALATE IS LISTED AS
A POTENTIAL CARCINOGEN BY THE NTP. OVEREXPOSURE TO TOLUENE MAY
CAU

SE LIVER DAMAG

Effects of Overexposure:PROLONGED AND REPEATED OCCUPATIONAL
OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM
DAMAGE. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND
INHALING THE CONTENTS MAY BE HARMFUL OR FATAL.

=====
===== First Aid Measures =====

First Aid:SWALLOWING: DO NOT INDUCE VOMITING. GET MED ATTN: INHALATION:
REMOVE TO FRESH AIR IMMED. IF BREATHING HAS STOPPED GIVE CPR. GET
MED ATTN: EYE: FLUSH
WITH LARGE AMOUNTS OF WATER LIFTING UPPER AND
LOWER LIDS FOR 15 MIN. SKIN: IMMEDIATELY FLUSH WITH WATER/REMOVE
CONTAMINATED CLOTHING AS WATER IS APPLIED CONSULT A M.D.

=====
===== Fire Fighting Measures =====

Flash Point:20F / -6.67C
Extinguishing Media:CLASS B FIRE EXTINGUISHERS TO EXTINGUISH FLAMMABLE
LIQUID FIRES. POLYMER FOAM IS PREFERRED FOR LARGE FIRES.
Fire Fighting Procedures:WEAR SELF CONTAINED BREATHING APPARATUS. USE
WATER TO COOL EXPOS

ED CONTAINERS TOPREVENT PRESSURE BUILD-UP AND
POSSIBLE EXPLOSION. FOG NOZZLE PREFERRED W/WATER.
Unusual Fire/Explosion Hazard:OVEREXPOSURE TO DECOMPOSITION PRODUCTS
MAY CAUSE HEALTH HAZARD. OBTAIN MEDICAL ATTENTION. WARNING
FLAMMABLE.

===== Accidental Release Measures =====

Spill Release Procedures:USE APPROPRIATE RESPIRATORS FOR SIZE OF SPILL.
ELIMINATE ALL IGNITION SOURCES. DIKE AND CONTAIN SPILLS WITH INERT
MATERIAL. TRANSFER AND RECOVER IN ME
TAL CONTAINERS. USE ONLY
NON-SPARKING TOOLS. DO NO T CONTAMINATE WATER SOURCES.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABOVE 95F. STORE LARGE
QUANTITIES IN COMPLIANCE WITH OSHA 29CFR1910.106.
Other Precautions:DO NOT TAKE INTERNALLY. CLOSE AFTER USE. DO NOT
RE-USE FOR ANY PURPOSE. CONTAINERS S/BE GROUNDED AND BONDED TO THE
RECEIVING CONTAINER. DO NOT WELD/BRAZE/CUT ONEMPTY CONTAINER. NEVER
USE PRESSU
RE TO E MPTY. DRUM NOT A PRESSURE VESSEL.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:GENERAL EXPOSURE MAY NOT REQUIRE THE USE OF
RESPIRATORY PROTECTION. RESTRICTED VENTILATION AREAS A NIOSH
APPROVED CHEMICAL CARTRIDGE RESPIRATOR MAY BE REQUIRED. CONDITIONS
SUCH AS SPRAYING A A MECHAN ICAL PREFILTER MAY BE REQUIRED.
CONFINED

Ventilation:GENERAL DILUTION AND LOCAL EXHAUSE VENTILATION TO MAINTAIN
HAZ SUBSTANCES BELOW LOWEST EXPO
SURE LIMITS.

Protective Gloves:SOLVENT IMPERMEABLE GLOVES

Eye Protection:SAFETY SPECTACLES

Other Protective Equipment:EYEWASH FACILITY, SAFETY SHOWER.

Supplemental Safety and Health

RESPIRATION PROTECTION CONTINUED: AREAS USE A NIOSH/MSHA APPROVED AIR
SUPPLIED RESPIRATOR.

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:180 TO 302F

Vapor Density:>AIR

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:82

=====

Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

STRONG ACIDS OR ALKALINE MATERIALS. OXIDIZING MATERIALS.

Stability Condition to Avoid: AVOID EXCESSIVE HEAT AND SOURCES OF IGNITION.

Hazardous Decomposition Products: WILL NOT OCCUR

Conditions to Avoid Polymerization: KEEP AWAY FROM HEAT SPARKS AND FLAME.

===== Disposal Considerations =====

Waste Disposal Methods: DISPOSE IAW FED/ST/LO LAWS. INCINERATE ONLY IN

EPA FACILITY. CONTAMINATED ABSORBANT MAY BE DISPOSED IN A HAZARDOUS WASTE LANDFILL. RCRA CLASSIFICATION D001.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.