

SEYMOUR OF SYCAMORE,INC -- BLK LACQ.ID:GPOOO17038,VINYL TOLUENE RESIN --
8010-00-290-6984

===== Product Identification =====

Product ID:BLK LACQ.ID:GPOOO17038,VINYL TOLUENE RESIN

MSDS Date:05/04/1988

FSC:8010

NIIN:00-290-6984

MSDS Number: BHRGS

=== Responsible Party ===

Company Name:SEYMOUR OF SYCAMORE,INC

Address:917 CROSBY AVE

City:SYCAMORE

State:IL

ZIP:60178-1343

Country:US

Info Phone Num:815-

895-9101

Emergency Phone Num:815-895-9101

CAGE:59581

=== Contractor Identification ===

Company Name:SEYMOUR OF SYCAMORE

Address:917 CROSBY AVE.

Box:City:SYCAMORE

State:IL

ZIP:60178-1343

Country:US

Phone:815-895-9101/800-255-3924

CAGE:59581

===== Composition/Information on Ingredients =====

Ingred Name:METHYLENE CHLORIDE (SARA III)

CAS:75-09-2

RTECS #:PA8050000

Fraction by Wt: 25.29%

OSHA PEL:500 PPM/C,1000; Z2

ACGIH TLV:50 PPM, A2; 9192

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 L

BS

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 18.99%

OSHA PEL:200 PPM/150 STEL

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:MINERAL SPIRITS

CAS:64475-85-0

RTECS #:PY8240000

Fraction by Wt: .48%

ACGIH TLV:100 PPM

Ingred Name:VM&P NAPHTHA (LIGROINE)

CAS:8032-32-4

RTECS #:OI6180000

Fraction by Wt: 7.55%

OSHA PEL:300 PPM/400 STEL

ACGIH TLV:300 PPM; 9192

Ingred Name:ETHYL ALCOHOL (ETHANOL)

CAS:64-17-5

RTECS #:KQ6300000

Fraction b

y Wt: 1.81%

OSHA PEL:1000 PPM

ACGIH TLV:1000 PPM; 9192

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS:1330-20-7

RTECS #:ZE2100000

Fraction by Wt: 1.55%

OSHA PEL:100 PPM/150 STEL

ACGIH TLV:100 PPM/150STEL;9192

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:2-BUTOXYETHANOL

CAS:111-76-2

RTECS #:KJ8575000

Fraction by Wt: 1.15%

OSHA PEL:S, 50 PPM

ACGIH TLV:S, 25 PPM; 9293

Ingred Name:PROPANE

CAS:74-98-6

RTECS #:TX2275000

Fraction by Wt: 18.0%

OSHA PEL:1000 PPM

ACGIH TLV:ASPHYXIAN; 9

Ingred Name:ISOBUTANE

CAS:75-28-5

Fraction by Wt: 12%

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Health Hazards Acute and Chronic:CAN CAUSE RESPORATORY SYSTEM IRRITATION.

Effects of Overexposure:EYE:IRRITATION UPON DIRECT CONTACT WITH SPRAY.

SKIN: MAY CAUSE DEFATTING, LEADING TO IRRITATION AND DERMATITIS. INHAL:

IRRITATION,HEADACHE,DIZZINESS,NAU SEA,POSS.UNCONSCIOUSNESS & ASPHYXIA

TION.INGESTION: IS UNLIKELY FROM AN AEROSOL CAN.

===== First Aid Measures =====

First Aid:EYE: IMMEDIATELY FLUSH W/PLENTY OF WATER FOR 15 MINUTES. GET MEDICAL ATTENTION. SKIN: WASH WITH SOAP AND WATER.

INHALATION: REMOVE PATIENT TO FRESH

AIR. IF BREATHING STOPS GIVE ARTIFICIALRESPIRATION. GET IMMEDIATE MEDICAL ATTENTION. INGESTION:

CALL A PHYSICIAN IMMEDIATELY.

===== Fire Fighting Measures =====

Flash Point:NA

Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, FOAM

Fire Fighting Procedures:WATER SPRAY MAYBE INEFFECTIVE.WATER MAYBE USED TO COOL CONTNR TO PREVENT BURSTNGIF WATER IS USED, FOG NOZZLES ARE PREFERABLE. WEAR GOGGLES & S.C.B.A.

Unusual Fire/Explosion Hazard:EXPOSURE TO HEAT MAY CAUSE BURSTING OR AEROSOL CAN.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION, AVOID BREATHING V

APORS, VENTILATE AREA. WIPE UP WITH INERT MATL & PLACE
IN APPROPRIATE CONTAINER.

=====
Handling and Storage
=====

Handling and Storage Precautions:DO NOT SOTE ABOVE 120F. EXPOSURE TO
HEAT OR PROLONG EXPOSURE TO SUN MAY CAUSE BURSTING.

Other Precautions:INTENTIAL MISUSE BY DILIBERATELY CONCENTRATING VAPORS
AND INHALING CONTENTS CAN BE HARMFUL OR FATAL.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:SE

LF CONTAINED BREATHING APPARATUS IS REQUIRED
FOR CONCENTRATIONS ABOVE TLV LIMITS.

Ventilation:SUFFICIENT TO PREVENT INHALATION OF SOLVENT VAPORS.

Protective Gloves:OPTIONAL

Eye Protection:ONLY IF SPRAY MIST MIGHT GET IN EYES.

Supplemental Safety and Health

NK

=====
Physical/Chemical Properties
=====

HCC:V2

Boiling Pt:B.P. Text:NA

Vapor Density:> AIR

Evaporation Rate & Reference:FASTER THAN ETHER

Percent Volatiles by Volume:85

=====
Stabilit
y and Reactivity Data
=====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING MATERIALS

Stability Condition to Avoid:DO NOT STORE ABOVE 120F. KEEP FROM SPARKS,
PILOT LIGHTS OR OPEN FLAME.

Hazardous Decomposition Products:CARBON DIOXIDE/MONOXIDE. FUMES MAY
ALSO CONTAIN HYDROGEN CHLORIDE VAPOR & TRACES OF PHOSGENE.

=====
Disposal Considerations
=====

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH FEDERAL, STATE, LOCAL
RE

GULATION.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.