

CHEMRAY COATING CORP -- VARNISH, SPAR, WATER-RESISTING -- 8010-00-160-5852

=====  
Product Identification  
=====

Product ID:VARNISH, SPAR, WATER-RESISTING

MSDS Date:01/01/1987

FSC:8010

NIIN:00-160-5852

MSDS Number: BHVZQ

=== Responsible Party ===

Company Name:CHEMRAY COATING CORP

Address:209 N MICHIGAN AVE

City:KENILWORTH

State:NJ

ZIP:07033

Country:US

Info Phone Num:201-245-1111

Emergency Phone Num:

800-424-9300 (CHEMTREC)

CAGE:33832

=== Contractor Identification ===

Company Name:CHEMRAY COATING CORP

Address:209 N MICHIGAN AVE

Box:City:KENILWORTH

State:NJ

ZIP:07033

Country:US

Phone:201-245-1111

CAGE:33832

=====  
Composition/Information on Ingredients  
=====

Ingred Name:RULE 66 MINERAL SPIRITS

CAS:64475-85-0

RTECS #:PY8240000

Fraction by Wt: 45%

ACGIH TLV:200 PPM

=====  
Hazards Identification  
=====

Routes of Entry: Inhalation:YES Skin:NO

Ingestion:NO

Health Hazards Acute and Chronic:OVEREXPOSURE-NAUSEA, HEADACHE, DIZZINESS CAUSED BY OVER INHALATION. HIGH VAPOR CONCENTRATIONS (>1000 PPM) ARE IRRITATING TO THE EYES AND RESPIRATORY TRACT, ARE ANESTHETIC, AND MAY HAVE OTHER CENTRAL N ERVOUS SYSTEM EFFECTS. Effects of Overexposure:OVEREXPOSURE-NAUSEA, HEADACHE, DIZZINESS CAUSED BY OVER INHALATION. HIGH VAPOR CONCENTRATIONS (>1000 PPM) ARE IRRITATING TO THE EYES AND RESPIRATORY TRACT, ARE ANESTHETIC, AND MAY H

AVE OTHER CENTRAL N ERVOUS SYSTEM EFFECTS.

Medical Cond Aggravated by Exposure:NONE GENERALLY KNOWN.

===== First Aid Measures =====

First Aid:EYE CONTACT: FLUSH WITH WATER 15 MINUTES OR UNTIL IRRITATION SUBSIDES. IF IRRITATION PERSISTS, CALL PHYSICIAN. SKIN CONTACT: REMOVE CONTAMINATED CLOTHING AND WASH THOROUGHLY WITH SOAP AND WATER. INHAL ATION: IF OVERCOME BY VAPORS REMOVE TO FRESH AIR, CALL PHYSICIAN. INGESTION: DO NOT INDUCE VOMITING, CALL PHYSICIAN.

===== Fire Fighting Measures =====

Flash Point Method:SCC

Flash Point:103 F/40 C

Lower Limits:0.9

Upper Limits:7

Extinguishing Media:CARBON DIOXIDE, FOAM, WATER FOG OR DRY CHEMICAL.

Fire Fighting Procedures:USE AIR SUPPLIED BREATHING EQUIPMENT. COOL ENCLOSED CONTAINERS WITH WATER SPRAY. AVOID BREATHING VAPORS OR FUMES.

Unusual Fire/Explosion Hazard:IF LEAK OR SPILL HAS IGNITED, USE WATER SPRAY TO DISPERSE THE VAPORS FROM FIRE FIGHTERS.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL IGNITION SOURCES. KEEP FROM HEAT, SPARKS AND OPEN FLAME. ADD ABSORBENT (SAND, EARTH, SAWDUST) TO SPILL. VENTILATE AREA (OPEN WINDOWS, DOORS). LARGE SPILL: KEEP FROM ENTERING SEWERS/WATERCOU RSES BY DIKING. ADVISE AUTHORITIES IF DOES ENTER.

===== Handling and Storage =====

Handling and Storage Precautions:STORE AWAY FROM IGNITION

SOURCES, KEEP

IN COOL, DRY, WELL VENTILATED AREAS. AVOID DIRECT SUNLIGHT AND EXTREME TEMPERATURES, HOT OR COLD.

Other Precautions:AVOID EYE, SKIN CONTACT, INHALATION &/OR INGESTION OF MISTS, SPRAY OR VAPORS. AVOID BREATHING SANDING OR BLASTING DUST.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE HYDROCARBON VAPOR CANISTER OR SUPPLIED AIR RESPIRATOR IN CONFINED AREAS.

Ventilation:LOCAL EXHAUST: FACE VELOCITY 60FPM. SPECIAL: USE ONLY

W/ADEQUATE VENTILATION. MECHANICAL: USE EXPLOSION PROOF EQUIPMENT.

Protective Gloves:CHEMICAL RESISTANT.

Eye Protection:SPLASH GOGGLES OR FACE SHIELD.

Other Protective Equipment:USE CHEMICAL RESISTANT APRON OR CLOTHING.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:308F,153C

Vapor Pres: