

CHEMTRONICS,INC NOW,JET RESEARCH -- H AGENT SIMULANT VIAL,DMS,(SEE SUPP DATA) --  
6910-00-106-4800

===== Product Identification =====

Product ID:H AGENT SIMULANT VIAL,DMS,(SEE SUPP DATA)

MSDS Date:01/01/1987

FSC:6910

NIIN:00-106-4800

Kit Part:Y

MSDS Number: BHWFK

=== Responsible Party ===

Company Name:CHEMTRONICS,INC NOW,JET RESEARCH

Address:180 OLD BEE TREE RD

City:SWANNANOA

State:NC

ZIP:28778

Cou

ntry:US

Info Phone Num:704-298-7941

Emergency Phone Num:704-298-7941

CAGE:KO082

=== Contractor Identification ===

Company Name:CHEMTRONICS INC

Address:180 OLD BEE TREE RD

Box:City:SWANNANOA

State:NC

ZIP:28778-3409

Country:US

Phone:NOT LISTED IN PHONE DIRECTORY

CAGE:60737

Company Name:CHEMTRONICS,INC NOW JET RESEARCH(NO LONGER MFR)

Address:180 OLD BEE TREE ROAD

Box:City:SWANNANOA

State:NC

ZIP:28778

Country:US

Phone:703-298-7941

CAGE:KO082

===== Composition/Information on Ingredients ==

=====

Ingred Name: DIMETHYL SULFATE (SARA III)

CAS: 77-78-1

RTECS #: WS8225000

Other REC Limits: N/K

OSHA PEL: S, 1 PPM

ACGIH TLV: S, 0.1 PPM, A2; 9293

EPA Rpt Qty: 100 LBS

DOT Rpt Qty: 100 LBS

===== Hazards Identification =====

LD50 LC50 Mixture: N/K

Reports of Carcinogenicity: NTP: YES IARC: YES OSHA: NO

Health Hazards Acute and Chronic: DELAYED EFFECTS. SEVERE DAMAGE TO RESPIRATORY TRACT. SEVERE EYE INJURY FROM VAPORS. CORROSIVE TO AND PENETRATES SKIN

Explanation of Carcinogenicity: DIMETHYL SULFATE: SUSP HUM CARC/KNOWN ANIM CARC (NTP, 1989). INADEQ EVID FOR CARC IN HUM; SUFF EVID FOR CARC IN (SEE SUPP)

Effects of Overexposure: DELAYED EFFECTS. EYES: SEVERE INJURY FROM VAPORS. SKIN: CORROSIVE TO AND PENETRATES SKIN. INGESTION: N/K . INHALATION: PAINFUL COUGH. SEVERE DAMAGE TO RESPIRATORY TRACT.

Medical Cond Aggravated by Exposure: N/K

===== First Aid Measures =====

First Aid: EYES: IMMEDIATELY FLUSH FOR

15 MINUTES WITH WATER.

SKIN: WASH WITH WATER. APPLY ICE PACK. INGESTION: GIVE MILK. DO NOT INDUCE VOMITING. INHALATION: MOVE TO FRESH AIR. ARTIFICIAL RESPIRATION IF NECESSARY. CONSULT PHYSICIAN IN ALL INSTANCES OF CONTACT.

===== Fire Fighting Measures =====

Flash Point Method: TCC

Flash Point: 84.4C, 183F

Lower Limits: N/K

Upper Limits: N/K

Extinguishing Media: FOAM, DRY CHEMICAL, CO\*2 OR WATER.

Fire Fighting Procedures: SCBA REQUIRED.

Unusual Fire/Expl

osion Hazard:MIXTURES OF DIMETHYL SULFATE AND  
CONCENTRATED AMMONIA CAN EXPLODE.

===== Accidental Release Measures =====

Spill Release Procedures:WEAR ORGANIC RESPIRATOR,GLOVES AND CLOTHING  
DURING CLEAN-UP.COVER SPILLS WITH SODA ASH AND WATER SPRAY.LET  
STAND 24 HOURS.WASH AWAY WITH WATER.

Neutralizing Agent:N/K

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE WITH AQUEOUS AMMONIA OR  
N  
EAR GASEOUS AMMONIA.KEEP AWAY FROM AREAS OF HIGH HEAT.  
Other Precautions:KEEP CONTAINERS,VIALS AND AMPOULES CLOSED OR SEALED.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:MESA APPROVED RESPIRATOR WITH ORGANIC VAPOR  
CARTRIDGE.

Ventilation:CONSULT LOCAL SAFETY/HEALTH AUTHORITIES IF ADDITIONAL  
GUIDANCE IS NEEDED .LOCAL-FUME HOOD:100 LFM MINIMUM.

Protective Gloves:RUBBER

Eye Protection:SPLASH PROOF GOGGLES.

Other Protective Equipment:RUBBERIZEE  
D COVERALLS,RUBBER BOOTS AND SCBA  
FOR EMERGENCIES.

Work Hygienic Practices:N/K

Supplemental Safety and Health

BP:DECOMPOSES @ 188C,370.4F.EXPLAN OF CARC:ANIMALS (IARC,1987).ACGIH  
A2=SUSP HUM CARC (1990).KNOWN TO CAUSE CANCER (CAL PROP 65  
1988).WASTE DISP METHODS:WITH ALKALI SCRUBBER OBSERVING LOCAL,STATE  
AND FEDERAL REGULATIONS.TLV:1 PPM OR 5 MG/M3.PART NO:(M72-A1  
TRAINING SET).

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:SEE  
SUPP

Melt/Freeze Pt:M.P/F.P Text:N/K

Decomp Temp:Decomp Text:188C,370.4F

Vapor Pres:0.54 MMHG

Vapor Density:4.35,AIR=1

Spec Gravity:1.328 (WATER=1)

Evaporation Rate & Reference:>1 (BUTYL ACETATE=1)

Solubility in Water:SLIGHT

Appearance and Odor:CLEAR WHITE WITH NO CHARACTERISTIC ODOR.

Percent Volatiles by Volume:100

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
AMMONIA AND METAL SALTS.

Stability Condition to Avoid:N/K

Hazar

dous Decomposition Products:POSSIBLY SULFUR DIOXIDE,HYDROGEN  
SULFIDE,CARBON DIOXIDE,CARBON MONOXIDE.

Conditions to Avoid Polymerization:WILL NOT OCCUR.

===== Disposal Considerations =====

Waste Disposal Methods:DISP MUST BE IAW FEDERAL,STATE & LOCAL  
REGULATIONS.COORDINATION W/ SUPPORTING INSTALLATION/MACOM ENVIRON  
COORDINATION BEFORE DISP IS REC TO DETERMINE APPROP DISP METHODS  
.MIX UNCONTAM MATL W/ SO LV & BURN IN INCINERATOR W/ AFTER BURNER

(SEE SUP)

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
partic  
ular situation.