View NSN Online: https://aerobasegroup.de/nsn/5330-01-047-7962

MFR UNKNOWN/DEFENSE INDUSTRIAL SUPPLY CTR PROCURED -- GASKET: PART NO. UNKNOWN -- 5330-01-047-7962

MSDS Date:03/11/1989 FSC:5330 NIIN:01-047-7962 MSDS Number: BHWKB === Responsible Party === Company Name: MFR UNKNOWN/DEFENSE INDUSTRIAL SUPPLY CTR PROCURED Address:700 ROBBINS AVENUE City:PHILADELPHIA State:PA ZIP:19111-5096 Country:US Info Phone Num:215-697-2000 Pr eparer's Name:DOD HMIS/DGSC-SSH CAGE: JO772 === Contractor Identification === Company Name: DEFENSE INDUSTRIAL SUPPLY CENTER Address:NONE Box:City:PHILADELPHIA State:PA ZIP:19111-5096 Country:US Phone:215-697-2000 CAGE:14153 Company Name: MFR UNKNOWN/DEFENSE INDUSTRIAL SUPPLY CTR PROCURED Address:700 ROBBINS AVENUE Box:3990 City:PHILADELPHIA State:PA ZIP:19111-5096 Country:US Phone:215-697-2000 CAGE: JO772

Ingred Name: ASBESTOS, C

HRYSOTILE CAS:12001-29-5 RTECS #:CI6478500 **OSHA PEL:0.2 FIBERS/CC** ACGIH TLV:2 FIBERS/CC; A1;9192 Ingred Name: ASBESTOS OVERALL COMPOSITION RTECS #:9999992Z Ingred Name: GENERIC "MSDS". SPECIFIC ASBESTOS TYPE NOT KNOWN. ONE CITED IS ASSUMED. INFORMATION BASED ON SEGMENT "M" OF "DLSC TIR" RTECS #:9999999ZZ Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES Hea Ith Hazards Acute and Chronic: ACUTE: NO ACUTE EFFECTS ARE KNOWN; CHRONIC: DUST FROM ABRASIVE ACTIONS(EG. CUTTING, MACHINING, FILING, ETC.) MAY CONTAIN ASBESTOS FIBERS. CHRONIC OVEREXPOSURE TO AIRBORNE FIBERS MAY LEAD TO ASBESTOSIS & MESOTHELIOMA. SMOKINGCOMBINED W/FIBER INHALATION GREATLY INCREASES LUNG CANCER RISK! Explanation of Carcinogenicity: OVEREXPOSURE TO AIRBORNE CONCENTRATIONS OF ASBESTOS MAY LEAD TO ASBESTOSIS AND MESOTHELIOMA. Effects of Overexpo sure:INHAL: INHALATION OF AIRBORNE DUST CONTAINING ASBESTOS FIBERS ON REPEATED EXPOSURE MAY CAUSE OR CAN LEAD TO ASBESTOSIS / MESOTHELIOMA; SKIN: N/K; EYE: POTENTIAL IRRITATION FROM AIRBORNE DUST; INGEST: N/K. Medical Cond Aggravated by Exposure: RESPIRATORY DEFICIENCIES DUE TO REPEATED INHALATION OF AIRBORNE FIBERS. First Aid:INHAL: REMOVE TO FRESH AIR. OBTAIN MEDICAL ADVICE; SKIN: WASH EXPOSED AR EA WITH SOAP & WATER; EYE: FLOOD W/ WATER. IF IRRITATION OCCURS, GET MEDICAL ATTN; INGEST: CONSULT A PHYSICIAN; OTHER: CHANGE CLOTHING AS REQUIRED TO AVOIDCARRYING DUST PARTICLES INTO OTHER AREAS

Flash Point:NONE

Extinguishing Media:MATERIAL IS NOT FLAMMABLE ; USE MEDIA APPROPRIATE FOR SURROUNDING FIRE.

Fire Fighting Procedures: COMBUSTION PRODUCTS OF THIS MATERIAL MAY BE TOXIC. USE A SELF-CONTAIN

ED BREATHING APPARATUS WHEN FIGHTING FIRES INVOLVING CHEMICAL PRODUCTS. Unusual Fire/Explosion Hazard:NONE KNOWN

Spill Release Procedures:USE PROPER PERSONAL PROTECTION. VACUUM OR WET CLEAN IF DUST IS INVOLVED. ANY VACUUM SYSTEM SHOULD BE EQUIPPED W/ AN OUTLET "HEPA" FILTER TO PREVENT REINTRODUCING ASBESTOS FIBERS TO THE ATMOSPHERE.

Handling

and Storage Precautions:HANDLE IN A MATTER TO MINIMIZE
FORMATION OR RETENTION OF AIRBORNE DUST. USE PROPER PERSONAL
PROTECTION FOR TASK AT HAND. CHECK W/YOUR SAFETY OFFICE!!!
Other Precautions:AS MANUFACTURED, LOCKED-IN ASBESTOS DOES NOT PRESENT
A HAZARD. ONLY WHEN THE ITEM IS SUBJECTED TO ABRASIVE ACTIONS &
DUST IS GENERATED, THEN ASBESTOS FIBERS MAY BE RELEASED & BECOME
AIRBORNE.

Respiratory Protection

:IF EXPOSURES EXCEED ESTABLISHED LIMITS, A

NIOSH/MSHA APPROVED RESPIRATOR FOR ASBESTOS SHOULD BE USED. CONSULT YOUR SAFETY OFFICE/IH PERSONNEL FOR GUIDANCE FOR THE TASK AT HAND.

Ventilation:LOCAL EXHAUST IS RECOMMENDED IN SITUATIONS WHERE DUST IS GENERATED BY ABRASIVE ACTIONS, ABRASION OR OTHER MEANS.

Protective Gloves: AS REQUIRED FOR TASK AT HAND.

Eye Protection:SAFETY GLASSES W/SIDE SHIELDS OR GOGGLES

Other Protective Equipment: AS REQUIRED FOR TASK AT HAND, AND THE G

UIDANCE SET FORTH BY YOUR SAFETY OFFICE OR IH PERSONNEL

Work Hygienic Practices: DONOT INHALE DUST CREATED BY ABRADING ACTIONS. USE FULL PROTECTION AGAINST AIRBORNE FIBERS. AVOID AIRBORNE DUST CREATION

Supplemental Safety and Health

GENERIC "MSDS" CREATED FOR "NSN" IDENTIFIED BY "DISC" AS CONTAINING ASBESTOS. WHEN A MANUFACTURER'S SPECIFIC "MSDS" IS PROVIDED FOR MATERIAL PROCURED UNDER THIS NSN, THIS GENERIC "MSDS" WILL BE REMOVED.

======== Physical/Chemical

Properties ==============

HCC:T6

Evaporation Rate & amp; Reference:NONE Solubility in Water:NOT SOLUBLE Appearance and Odor:MANUFACTURED COMMODITY DESCRIBED BY LOGISTICS: "ITEM-NAME" Percent Volatiles by Volume:NONE

Stability Indicator/Materials to Avoid:YES NONE KNOWN Stability Condition to Avoid:NONE KNOWN

Waste Disposal Methods:DUST SHOULD BE HANDLED AS A HAZARDOUS AIR POLLUTANT I/A/W 40CFR61 SUBPART "M" PERTAINING TO ASBESTOS. USE LANDFILLS APPROVED FOR ASBESTOS DISPOSAL. NOTE IF ITEM UNDER CONSIDERATION FOR DISPOSAL IS "FRIABLE OR NON-FRIABLE".

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurat e and

disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.