

DEXSIL CHEMICAL CORP -- CLOR-D-TECT 1000; AMPULE 1 (GRAY-YELLOW DOT)

=====
MSDS Safety Information
=====

FSC: 6850
NIIN: 01-316-9398
MSDS Date: 05/17/1995
MSDS Num: BHWYN
Product ID: CLOR-D-TECT 1000; AMPULE 1 (GRAY-YELLOW DOT)
MFN: 01
Kit Part: Y
Responsible Party
Cage: 65297
Name: DEXSIL CHEMICAL CORP
Address: 1 HAMDEN P
ARK DR
City: HAMDEN CT 06514-3150
Info Phone Number: 203-288-3509
Emergency Phone Number: 203-288-3509, CHEMTREC 800-424-9300
Preparer's Name: UNKNOWN
Proprietary Ind: Y
Review Ind: Y
Published: Y

=====
Contractor Summary
=====

Cage: 65297
Name: DEXSIL CORP
Address: 1 HAMDEN PARK DR
City: HAMDEN CT 06514-3150
Phone: 203-288-3509

=====
Item Description Information
=====

Item Manager: S9G
Item Name: DETECTION KIT,CHLORINATED SOLVENTS
Unit of Issue: BG
Quantitative Expression: 00000000020EA
UI Container Qty: 1
Type of Container: BAG

=====
Ingredients
=====

Name: *** PROPRIETARY ***

=====

=====
Health Hazards Data
=====

LD50 LC50 Mixture: UNKNOWN
Route Of Entry Inds - Inhalation: YES
Skin: NO
Ingestion: YES
Carcinogenicity Inds - NTP: NO
IARC: NO
OSHA: NO

Effects of Exposure: CORROSIVE TO ALL TISSUES. EXPOSURE TO THIS PRODUCT MAY HAVE SERIOUS ADVERSE HEALTH EFFECTS. THE USER SHOULD RECOGNIZE THAT THIS PRODUCT CAN CAUSE SEVERE INJURY AND EVEN DEATH, ESPECIALLY IF IMPROPERLY HANDLED OR THE KNOWN DANGERS OF USE ARE NOT HEEDDED.

Signs And Symptions Of Overexposure: IRRITATION AND BURNS.

Medical Cond Aggravated By Exposure: NONE SPECIFIED BY MANUFACTURER.

First Aid: EYES- FLUSH WITH LARGE AMOUNTS OF WATER 15 MINUTES. SEEK MEDICAL ATTENTION. SKIN- FLUSH WITH LARGE AMOUNTS OF WATER. USE SOAP AND WATER TO WASH AWAY ORGANIC COMPONENTS. INHALATION- REMOVE TO FRESH AIR .

Handling and Disposal

Spill Release Procedures: COVER WITH DRY SODA ASH OR SALT. STORE IN A WELL VENTILATED AREA AWAY FROM MOISTURE.

Waste Disposal Methods: DISPOSE OF IN ACCORDANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL ENVIRONMENTAL REGULATIONS. TEST TUBE 1- CONTAINS REACTED OIL SAMPLE AND ORGANIC LIQUID. DISPOSE OF AS AN ORGANIC WASTE.

Handling And Storage Precautions: STORE KITS IN A COOL, DRY PLACE. CHECK EXPIRATION DATE PRIOR TO PERFORMING TEST.

Other Precautions: THIS DOCUMENT IS INTENDED AS A GUIDE TO THE APPROPRIATE PRECAUTIONARY HANDLING OF THE MATERIAL BY A PERSON TRAINED IN CHEMICAL HANDLING. THESE CHEMICALS MAY INTERACT WITH OTHER SUBSTANCES. THIS PRODUCT CAN CAUSE SEVERE INJURY AND EVEN DEATH

Fire and Explosion Hazard Information

Flash Point Text: 212F,100C

Extinguishing Media: DO NOT USE WATER ON A SODIUM FIRE. USE DRY CHEMICAL, FOAM, CARBON DIOXIDE.

Fire Fighting Procedures: DO NOT USE WATER. WEAR SCBA. A

VOID BREATHING SODIUM

OXIDE FUMES WHICH WILL FORM ON COMBUSTION.

Unusual Fire/Explosion Hazard: SODIUM WILL FORM FLAMMABLE HYDORGEN GAS AND SODIUM OXIDE WHEN IN CONTACT WITH MOISTURE. CONTAINER MAY EXPLODE.

=====
Control Measures

=====
Respiratory Protection: DEPENDING ON USAGE, RESPIRATORS MUST BE USED TO AVOID CONTACT WITH MATERIAL OR BREATHING CHEMICAL VAPORS/FUMES.

Ventilation: PERFROM

TEST ONLY IN A WELL VENTILATED AREA.

Protective Gloves: ALWAYS WEAR RUBBER GLOVES.

Eye Protection: SAFETY GLASSES.

Other Protective Equipment: WEAR APPROPRIATE SAFETY EQUIPMENT WHEN PERFORMING TEST ON SITE.

Work Hygienic Practices: NONE SPECIFIED BY MANUFACTURER.

Supplemental Safety and Health: KEY1 HCC R2. THIS MSDS IS FOR AMPULE 1: CONTAINS 60 MG SODIUM. KIT CONSISTS OF FOUR AMPULES, SAMPLING SYRINGE, TISSUE WIPES, PLASTIC FILTERATION FUNNEL AND TWO TEST TUBES. FOR AMPULE 2, 3, 4, 5 AND A

QU
EUOUS SOLUTION, SEE PNI B, C, D, E, AND F; UNDER SAME NSN.

=====
Physical/Chemical Properties

HCC: R2

Spec Gravity: 0.86

Viscosity: NOT RELEVANT

Solubility in Water: REACTS

Appearance and Odor: GRAY WITH NO ODOR.

Percent Volatiles by Volume: NONE

=====
Reactivity Data

Stability Ind

icator: YES

Stability Condition To Avoid: DO NOT EXPOSE BROKEN SODIUM AMPULE TO MOISTURE.

Materials To Avoid: STRONG OXIDIZERS.

Hazardous Decomposition Products: SODIUM WILL FORM HYDROGEN AND SODIUM OXIDE WHEN MOISTURE IS PRESENT.

Hazardous Polymerization Indicator: NO

Conditions To Avoid Polymerization: NOT RELEVANT

=====
Toxicological Information

=====
Ecological Information
=====

=====
MSDS Transport Information
=====

=====
Regulatory Information
=====

=====
Other Information
=====

=====
Transportation Information
=====

Responsible Party Cage: 65297
Trans ID NO: 124856
Product ID: CLOR-D-TECT 1000; AMPULE 1 (GRAY-YELLOW DOT)
MSDS Prepared Date: 05/17/1995
Review Date: 07/20/1995
MFN: 1
Net Unit Weight: 60MG,SODIUM
Multiple KIT Number: 0
Kit Part IND: Y
Review IND: Y
Unit Of Issue: BG
Container QTY: 1
Type Of Container: BAG
Additional Data: TOTAL KIT SHOULD BE SHIPPED AS
FOLLOWS: PSN-ALKALI METAL
DISPERSIONS; HAZARD CLASS-4.3; UN 1391; PAC KING GROUP 1. SEE THIS NSN AND PN
IND B, C, D, E, AND F FOR ADDITIONAL INFORMATION OF OTHER COMPONENTS IN THIS
KIT.

=====
Detail DOT Information
=====

DOT PSN Code: NCP
DOT Proper Shipping Name: SODIUM
Hazard Class: 4.3
UN ID Num: UN1428
DOT Packaging Group: I
Label: DANGEROUS WHEN WET
Special Provision: A7,A8,A19,A20,B9,

B48,B68,N34,T15,T29,T46
Non Bulk Pack: 211
Bulk Pack: 244
Max Qty Pass: FORBIDDEN
Max Qty Cargo: 15 KG
Vessel Stow Req: D

=====
Detail IMO Information
=====

IMO PSN Code: NNN
IMO Proper Shipping Name: SODIUM
IMDG Page Number: 4360
UN Number: 1428
UN Hazard Class: 4.3
IMO Packaging Group: I
Subsidiary Risk Label: -
EMS Number: 4.3-01
MED First Aid Guide NUM: 705
=====

=====
Detail IATA Information
=====

IATA PSN Code: WJD
IATA UN ID Num: 1428
IATA Proper Shipping Name: SODIUM
IATA UN Class: 4.3
IATA Label: DANGEROUS WHEN WET
UN Packing Group: I
Packing Note Passenger: FORB
Max Quant Pass: FORB
Max Quant Cargo: 15KG
Packaging Note Cargo: 412
Exceptions: A1
=====

=====
Detail AFI Information
=====

AFI P
SN Code: WJD
AFI Symbols: 0
AFI Proper Shipping Name: SODIUM
AFI Hazard Class: 4.3
AFI UN ID NUM: UN1428
AFI Packing Group: I
Special Provisions: P3, A7, A8, A19, A20, N34
Back Pack Reference: A8.4
=====

=====
HAZCOM Label
=====

Product ID: CLOR-D-TECT 1000; AMPULE 1 (GRAY-YELLOW DOT)
Cage: 65297
Company Name: DEXSIL CORP
Street: 1 HAMDEN PARK DR
City: HAMDEN CT
Zipcode: 06514-3150
Health Emergency Pho

ne: 203-288-3509, CHEMTREC 800-424-9300

Label Required IND: Y

Date Of Label Review: 08/02/1995

Status Code: C

Label Date: 08/02/1995

Year Procured: 1992

Origination Code: F

Eye Protection IND: YES

Skin Protection IND: YES

Signal Word: WARNING

Respiratory Protection IND: YES

Health Hazard: Slight

Contact Hazard: Moderate

Fire Hazard: Moderate

Reactivity Hazard: Moderate

Hazard And Precautions: CORROSIVE TO ALL TISSUES. EXPOSURE TO THIS PRODUCT MAY HAVE SERIOUS ADVERSE HEALTH EFFECTS. THE USER S

HOULD RECOGNIZE THAT THIS

PRODUCT CAN CAUSE SEVERE INJURY AND EVEN DEATH, ESPECIALLY IF IMPROPERLY HANDLED OR THE KNOWN DANGERS OF USE ARE NOT HEDED. STORE KITS IN A COOL, DRY PLACE. CHECK EXPIRATION DATE PRIOR TO PERFORMING TEST. FIRST AID: EYES- FLUSH WITH LARGE AMOUNTS OF WATER 15 MINUTES. SEE K MEDICAL ATTENTION. SKIN- FLUSH WITH LARGE AMOUNTS OF WATER. USE SOAP AND WATER TO WASH AWAY ORGANIC COMPONENTS. INHALATION- REMOVE TO FRESH AIR. TARGET ORGANS: SKIN, EYES.

=====

=====

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever expressly or implied warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Department of Defense nor any person or persons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.