

PRATT & LAMBERT, INC. -- PRIMER COATING LAC RUST INHIBITING ID725202 -- 8010-00-597-7854
===== Product Identification =====

Product ID:PRIMER COATING LAC RUST INHIBITING ID725202

MSDS Date:06/27/1988

FSC:8010

NIIN:00-597-7854

MSDS Number: BHWZV

=== Responsible Party ===

Company Name:PRATT & LAMBERT, INC.

Box:2153

City:WICHITA

State:KS

ZIP:67201

Country:US

Info Phone Num:316-733-1361

Emergency Pho

ne Num:316-733-1361

Preparer's Name:W.A. ELLISON

CAGE:FO127

=== Contractor Identification ===

Company Name:PRATT & LAMBERT, INC/BUFFALO, NY 14240

Box:22

CAGE:FO127

Company Name:PRATT AND LAMBERT INC

Address:Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

===== Composition/Information on Ingredients =====

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

OSHA PEL:200 PPM/150 STEL

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:VM&P NAPHTHA
(VAPOR PRESSURE 40 MM HG @ 20C)
CAS:8030-30-6
RTECS #:DE3030000
OSHA PEL:500 PPM
ACGIH TLV:300 PPM 1350 MG/CU.M

Ingred Name:ISOPROPYL ALCOHOL (SARA III)
CAS:67-63-0
RTECS #:NT8050000
OSHA PEL:400 PPM/500 STEL
ACGIH TLV:400 PPM/500STEL;9192

Ingred Name:DI-SEC-OCTYL PHTHALATE (DI-2-ETHYLHEXYL-PHTHALATE) (SARA III)
CAS:117-81-7
RTECS #:TI0350000
OSHA PEL:5 MG/M3/10 STEL
ACGIH TLV:5 MG/M3; 9192
EPA Rpt Qty:100 LBS
DOT Rpt Qty:100
LBS

Ingred Name:ISOBUTYL ACETATE
CAS:110-19-0
OSHA PEL:150 PPM 700 MG/CU.M
ACGIH TLV:150 PPM 700 MG/CU.M
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:ZINC CHROMATE
CAS:13530-65-9
RTECS #:GB3290000
OSHA PEL:0.1 MG/M3 (CRO3)
ACGIH TLV:0.01MG/M3(CR)A1;9192

Ingred Name:SILICA, CRYSTALLINE - QUARTZ
CAS:14808-60-7
RTECS #:VV7330000
OSHA PEL:SEE TABLE Z3
ACGIH TLV:0.1 MG/M3 RDUST;9293

Ingred Name:TALC (CONTAINING NO ASBESTOS)
CAS:14807-96-6
RTECS #:WW2710000
OSHA PEL:2 MG/M3 RDUST
ACGIH TL

V:2 MG/M3 RDUST; 9192

Ingred Name:SILICA, CRYSTALLINE - CRISTOBALITE
CAS:14464-46-1
RTECS #:VV7325000
OSHA PEL:SEE TABLE Z3
ACGIH TLV:0.05 MG/M3 RDUST9293

Ingred Name:ISOPROPYL ALCOHOL (SARA III)
CAS:67-63-0
RTECS #:NT8050000
OSHA PEL:400 PPM/500 STEL
ACGIH TLV:400 PPM/500STEL;9192

Ingred Name:NITROCELLULOSE
CAS:9004-70-0
RTECS #:QW0970000
OSHA PEL:NONE ESTABLISHED
ACGIH TLV:NONE ESTABLISHED

Ingred Name:ALIPHATIC HYDROCARBON
(VP 12 MM HG @ 20 DEG.C)
CAS:64742-89-8
OSHA PEL:NO
N ESTABLISHED
ACGIH TLV:NON ESTABLISHED

Ingred Name:VOC. ORGANIC CMPD 4.80 LB/GL LESS WATER & NPRS* 576 G/L
LESSWATER VOC 16.2 LB/GAL SOLIDS 1944 G/L SOLIDS CALCULATED.
RTECS #:9999999VO

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO
Health Hazards Acute and Chronic:INGEST: CAN CAUSE GASTROINTESTINAL
IRRI/NAUSEA/VOMIT. ASPIRATION OF MATERIAL MAYCAUSE
CHEM
PNEUMONITIS. INHALE: NOSE & THROAT IRRI. IN HIGH CONCENTRATIONS MAY
CAUSE CENTRAL NERVOUS SYSTEM DEPRESSION CHAR BY
HEADACHES/DIZZINESS/NAUSEA &CONFUSION. EYES: MAY CAUSE EYE IRRI.
SKIN: MAY CAUSE DEFATTING AND IRRITATION.
Explanation of Carcinogenicity:DI(2-ETHYLHEXYL) PHTHALATE-POTENTIAL
CARCINOGEN BY NTP. ZINC CHROMATE-POTENTIAL CARCINOGEN BY IARC.
Effects of Overexposure:REPEATED EXPOSURE TO CRYSTALLINE SILICA MAY
CAUSE PNEUMOCONIOSIS. OCCUPATIONAL OVEREXPOS

URE TO SOLVENTS ASSOC

W/PERM BRAIN & NERVOUS SYSTEM DAMAGE. INTENTIONALMISUSE BY CONCENTRATING/INHALING CONT MA Y BE HARMFUL/FATAL. INSOLUBLE CHROMATESMAY CAUSE LUNG CANCER. TOLUENE FOUND TO CAUSE KIDNEY/SPLEEN DAMAGE IN LAB ANIMAL

Medical Cond Aggravated by Exposure:PRE-EXISTING RESPIRATORY CONDITIONS MAY BE AGGRAVATED BY EXPOSURE TO CRYSTALLINE SILICA.

=====
First Aid Measures
=====

First Aid:INGESTION: DO NOT INDUCE VOMITING, GET M
ED ATTN. INHALATION:

REMOVE TO FRESH AIRIF BREATHING HAS STOPPED GIVE CPR. GET MED ATTN.
EYES: FLUSH W/WATER FOR 15 MIN.LIFTING UPPER/LOWER LIDS. GET MED
ATTN. SKIN: REMOVE CONTAMINATED CLOTHING. WASHAFFECTED AREAS.
OBTAIN MED ATTN IF IRRITATIONS PERSIST. TREATMENT REQ FOR OVER-
EXPOSURE SHOULD BE DIRECTED AT CONTROL OF SYMPTOMS & THE CLINICAL
CONDITIONS.

=====
Fire Fighting Measures
=====

Flash Point:20 F/-6.67 C

Extinguishing Media:F

OR CLASS B FIRE EXTINGUISHERS. POLYMER FOAM IS
PREFERRED FOR LARGE FIRES.

Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS. WATER
TO COOL CONT TO PREVENT POSSIBLE AUTO-IGNITION OR EXPLOSION. IF
WATER IS USED, FOG NOZZLES ARE PREFERABLE.

Unusual Fire/Explosion Hazard:DURING EMERG CONDITIONS, OVEREXPOSURE TO
DECOMP PRODUCT MAY CAUSE HEALTH HAZARDSSYMPTOMS MAY NOT BE
IMMEDIATELY APPARENT. GET MEDICAL ATTN. WARNING! FLAMMABLE.

=====
Accidental Relea
se Measures
=====

Spill Release Procedures:ELIM ALL IGNITION SOURCES. DIKE/CONTAIN SPILL
WITHINERT MATERIAL. TRANSFER LIQ/ABSORBENT INTO COVER-ED METAL
CONTAINER FOR RECOVERY/DISPOSAL. USE ONLYNON-SPARKING TOOLS.
PREVENT CONTAMINATION OF SEWER STREAMS/GROUNDWATERS W/SPILLED
MATERIAL/ABSORBENT.

=====
Handling and Storage
=====

Handling and Storage Precautions:DO NOT STORE ABOVE 95 F. STORE LARGE
QUANTITIES INCOMPLIANCE WITH O

SHA 29CFR1910.106.

Other Precautions:DO NOT BREATHE SANDING DUST OR REUSE EMPTY CONTAINER.
DO NOT TAKE INTERNALLY. BOND/GROUND CONTAIN TO THE RECEIVING
CONTAINER. DO NOT WELD/BRAZE OR CUT CONTAINNEVER USE PRESSURE TO
EMPTY. DRUM IS NOT A PRESSURE VESSEL. CLOSE AFTER USING.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:WELL VENTILATE AREA. RESP NOT REQ. RESTRICTED
VENT-NIOSH CHEMICAL CARTRIDGE MAY BE REQ. IF SPRAYING, MECH
PREFI

LTER MAY BE REQ. IF TLV ARE EXCEEDED, USE A PROPRFITTED
NIOSH/MSHA RESP W/APPROP PROTECTI ON FACTOR. SEE OSHA 29 CFR
1910.134.

Ventilation:PROVIDE DILUTED/LOCAL EXHAUST TO KEEP CONCENTRATE OF
HAZARD-OUS INGREDIENT(S) BELOW EXPOSURE LIMIT STANDARDS.

Protective Gloves:SOLVENT IMPERMEABLE GLOVES.

Eye Protection:WEAR SAFETY SPECTACLES.

Other Protective Equipment:NOT LIKELY TO BE NEEDED.

Work Hygienic Practices:WASH WITH SOAP AND WATER HANDS/FACE THOROUGHLY
BEFORE EATING OR DRINKING.

S

upplemental Safety and Health

NK

=====
===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:180 F/302 F

Vapor Density:> AIR

Evaporation Rate & Reference:SLOWER THAN ETHER.

Percent Volatiles by Volume:70

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG ACIDS OR ALKALINE MATERIALS.

Stability Condition to Avoid:AVOID EXCESSIVE HEAT AND SOURCES OF
IGNITION.

Hazardous Decomposition Products

:BURNING, ALSO WHEN HEATED BY

CUT/WELDING WILL PRODUCE SMOKE/CARBON MONOXIDE/DIOXIDE AND OXIDES
OF NITROGEN & CHROMIUM.

Conditions to Avoid Polymerization:KEEP AWAY FROM HEAT, SPARKS AND
FLAME.

=====
===== Disposal Considerations =====

Waste Disposal Methods:INCINERATE ONLY IN EPA PERMITTED FACILITY.

DISPOSEONLY IN ACCORD W/FED, STATE & LOCAL REGS. DO NOT INCINERATE
CLOSED CONTAINER. OBSERVE PRECAUTIONS FOR DISPOSAL OF FLAMMABLE
MATERIALS. CO

NTAMINATED ABSORBENT, DISPOSE IN A HAZARDOUS
WASTELANDFILL.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility fo
r the suitability of this information to their
particular situation.