

SEYMOUR OF SYCAMORE, INC. -- AEROSOL VINYL TOLUENE ALKYD RESIN ID:GP1551 --
8010-00-616-9181

===== Product Identification =====

Product ID:AEROSOL VINYL TOLUENE ALKYD RESIN ID:GP1551

MSDS Date:09/21/1988

FSC:8010

NIIN:00-616-9181

MSDS Number: BHXBW

=== Responsible Party ===

Company Name:SEYMOUR OF SYCAMORE, INC.

Address:917 CROSBY AVE.

City:SYCAMORE

State:IL

ZIP:60178

Country:US

Info Phone Num:81

5-895-9101

Emergency Phone Num:815-895-9101

CAGE:59581

=== Contractor Identification ===

Company Name:SEYMOUR OF SYCAMORE

Address:917 CROSBY AVE.

Box:City:SYCAMORE

State:IL

ZIP:60178-1343

Country:US

Phone:815-895-9101/800-255-3924

CAGE:59581

===== Composition/Information on Ingredients =====

Ingred Name:TITANIUM DIOXIDE

CAS:13463-67-7

RTECS #:XR2275000

Fraction by Wt: 6.43%

OSHA PEL:15 MG/M3 TDUST

ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:METHYLENE CHLORIDE (SARA III)

CAS:7

5-09-2
RTECS #:PA8050000
Fraction by Wt: 22.94%
OSHA PEL:500 PPM/C,1000; Z2
ACGIH TLV:50 PPM, A2; 9192
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:TOLUENE (SARA III)
CAS:108-88-3
RTECS #:XS5250000
Fraction by Wt: 15.08%
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:MINERAL SPIRITS
CAS:64475-85-0
RTECS #:PY8240000
Fraction by Wt: .63%
ACGIH TLV:100 PPM

Ingred Name:VARNISH MAKERS & PAINTER
CAS:8032-32-4
Fraction by Wt: 9.16%
OS
HA PEL:1350 MG/M3
ACGIH TLV:300 PPM

Ingred Name:ETHYL ALCOHOL (ETHANOL)
CAS:64-17-5
RTECS #:KQ6300000
Fraction by Wt: 1.76%
OSHA PEL:1000 PPM
ACGIH TLV:1000 PPM; 9192

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)
CAS:1330-20-7
RTECS #:ZE2100000
Fraction by Wt: 1.94%
OSHA PEL:100 PPM/150 STEL
ACGIH TLV:100 PPM/150STEL;9192
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:2-BUTOXYETHANOL
CAS:111-76-2
RTECS #:KJ8575000
Fraction by Wt: 1.12%
OSHA PEL:S, 50 PPM
ACGIH TLV:S, 25 PPM; 9293

Ingred Name:PROPANE
CAS:74-98-6
RTECS #:TX2275000
Fraction by Wt: 15.0%
OSHA PEL:1000 PPM
ACGIH TLV:ASPHYXIAN; 9192

Ingred Name:ISOBUTANE
CAS:75-28-5
Fraction by Wt: 10%

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Health Hazards Acute and Chronic:EXPOSURE TO SOLVENT VAPORS
CONCENTRATION EXCEEDING THE ESTABLISHED TLV CAN CAUSE RESPORATORY
SYSTEM IRRITATION.
Effects of Overexposure:INHAL:IRRITATION,HEADACH
E,DIZZINESS,NAUSEA,
POSSIBLE UNCONSCIOUSNESS & ASPHYXIA- TION. EYE: IRRITATION
ESPECIALLY UPON DIRECT CONTACE WITH THE SPRAY. SKIN: PROLONGED OR
REPEATED LIQUID CONTACT MAY CAU SE DEFATTING OF THE SKIN, LEADING
TO DERMATITIS. INGST: IS UNLIKELY IF INGESTED CALL A PHYSICIAN
IMMEDIATE

=====
First Aid Measures
=====

First Aid:INHAL: REMOVE TO FRESH AIR. IF BREATHING STOPS, BEGIN
ARTIFICIAL RESPIRATION. SKIN: WASH WITH SOAP AND WATER. E
YE:
IMMEDIATELY FLUSH EYES WITH PLENTY OF WATER FOR 15 MINUTES, GET
MEDICAL ATTENTION. IN GEST: CALL A PHYSICIAN IMMEDIATELY

=====
Fire Fighting Measures
=====

Flash Point Method:TOC
Flash Point:10
Extinguishing Media:USE CARBON DIOXIDE, DRY CHEMICAL OR FOAM
Fire Fighting Procedures:EXPOSURE TO HEAT MAY CAUSE BURSTING OF AEROSOL
CAN.
Unusual Fire/Explosion Hazard:WATER SPRAY MAY BE INEFFECTIVE, WATER MAY
BE USED TO COOL CONTAINERS TO PREVENT BU

RSTING. IF WATER IS USE,
FOG NOZZLES ARE PREFERABLE. WEAR GOGGLES & S.C.B.A

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OFIGNITION, AVOID BREATHING VAPORS, VENTILATE AREA. WIPE UP W/INERT MATERIALS & PLACE IN APPROPRIATE CONTAINER.

===== Handling and Storage =====

Handling and Storage Precautions:DONOT STORE ABOVE 120F. EXPOSURE TO HEAT OR PRO- LONGED EXPOSURE TO SUN MAY CAUSE BURSTING.

Other Precautions:USE ONLY AS DIRECTED. INTENTIONAL MISUSE BY DILIBERATELY CONCENTRATING VAPORS AND INHALING CONTENTS CAN BE HARMFUL OR FATAL.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:AVOID CONTINUOUS BREATING OF VAPORS AND SPRAY MIST. A SELF CONTAINED BREATHING APPARATUS REQUIRED FOR CONCENTRATIONS ABOVE TLV LIMITS.

Ventilation:ADEQUATE VENTILATION, SUFFICIENT TO PREVETN INHALATION OF SOLVENT VAPORS.

Protective G

loves:OPTIONAL

Eye Protection:SEE BELOW

Other Protective Equipment:EYE PROTECTION: ONLY UNDER CONDITIONS WHERE SPRAY MIST MIGHT GET INTO EYES.

Supplemental Safety and Health

NK

===== Physical/Chemical Properties =====

HCC:V3

Boiling Pt:B.P. Text:NA

Vapor Density:> AIR

Evaporation Rate & Reference:FASTER THAN ETHER

Percent Volatiles by Volume:85

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

ST

STRONG OXIDIZING MATERIALS

Stability Condition to Avoid: DONOT STORE ABOVE 120F. KEEP FROM SPARKS,
PILOT LIGHTS OR OPEN FLAMES.

Hazardous Decomposition Products: MAY PRODUCE FUMES W/HEATED TO
DECOMPOSITION. FUMES MAY CONTN CARBON DIOXIDE &/OR CARBN MONOXIDE.

===== Disposal Considerations =====

Waste Disposal Methods: DONOT INCINERATE AEROSOL, DISPOSE OF IN
ACCORDANCE W/FEDERAL, STATE, AND LOCAL REGULATIONS. DONOT PLACE
AEROSOL CANS IN HOME COMPACTOR. D
O NOT PUNCTURE CAN.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to thei
r
particular situation.