

PRATT & LAMBERT, INC. -- ENAMEL ALKYD GLOSS GREEN 14064 ID742412 -- 8010-00-582-4667
===== Product Identification =====

Product ID:ENAMEL ALKYD GLOSS GREEN 14064 ID742412

MSDS Date:03/23/1988

FSC:8010

NIIN:00-582-4667

MSDS Number: BHXNP

=== Responsible Party ===

Company Name:PRATT & LAMBERT, INC.

Box:2153

City:WICHITA

State:KS

ZIP:67201

Country:US

Info Phone Num:316-733-1361

Emergency Phone Num:3

16-733-1361

Preparer's Name:W.A. ELLISON

CAGE:FO127

=== Contractor Identification ===

Company Name:PRATT & LAMBERT, INC/BUFFALO, NY 14240

Box:22

CAGE:FO127

Company Name:PRATT AND LAMBERT INC

Address:Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

===== Composition/Information on Ingredients =====

Ingred Name:VM&P NAPHTHA (LIGROINE)

CAS:8032-32-4

RTECS #:OI6180000

OSHA PEL:300 PPM/400 STEL

ACGIH TLV:300 PPM; 9192

Ingred Name:MINERAL SP

IRITS (VAPOR PRESSURE 2 MM HG @ 20 C)

CAS:64742-88-7

OSHA PEL:500 PPM 2950 MG/CU.M

ACGIH TLV:100 PPM 525 MG/CU.M

Ingred Name:CARBON BLACK

CAS:1333-86-4

RTECS #:FF5800000

OSHA PEL:3.5 MG/M3

ACGIH TLV:3.5 MG/M3; 9192

Ingred Name:VOC. ORGANIC CMPD 4.0 LB/GAL LESS WATER & NPRS* 480 G/L

LESS WATER VOC. 8.0 LB/GAL SOLIDS 1272 G/L SOLIDS CALCU

RTECS #:9999999VO

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Health

h Hazards Acute and Chronic:EYE: MAY CAUSE EYE IRRITATION SKIN:

MAY CAUSE DEFATTING AND IRRITATION OF THE SKIN. INHALATION: NOSE OR THROAT IRRITATION. INGESTION: GASTROINTESTINAL IRRITATION, NAUSEA, AND VOMITING. ASPIRATION OF MATERIAL INTO LUNG MAY CAUSE CHEMICALPNEUMONITIS.

Effects of Overexposure:REPORTS HAVE ASSOCIATED PROLONGED AND REPEATED OCCUPATIONL OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE. INTENTIONAL MISUSE BY DELIBERATELY

CONCENTRATING AND INHALING THE CONTENTS MAY BE HARMFUL OR FATAL.

===== First Aid Measures =====

First Aid:EYE: WASH WITH WATER AT LEAST 15 MINUTES. INHALATION: REMOVE TO FRESH AIR IMMEDIATELY, IF BREATHING HAS STOPPED GIVE CPR. GET MEDICAL ATTENTION. INGESTION: DO NOT INDUCE VOMITING. SKIN: REMOVE CONTAMINATED CLOTHING. WASH AFFECTED AREA WITH SOAP AND WATER. OBTAIN MEDICAL ATTENTION IF IRRITATION PERSISTS. NOTE TO PHYSICIAN ANY

TREATMENT SHOULD BE DIRECTED AT THE CONTROL OF SYMPTOMS AND THE CLN COND

===== Fire Fighting Measures =====

Flash Point:>102F/38.89C

Extinguishing Media:CLASS B FIRE EXTINGUISHERS DESIGNED TO EXTINGUISH FLAMMABLE LIQUID FIRES. POLYMER FOAM IS PREFERRED FOR LARGE FIRES.

Fire Fighting Procedures:WEAR SELF CONTAINED BREATHING APPARATUS. WATER MAY BE INEFFECTIVE. BUT MAY BE USED TO PREVENT PRESSURE BUILD-UP. IF WATER IS USED, FOG NOZZLES ARE PREFERRED

ERABLE.

Unusual Fire/Explosion Hazard:KEEP CONTAINERS TIGHTLY CLOSED ISOLATE FROM HEAT. CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT.

===== Accidental Release Measures =====

Spill Release Procedures:ELIMATE ALL IGNITION SOURCES. DIKE AND CONTAIN SPILL WITH INERT MATER. TRANSFER IN METAL CONTAINERS FOR RECOVERY/DISPOSAL. USE ONLY NONSPARKING TOOLS. PREVENT CONTAMINATION OF SEWERS, STREAMS, OR GROUNDWATER FROM SPILLED MATERIAL/
USED ABSORBENT.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABOVE 95F. STORE LARGE QUANTITIES IN COMPLIANCE WITH OSHA 29CFR1910.106. RCRA CLASSIFICATION D0001.

Other Precautions:DO NOT REUSE FOR ANY PURPOSE. CONTAINERS SHOULD BE GROUNDED AND BONDED TO THE RECEIVING CONTAINER. DO NOT WELD, BRAZE, CUT CONTAINER. NEVER USE PRESSURE TO EMPTY. CLOSE CONTAINER AFTER EACH USE. DO NOT TAKE INTERNALLY.

=====

==== Exposure Controls/Personal Protection =====

Respiratory Protection:IN RESTRICTED VENTILATION AREAS A NIOSH APPROVED CHEMICAL CARTRIDGE RESPIRATOR MAY BE REQUIRED. IN CONFINED AREAS USE A NIOSH/MSHA APPROVED AIR SUPPLIED RESPIRATOR. IF SPRAYING A RESPIRATOR MAY BE REQUIRED.

Ventilation:GENERAL DILUTION AND LOCAL EXHAUST VENTILATION IN SUFFICIENT VOLUME AND PATTERN TO KEEP HAZARD BELOW LOWEST EXPOSURE LIMITS

Protective Gloves:SOLVENT IMPERMEABLE GLOVES

Eye Protection:

WEAR SAFETY SPECTACLES

Other Protective Equipment:NOT LIKELY TO BE NEEDED

Supplemental Safety and Health

NK

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:280F-388F

Vapor Density:>AIR

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:61

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG ACIDS OF ALKALINE MATERIALS

Stability Condition to Avoid:AVOID

EXCESSIVE HEAT AND SOURCES OF
IGNITION.

Hazardous Decomposition Products: BURNING, INCLUDING WHEN HEATED BY
WELDING OR CUTTING, WILL PRODUCE SMOKE, CARBON MONOXIDE AND CARBON
DIOXIDE.

Conditions to Avoid Polymerization: KEEP AWAY FROM HEAT SPARKS AND FLAME

===== Disposal Considerations =====

Waste Disposal Methods: DISPOSE IAW FEDERAL, STATE AND LOCAL LAWS.
INCINERATE ONLY IN EPA FACILITY. DO NOT INCINERATE
CLOSED CONTAINERS. OBSERVE PRECAUTION
FOR DISPOSAL OF FLAMMABLE
MATERIALS. CONTAMINATED ABSORBANT MAY BE DISPOSED OF IN A
HAZARDOUS WASTE LANDFILL.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent profes
sional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.