

CSD, INC. -- THINNER PAINT, MINERAL SPIRITS REG ODORLESS -- 8010-00-837-7969

=====
Product Identification
=====

Product ID:THINNER PAINT, MINERAL SPIRITS REG ODORLESS

MSDS Date:09/15/1986

FSC:8010

NIIN:00-837-7969

MSDS Number: BHXPJ

=== Responsible Party ===

Company Name:CSD, INC.

Address:#5 HACKBERRY

City:CUT & SHOOT

State:TX

ZIP:77302

Country:US

Info Phone Num:409-756-1065

Emergency Phone Num:4

09-756-1065

CAGE:KO005

=== Contractor Identification ===

Company Name:CSD INC. (PRE 1985 NAME: MATHEWS, INC)

Address:420 SEABOARD DRIVE

Box:City:MATTHEWS

State:NC

ZIP:28105-5073

Country:US

Phone:704-821-9822

CAGE:5W216

Company Name:CSD, INC.

Address:5 HACKBURY ST

Box:687

City:CONROE

State:TX

ZIP:77305

Country:US

Phone:409-756-1065

CAGE:KO005

=====
Composition/Information on Ingredients
=====

Ingred Name:C10-C11 PARAFFINS, CYCLOPARAFFINS AND AROMATICS

Fraction by Wt: 100%

===

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Effects of Overexposure:INHALATION OF HIGH VAPOR CONCENTRATIONS MAY
HAVE RESULTS RANGING FROM DIZZINESS,HEADACHES TO UNCONS.
PROLONGED/REPEATED LIQUID CONTACT WITH THE SKIN WILL DRY AND DEFAT
THE SKIN LEADING TO IRRITATION AND DERMATITIS

=====
First Aid Measures
=====

F
First Aid:IF OVERCOME BY VAPOR, REMOVE FROM EXPOSURE IMMEDIATELY. CALL
PHYSICIAN, IF BREATHING IS IRREGULAR OR STOPPED, START
RESUSCITATION, ADMINISTER OXYGEN. IF INGESTED, DO NOT INDUCE VOMIT, CALL
PHYSICIAN. IN CASE OF SKIN CONTACT, REMOVE ANY CONTAMINATED CLOTHING AND
WASH SKIN WITH SOAP AND WATER. IF SPLASHED INTO EYES, FLUSH EYES
WITH CLEAR WATER FOR 15 MINUTES OR UNTIL IRRITATION SUBSIDES.

=====
Fire Fighting Measures
=====

Flash Point Method:TCC
Flash
Point:128F
Lower Limits:0.9
Upper Limits:6.0
Extinguishing Media:FOAM, DRY CHEMICAL, CO2, OR WATER FOG OR SPRAY
Fire Fighting Procedures:USE AIR SUPPLIED BREATHING EQUIPMENT FOR ENCLOSED
AREAS. COOL EXPOSED CONTAINERS WITH WATER SPRAY, AVOID BREATHING
VAPORS OR FUMES.
Unusual Fire/Explosion Hazard:DO NOT MIX OR STORE WITH STRONG OXIDANTS
LIKE LIQUID CHLORINE OR CONCENTRATED OXYGEN. COMBUSTIBLE LIQUID

=====
Accidental Release Measures
=====

Spill Release Procedures:REMOVE ALL IGNITION SOURCES. KEEP PEOPLE AWAY.
RECOVER FREE LIQUID. ADD ABSORBENT (SAND, EARTH ETC), TO SPILL
AREA. AVOID BREATHING VAPORS. VENTILATE CONFINED SPACES. KEEP PETROLEUM
OUT OF SEWERS/WATERCOURSES BY DIKE/IMPOUNDING. ADVISE AUTHORITIES OF
ENTERING.

=====
Handling and Storage
=====

Handling and Storage Precautions:KEEP CONTAINER CLOSED WHEN NOT IN USE.
DO NOT HANDLE OR STORE NEAR HEAT, FLAME, STRONG OXIDANTS. ADEQUATE
VENTILATION

ATION REQUIRED. (EQUIV TO OUTDOORS).

Other Precautions:AVOID BREATHING VAPOR. AVOID PROLONGED/REPEATED CONTACT WITH SHIN. REMOVE CONTAMINATED CLOTHING. LAUNDER BEFORE REUSE REMOVE CONTAMINATED SHOES AND THOROUGHLY DRY BEFORE REUSE. WASH SKIN THOROUGHLY WITH SOAP AND WATER AFTER CONTACT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE HYDROCARBON VAPOR CANISTER OR SUPPLIED AIR RESPIRATORY PROTECTION IN CONFINED OR ENCLOSED SPACES IF NEEDED.

Ventilation:LOCAL FACE VELOCITY >60 FPM. USE ONLY W/ADEQUATE VENT. USE EXPLOSION PROOF EQUIPMENT NO SMOKING OR OPEN LIGHTS.

Protective Gloves:CHEMICAL RESISTANT GLOVES

Eye Protection:SPLASH GOGGLES OR FACE SHIELD

Other Protective Equipment:CHEMICAL-RESISTANT APRON RECOMMENDED

Supplemental Safety and Health

NK

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:354F/179C

Vapor Pres: