

AUFHAUSER BROTHERS CORPORATION -- FLUX COATED SILVER ALLOY -- 3439-00-956-4183

=====
Product Identification
=====

Product ID:FLUX COATED SILVER ALLOY

MSDS Date:08/29/1988

FSC:3439

NIIN:00-956-4183

MSDS Number: BHYDB

=== Responsible Party ===

Company Name:AUFHAUSER BROTHERS CORPORATION

Address:39 WEST MALL

City:PLAINVIEW

State:NY

ZIP:11803-4209

Country:US

Info Phone Num:516-694-8695

Emergency Phon

e Num:516-694-8695

CAGE:59401

=== Contractor Identification ===

Company Name:AUFHAUSER CORP

Address:39 WEST MALL

Box:City:PLAINVIEW

State:NY

ZIP:11803-4209

Country:US

Phone:212-757-6824/FAX: 516-694-8690

CAGE:59401

=====
Composition/Information on Ingredients
=====

Ingred Name:SILVER (SARA III)

CAS:7440-22-4

RTECS #:VW3500000

Fraction by Wt: 55-60%

Other REC Limits:NONE SPECIFIED

OSHA PEL:0.01 MG/M3

ACGIH TLV:0.1 MG/M3; 9192

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

Ingred Name:COP

PER (SARA III)
CAS:7440-50-8
RTECS #:GL5325000
Other REC Limits:NONE SPECIFIED
OSHA PEL:0.1MG/M3 FUME/1 DUST
ACGIH TLV:0.2MG/M3 FUME; 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:ZINC (SARA III)
CAS:7440-66-6
RTECS #:ZG8600000
Other REC Limits:NONE SPECIFIED
OSHA PEL:10 MG ZNO/M3
ACGIH TLV:10 MG ZNO/M3; 9192
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:NICKEL (SARA III)
CAS:7440-02-0
RTECS #:QR5950000
Other REC Limits:NONE SPECIFIED
OSHA PEL:1 MG/M3
ACGIH TLV:1 MG/M3;
9192

Ingred Name:CADMIUM (SARA III)
CAS:7440-43-9
RTECS #:EU9800000
Other REC Limits:NONE SPECIFIED
OSHA PEL:SEE 1910.1027
ACGIH TLV:0.01 MG/M3 DUST;9394
EPA Rpt Qty:10 LBS
DOT Rpt Qty:10 LBS

Ingred Name:TIN
CAS:7440-31-5
RTECS #:XP7320000
Other REC Limits:NONE SPECIFIED
OSHA PEL:2 MG/M3
ACGIH TLV:2 MG/M3; 9192

Ingred Name:POTASSIUM HYDROGEN FLUORIDE
CAS:7789-29-9
RTECS #:TS6650000
Other REC Limits:NONE SPECIFIED
OSHA PEL:2.5 MG/M3 (F)
ACGIH TLV:2.5 MG/M3 (F); 8990

Ingred Name:POTASSIUM TE

TRAFUOBORATE
CAS:14075-53-7
RTECS #:ED2800000
Other REC Limits:NONE SPECIFIED

Ingred Name:POTASSIUM BORATE
CAS:1332-77-0
Other REC Limits:NONE SPECIFIED

Ingred Name:POTASSIUM FLUORIDE
CAS:7789-23-3
RTECS #:TT0700000
Other REC Limits:NONE SPECIFIED
OSHA PEL:2.5 MG/M3 (F)
ACGIH TLV:2.5 MG/M3 (F); 8990

Ingred Name:BORIC ACID
CAS:10043-35-3
RTECS #:ED4550000
Other REC Limits:NONE SPECIFIED

Ingred Name:WATER
CAS:7732-18-5
RTECS #:ZC0110000
Other REC Limits:NONE SPECIFIED

=====
Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO
Health Hazards Acute and Chronic:FUMES AND GASES CAN BE DANGEROUS TO
YOUR HEALTH. ARC RAYS CAN INJURE EYES AND BURN SKIN. ELECTRIC SHOCK
CAN KILL. NOISE CAN DAMAGE HEARING.
Explanation of Carcinogenicity:NICKEL AND CADMIUM ARE LISTED UNDER IARC
AND NTP.
Effects of Overexposure:ACUTE:METALLIC TASTE,NAUSEA,TIGHTNESS OF
CHEST,
FEVER,DIZZINESS,DRYNESS,IRRITATION OF EYES,NOSE AND THROAT.
CHRONIC:EXCESSIVE LEVELS MAY CAUSE BRONQUIAL ASTHMA,LUNG FIBROSIS
AND PNEUMOCONIOSIS.
Medical Cond Aggravated by Exposure:AGGRAVATION OF EXISTING RESPIRATORY
OR ALLERGIC CONDITIONS.HIGHER LEVEL OF LUNG RELATED PROBLEMS AMONG
SMOKERS.

===== First Aid Measures =====

First Aid:REMOVE FROM EXPOSURE AND OBTAIN PROMPT MEDICAL ATTENTION. IF
NOT BREATHING,GIVE CPR/OXYGEN. EMPLOY FIRST

AID TECHNIQUES

RECOMMENDED BY AMERICAN RED CROSS.

===== Fire Fighting Measures =====

Extinguishing Media:AS APPROPRIATE FOR SURROUNDING FIRE.

Fire Fighting Procedures:FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA & FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE.

Unusual Fire/Explosion Hazard:FIRE OR EXCESSIVE HEAT MAY CAUSE PRODUCTION OF HAZARDOUS DECOMPOSITION PRODUCTS.

===== Accidental Release Measures =====

Spill Release Procedures:CLEAN UP ANY GRINDING DUST OR WASTE RESIDUE AND PLACE IN APPROPRIATE DISPOSAL CONTAINER.

===== Handling and Storage =====

Other Precautions:TRAIN WELDER TO KEEP HIS HEAD OUT OF THE FUMES.MONITOR AIR TO ENSURE ACCEPTABLE EXPOSURES.AVOID ELECTRICAL SHOCK BY MAINTAINING DRY WORK AREA. WELDING ARC CAN IGNITE COMBUSTIBLES AND FLAMMABLES.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:FUME RESPIRATOR OR AIR SUPPLIED RESPIRATOR IN CONFINED SPACES OR WHERE VENTILATION DOES NOT KEEP EXPOSURE BELOW TLV.

Ventilation:LOCAL EXHAUST TO KEEP BELOW TLV.

Protective Gloves:WELDER'S GLOVES.

Eye Protection:HELMET OR FACE SHIELD WITH FILTER LENS.

Other Protective Equipment:SUBSTANTIAL DARK CLOTH,ARM PROTECTOR,APRON,HAT AND SHOULDER PROTECTION.

Work Hygienic Practices:WASH HANDS THOROUGHLY BEFORE EATING,SMOKING OR

USING SANITARY FACILITIES.

Supplemental Safety and Health
NONE.

===== Physical/Chemical Properties =====

HCC:N1

Solubility in Water:INSOLUBLE

Appearance and Odor:METALLIC ROD OR WIRE.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
NONE.

Stability Condition to Avoid:NONE.

Hazardous Decomposition Products:FUMES OF METALS AND METAL OXIDES, HYDROFLUORIC ACID, FLUORIDES, CARBON MONOXIDE, CARBON DIOX

IDE,
OZONE, NITROGEN OXIDES.

===== Disposal Considerations =====

Waste Disposal Methods:CONSULT WITH YOUR LOCAL ENVIRONMENTAL OFFICER.DISPOSE OF FUMES,FLUX OR WELD GRINDING RESIDUE FROM THE WORK AREA OR FROM FILTERS IN ACCORDANCE WITH FEDERAL,STATE AND LOCAL ENVIRONMENTAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.