

EASTMAN KODAK COMPANY -- 817 8998 FLEXICOLOR AR DEV/REPL,PART B -- 6750-01-285-1767
===== Product Identification =====

Product ID:817 8998 FLEXICOLOR AR DEV/REPL,PART B

MSDS Date:08/03/1994

FSC:6750

NIIN:01-285-1767

Kit Part:Y

MSDS Number: BHZHL

=== Responsible Party ===

Company Name:EASTMAN KODAK COMPANY

Address:343 STATE STREET

City:ROCHESTER

State:NY

ZIP:14650

Country:US

Info Phone Num:716-722-

5151

Emergency Phone Num:716-722-5151

CAGE:19139

=== Contractor Identification ===

Company Name:EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST

Box:City:ROCHESTER

State:NY

ZIP:14650-1115

Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

Company Name:FULLER AND D ALBERT INC

Address:3170 CABBELL

Box:2706

City:FAIRFAX

State:VA

ZIP:22031-2302

Country:US

Phone:703-591-8000

CAGE:82960

===== Composition/Information on Ingredients =====

Ingred Name:WATER

CAS:

7732-18-5

RTECS #:ZC0110000

Fraction by Wt: 70 - 75%

Other REC Limits:NONE SPECIFIED

Ingred Name:HYDROXYLAMINE SULFATE

CAS:10039-54-0

RTECS #:NC5425000

Fraction by Wt: 25 - 30%

Other REC Limits:NONE SPECIFIED

=====
===== Hazards Identification =====

LD50 LC50 Mixture:LD50(ORAL,RAT):100-200MG/KG HYDOXYLAMINE

Routes of Entry: Inhalation:NO Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:TARGET ORGANS:EYES,
SKIN,

GASTROINTESTINAL TRACT. ACUTE- EYES:IRRITATION. SKIN:HARMFUL IF
ABSORBED THROUGH SKIN. CAUSES IRRITATION. MAY CAUSE ALLERGIC SKIN
REACTION. ORAL:HARMFUL IF INGESTED. INHALATI ON:LOW HAZARD FOR
RECOMMENDED HANDLING.CHRONIC- BLOOD DISORDERS.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:EYES, SKIN AND GASTROINTESTINAL TRACT
IRRITATION, ALLERGIC SKIN REACTION

Medical Cond Aggravated by Exposure:PERSONS WITH A HISTORY OF AILMENTS
OR WITH A PRE-EXISTING DI

SEASE INVOLVING EYES OR SKIN MAY BE AT
INCREASED RISK FROM EXPOSURE.

=====
===== First Aid Measures =====

First Aid:GET MEDICAL ATTENTION IF SYMPTOMS PERSIST. SKIN:IMMEDIATELY
FLUSH WITH WATER FOR AT LEAST 15 MINUTES WHILE REMOVING
CONTAMINATED CLOTHING. EYES:IMMEDIATELY FLUSH WITH WATER FOR AT
LEAST 15 MINUTES. HO LD EYELIDS OPEN. INHALED:REMOVE TO FRESHAIR.
ORAL:IF CONSCIOUS, INDUCE VOMITING IMMEDIATELY AS DIRECTED BY
MEDICAL PERSONNEL.

CALL A PHYSICIAN/POISON CONTROL CENTER
IMMEDIATELY.

=====
===== Fire Fighting Measures =====

Flash Point:NONE, NONCOMBUST

Extinguishing Media:WATER SPRAY, CARBON DIOXIDE, FOAM OR DRY CHEMICAL
FOR SURROUNDING FIRE. USE WATER SPRAY TO COOL FIRE EXPOSED
CONTAINERS.

Fire Fighting Procedures:WEAR PROTECTIVE CLOTHING AND NIOSH-APPROVED
SELF-CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard:SOLUTION CONTAINS A STRONG REDUCING
AGENT. DRIED PR

ODUCT RESIDUE CAN ACT AS A REDUCING AGENT. DRYING ON CLOTHING OR OTHER MATERIALS MAY CAUSE FIRE.

===== Accidental Release Measures =====

Spill Release Procedures:FLUSH TO SEWER WITH LARGE AMOUNT OF WATER. FOR LARGE SPILLS, ABSORB SPILL WITH VERMICULITE, THEN PLACE IN A CONTAINER FOR CHEMICAL WASTE. PREVENT RUNOFF FROM ENTERING DRAINS, SEWERS OR STREAMS.

Neutralizing Agent:SODIUM BICARBONATE

===== Handling and Storage =====
=====

Handling and Storage Precautions:STORE IN A COOL AREA. KEEP CONTAINERS TIGHTLY CLOSED. KEEP AWAY FROM INCOMPATIBLE MATERIALS.

Other Precautions:DO NOT GET IN EYES, ON SKIN/ON CLOTHING. WASH THOROUGHLY AFTER HANDLING. THE ROUTINE USE OF A NONALKALINE TYPE OF HAND CLEANER AND CLEANING OF WORKING SURFACES, GLOVES WILL REDUCE POSSIBILITY OF SKIN REACTION. KEEP OUT OF REACH OF CHILDREN.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT NORMALLY NEEDED IN CASE OF GOOD VENTILATION.

Ventilation:GOOD GENERAL VENTILATION IS SUFFICIENT FOR MOST CONDITIONS (10 ROOM VOLUMES PER HOUR).

Protective Gloves:NEOPRENE, NITRILE, OR NATURAL RUBBER

Eye Protection:SAFETY GLASSES WITH SIDE SHIELD/GOGGLES

Other Protective Equipment:EYE WASH STATION AND SAFETY SHOWER, WORK CLOTHING AND APRON AS REQUIRED.

Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. DO NOT WEAR CONTAMINATED CLOTHING OR FOOTWEAR.

Supplemental Safety and Health

KEY1:C1. THIS IS A KIT WITH THREE PARTS. THIS PART B IS TO BE USED WITH PART A & PART C FOR 1 GALLON OF WORKING SOLUTION. PART A HAS NSN: 6750-01-285-1766, CAT. NO.: 815 5194; PART C HAS NSN: 6750-01-285-1765, CAT. NO.: 818 3428.

===== Physical/Chemical Properties =====

HCC:C2

Boiling Pt:B.P. Text:>212F,>100C

Vapor Pres:18 @ 68F

Vapor Density:0.6

Spec Gravity:1.16

pH:3.0

Solubility in Water:COMPLETE

Appea

rance and Odor:COLORLESS LIQUID - ODORLESS
Percent Volatiles by Volume:70-75

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS, COMBUSTIBLE MATERIALS, HALOGENATED MATERIALS

Stability Condition to Avoid:STABLE; HOWEVER, MATERIAL IS SHOCK

SENSITIVE AND CAN DECOMPOSE ABOVE 110C (230F). AVOID HEATING ABOVE
ROOM TEMPERATURE.

Hazardous Decomposition Products:NITROGEN OXIDES (NOX), SULFUR DIOXIDE

=====

===== Disposal Considerations =====

Waste Disposal Methods:DISCHARGE, TREATMENT OR DISPOSAL MAY BE SUBJECT
TO NATIONAL, STATE OR LOCAL REGULATIONS. CONTRACT WITH A LICENSED
CHEMICAL DISPOSAL AGENCY. SINCE EMPTIED CONTAINERS RETAIN PRODUCT
RESIDUE, FOLLOW LABEL WARNINGS EVEN AFTER CONTAINER IS EMPTIED.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The U

nited States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.