View NSN Online: https://aerobasegroup.de/nsn/6520-00-782-0520

KERR MANUFACTURING COMPANY -- FORMATRAY LIQUID -- 6520-00-782-0520

======== Product Identification ===========

Product ID:FORMATRAY LIQUID

MSDS Date:04/25/1989

FSC:6520

NIIN:00-782-0520

MSDS Number: BJCQS === Responsible Party ===

Company Name: KERR MANUFACTURING COMPANY

Address:28200 WICK ROAD

City:ROMULUS

State:MI ZIP:48174

Info Phone Num:(313) 946-7800

Emergency Phone Num: (313) 946-7800

CAGE:EO529

=== Co

ntractor Identification ===

Company Name: KERR CORP

Address:1717 W COLLINS AVENUE

Box:City:ORANGE

State:CA

ZIP:92867-5422

Country:US

Phone:800-537-7187

CAGE:33339

Company Name: KERR MANUFACTURING COMPANY, DIVISION OF SYBRON COR

Address:28200 WICK ROAD

Box:City:ROMULUS

State:MI ZIP:48174 Country:US

Phone: (313) 946-7800

CAGE:EO529

====== Composition/Information on Ingredients ========

Ingred Name: METHYL METHACRYLATE (SARA III)

CAS:80-62-6

RTECS #:OZ5075000 Fraction by Wt: 99%

Other

OSHA PEL:100 PPM ACGIH TLV:100 PPM; 9192
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS
======================================
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:EYES: IRRITATION. SKIN: RASHES. INHALATION: HEADACHES, NAUSEA, DROWSINESS, & UNCONSCIOUSNESS. INGESTION: GASTRO-INTESTINAL DISTRESS. Explanation of Carcinogenicity:NONE
Effects of Overexposure:EYES: IRRITATION. SKIN: RASHES. INHALATION: HEADACHES, NAUSEA, DROWSINESS, & UNCONSCIOUSNESS. INGESTION: GASTRO-INTESTINAL DISTRESS.
Medical Cond Aggravated by Exposure:RASHES
======================================
First Aid:EYES: FLUSH W/WATER FOR 15 MINUTES. SKIN: WASH W/SOAP & WATER. INHALATION: MOVE TO FRESH AIR. ADMINISTER OXYGEN OR GIVE ARTIFICIAL RESPIRATION, AS REQUIRED. INGESTION: CALL PHYSICIAN.
======================================
re Fighting Measures =============
Flash Point:50F Lower Limits:1.7%
Upper Limits:8.2% Extinguishing Media:CO2, FOAM, DRY CHEMICALS, WATER FOG
Fire Fighting Procedures:FIGHT FIRES FROM SAFE DISTANCE. COOL EXPOSED MATERIAL W/COLD WATER SPRAY.
Unusual Fire/Explosion Hazard:SEALED CONTAINERS EXPOSED TO ELEVATED

Unusual Fire/Explosion Hazard:SEALED CONTAINERS EXPOSED TO ELEVATED TEMPERATURES MAY RUPTURE EXPLOSIVELY DUE TO POLYMERIZATION. VAPORS ARE >AIR & MAY TRAVEL.

======== Accidental Release Measures ==========

Spill Re

REC Limits:100 PPM

lea	se Procedures:EVACUATE AREA, ELIMINATE IGNITION SOURCES.
F	ABSORB SPILLS W/INERT MATERIAL & TRANSFER TO SUITABLE CONTAINER FOR
	DISPOSAL.

Handling and Storage Precautions:STORE IN A COOL, DARK PLACE. KEEP AWAY FROM IGNITION SOURCES.

Other Precautions:USE ACCORDING TO DIRECTIONS. USE GOOD PERSONAL HYGIENE.

====== Exposure Controls/Personal Protection ========

Respiratory Protection:WHEN VAPORS EX CEED TLV, SELF-CONTAINED BREATHING APPARATUS.

Ventilation:PROVIDE SUFFICIENT LOCAL EXHAUST VENTILATION TO KEEP