

NATIONAL AEROSOL PRODUCTS CO SUB OF GROW GROUP INC -- OBLITERATING COATING FOR
12-010 -- 8010-00-582-4743

===== Product Identification =====

Product ID:OBLITERATING COATING FOR 12-010

MSDS Date:01/01/1987

FSC:8010

NIIN:00-582-4743

MSDS Number: BJD SM

=== Responsible Party ===

Company Name:NATIONAL AEROSOL PRODUCTS CO SUB OF GROW GROUP INC

Address:2193 E. 14TH STREET

City:LOS ANGELES

State:CA

ZIP:9

0021

Country:US

Info Phone Num:213-627-2668

Emergency Phone Num:213-627-2668

CAGE:59986

=== Contractor Identification ===

Company Name:GROW GROUP INC DEVOE AND REYNOLDS CO DIV

Address:4000 DUPONT CIRCLE

Box:City:LOUISVILLE

State:KY

ZIP:40207-4802

Country:US

Phone:502-361-2536

CAGE:97758

Company Name:NATIONAL AEROSOL PRODUCTS CO SUB OF GROW GROUP INC

Address:2193 E 14TH STREET

Box:City:LOS ANGELES

State:CA

ZIP:90021-2843

Country:US

CAGE:59986

===== Composition/Information on Ingredients

=====

Ingred Name:TITANIUM DIOXIDE
CAS:13463-67-7
RTECS #:XR2275000
OSHA PEL:15 MG/M3 TDUST
ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:V.T. ALKYD

Ingred Name:ALIPHATIC HYDROCARBONS
ACGIH TLV:400 PPM

Ingred Name:N-BUTYL ALCOHOL (SARA III)
CAS:71-36-3
RTECS #:EO1400000
OSHA PEL:100 PPM
ACGIH TLV:S, C 50 PPM; 9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:METHYLENE CHLORIDE (SARA III)
CAS:75-09-2
RTECS #:PA8050000
OSHA PEL:500 PPM/C,1000; Z2
ACGIH TLV:50 PPM, A2; 9192
EP
A Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:BUTANE-PROPANE PROPELLANT
ACGIH TLV:1000 PPM

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Health Hazards Acute and Chronic:INHALATION: HEADACHE, NAUSEA, AND
DIZZINESS. SKIN CONTACT: PROLONGED OR REPEATED CONTACT MAY CAUSE
IRRITATION.
Effects of Overexposure:INHALATION: HEADACHE, NAUSEA AND DIZZINESS.
SKIN CONTACT: PROLONGED OR REPEATED CONTACT MAY CA

USE IRRITATION.

=====
===== First Aid Measures =====

First Aid:INHALATION: MOVE TO FRESH AIR. SKIN CONTACT: FLUSH WITH LARGE AMOUNTS OF WATER. REMOVE CONTAMINATED CLOTHING. EYE CONTACT: FLUSH WITH CLEAN WATER FOR AT LEAST 15 MINUTES.

=====
===== Fire Fighting Measures =====

Flash Point:NR

Extinguishing Media:WATER FOG, DRY CHEMICALS OR CO2.

Fire Fighting Procedures:USE AIR SUPPLIED EQUIPMENT FOR ENCLOSED AREAS.
COOL EXPO

SED CONTAINERS WITH WATER.

Unusual Fire/Explosion Hazard:KEEP AWAY FROM HEAT, SPARKS OR OPEN FLAME.

=====
===== Accidental Release Measures =====

Spill Release Procedures:AVOID BREATHING VAPORS, EXTINGUISH IGNITION SOURCES IN IMMEDIATE AREA. AVOID CONTACT WITH LIQUID.

=====
===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE AT ELEVATED TEMPERATURES.

Other Precautions:CLOSE CONTAINERS AFTER USE.

=====

==== Exposure Controls/Personal Protection =====

Respiratory Protection:ADEQUATE VENTILATION IS REQUIRED. IN CONFINED AREAS USE U.S. BUREAU OF MINES APPROVED RESPIRATOR DEVICE.

Ventilation:LOCAL EXHAUST: PROVIDE SUFFICIENT VENTILATION TO KEEP CONCENTRATION BELOW GIVEN TLV.

Protective Gloves:REQUIRED FOR PROLONGED/REPEATED CONTACT

Eye Protection:SOLVENT RESISTANT

Other Protective Equipment:NORMAL PROTECTIVE CLOTHING.

Supplemental Safety and Health

=====
===== Physical/

Chemical Properties =====

Boiling Pt:B.P. Text:176 TO 343F

Vapor Density:> (AIR=1)

Spec Gravity:1.120 (H2O=1)

Evaporation Rate & Reference:SLOWER THAN ETHER

Solubility in Water:SLIGHT

Appearance and Odor:LIQUID WITH TYPICAL PAINT ODOR.

Percent Volatiles by Volume:78.18

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

OXIDIZING MATERIALS, RUBBER SOFTENS.

Hazardous Decomposition Products:CARBON MONOXIDE AND CARBON DIOXIDE.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN CLOSED CONTAINERS AWAY FROM IGNITION SOURCES.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.